
# 4MP Flexible Intensifier® HD-TVI Bullet Camera with Junction Box, Wall/Ceiling Mount, Dual voltage



H4FB2M - 2.7~12mm motorized zoom focus lens, dark gray housing

200 New Highway, Amityville, NY 11701 800-645-5516 / www.specotech.com

#### **DIMENSIONS**



# **FEATURES**

- Flexible Intensifier Technology® fits any lighting application
- Supports 4MP @ 30FPS
- True WDR operation
- Adaptive IR LED's
- Presets: Outdoor, Low Light, Hallway, Lobby, Elevator, Indoor
- Built-in heater and anti-fog glass reduces condensation
- · 3-axis for wall and ceiling mounting
- Full OSD and Zoom / Focus control through on-board and UTC
- · Signal distance up to 1600 feet\*
- · Vandal / tamper resistant
- IP67 compliant, weather resistant
- 12VDC & 24VAC dual voltage operation
- 5 year warranty

#### **SPECIFICATIONS**


Image Sensor...... 1/2.8" SONY Starvis 5MP Sensor Minimum Illumination...... 0.00 lux (IR LED 'on') Effective Pixels...... 2616 (H) x 1964 (V) Total Pixels...... 2704 (H) x 2104 (V) Scanning System..... Progressive S/N Ratio..... More than 50dB Video Output...... 1.0Vp-p / 75 Ohms Electronic Shutter..... Auto / Manual (1/30 – 1/30,000 sec.) WDR...... On (Low / Middle / High) / Off Day / Night..... Auto / Intensifier Test Monitor Output...... TVI out Power...... 12VDC / 24VAC Power Consumption...... 900mA max. (DC), 700mA max. (AC) Operating Temperature.... -40° F - 140° F Unit Dimensions...... 9.64" (L) x 3.72" (Dia.) Unit Weight...... 2 lbs (camera), 0.9 lbs (junction box) Certifications..... FCC, RoHS

#### **OSD MENU TREE**


#### PRESET MODE

• OUTDOOR • LOW LIGHT • HALLWAY • LOBBY • ELEVATOR • INDOOR

#### **MAIN SETUP**



## **OSD CONTROL**



# 4MP Flexible Intensifier® HD-TVI Bullet Camera with Junction Box, Wall/Ceiling Mount, Dual voltage



H4FB2M - 2.7~12mm motorized zoom focus lens, dark gray housing 200 New Highway, Amityville, NY 11701 800-645-5516 / www.specotech.com

#### **OSD MENU Details**

IRIS: 'ALC' as a default value

**EXPOSURE**: adjusts exposure settings.

BRIGHTNESS: Adjusts image brightness. (0~20)

SHUTTER: Outdoor / Indoor / Deblur

INTENSIFY: Sets the desired multiple of the digital exposure length.

AGC(Auto Gain Control): Adjusts the AGC level. (0~10)

#### BACKLIGHT: Adjusts backlight options.

WDR: WDR illuminates darker areas of an image while retaining the same light level for brighter areas to even out the overall brightness of images with high contrast between bright and dark area

- Adjusts the WDR Weight (LOW/MIDDLE/HIGH)

BLC: Produces a clearer image of an object darkened by strong backlighting.

- H-POS: Adjusts the horizontal position(0~20)
- V-POS: Adjusts the Vertical position(0~20)
- H-SIZE: Adjusts the horizontal block size (0~20)
- V-SIZE: Adjusts the vertical block size (0~20)

HLC: Uses to contain extremely bright areas such as from car headlight, the light can be masked out much of the on-screen details.

#### DAY / NIGHT: Adjust Day / Night options.

AUTO: Day / Night is switching automatically

- ANTI-SAT.: Adjusts the Anti Saturation level (0~20)

- D > N THRES: Adjusts AGC THRES (0~20) - N > D THRES: Adjusts AGC THRES (0~20)

- DELAY: Adjusts the changing delay time (LOW/MIDDLE/HIGH)

INTENSIFIER: Always Color mode

#### **COLOR**: Adjusts white balancing options.

AWB: it goes to optimized color level automatically. COLOR GAIN: Sets the desired Color Gain value (0~20)

SPECO DNR: Uses to reduce the background noise in a low luminance environment with 2D + 3D filtering system.

### IMAGE: Adjusts various image options.

SHARPNESS: Adjusts sharpness level. Increasing this value, the picture outline becomes stronger and clear. (0~10)

GAMMA: Sets the desired Gamma value. (0.45 ~ 0.75) MIRROR: Change the video direction horizontally. FLIP: Change the video direction perpendicularly. D-ZOOM: Digital zoom up to x8 will be activated.

ACE (D-WDR): Uses a digital wide dynamic range to balance dark and over saturated areas within the image.

DEFOG: Activated this mode when the video or the weather is foggy. SHADING: Sets the Lens Shading Compensation value. (ON/OFF)

PRIVACY: Used to hide regions of the image.

#### MOTION: Adjust motion detection settings.

**DET WINDOW** 

SENSITIVITY: Sets the desired of "Motion" (0~20)

MOTION OSD **TEXT ALARM** SIGNAL OUT

# SYSTEM: Adjusts various camera system options.

COMM.

- CAM ID: Sets the camera ID for the RS-485 (0~255)

- BAUD RATE: Sets the baud rate for the RS-485 (2400~115200). OUTPUT

FRAME RATE 1440p 30 1080p 30 720p 30 1944p 12.5 1944p 20 2160p 15

**CONFIRM YES IMAGE RANGE** COLOR SPACE

COLOR BAR: Manufacturer's option LANGUAGE: Sets the desired OSD language

CAM TITLE

RESET: Press with long to reset all settings to factory defaults.



## LIMITED WARRANTY - VIDEO PRODUCTS

UNITED STATES OF AMERICA AND CANADA. THIS WARRANTY APPLIES ONLY TO THE ORIGINAL USER.

SUBJECT TO CONDITIONS AND EXCLUSIONS FOUND BELOW, THIS PRODUCT IS WARRANTED AGAINST MANUFACTURING DEFECTS IN MATERIAL AND WORKMANSHIP FOR THE FOLLOWING PERIOD FOR PARTS AND LABOR:

SPECO TECHNOLOGIES CAMERAS 5 YEARS	DVRs5 YEARS
SPECO TECHNOLOGIES IP CAMERAS 5 YEARS	NVRs5 YEARS
SPECO PTZ 1 YEAR	BALANCE OF
SPECO TECHNOLOGIES MONITORS 1 YEAR	SPECO TECHNOLOGIES LINE1 YEAR
IR LEDS90 DAYS	

SPECO TECHNOLOGIES WILL REPAIR OR REPLACE (AT OUR DISCRETION) ANY PARTS FOUND TO BE DEFECTIVE FOR THE WARRANTY PERIOD SPECIFIED. WE WILL PROVIDE A REPLACEMENT FOR ANY DEFECTIVE PART.

- YOU MUST OBTAIN A RETURN AUTHORIZATION (RA) NUMBER FOR ANY MERCHANDISE BEING RETURNED TO SPECO TECHNOLOGIES, WHETHER FOR RETURN/EXCHANGE OR REPAIR, WHETHER IN OR OUT OF WARRANTY.
- 2. THIS WARRANTY WILL BE HONORED ONLY UPON PRESENTATION OF THE ORIGINAL DATED BILL OF SALE OR SALES SLIP.
- 3. TRANSPORTATION OF THE PRODUCT TO OUR SERVICE DEPARTMENT IS THE RESPONSIBILITY OF THE USER. REPAIRED OR REPLACED PRODUCT WILL BE RETURNED PREPAID DURING THE WARRANTY PERIOD.
- A SPECO TECHNOLOGIES DOES NOT AUTHORIZE ANY INTERNET OR MAIL ORDER PRODUCT SALES. IF A SPECO TECHNOLOGIES PRODUCT IS PURCHASED FROM AN UNAUTHORIZED DISTRIBUTOR OR OTHER SOURCE. INCLUDING RETALLERS, MAIL ORDER SELLERS AND ONLINE SELLERS. IN UNIVERSELLERS AND ONLINE SELLERS. IN UNIVERSELLERS AND ONLINE SELLERS. IN UNIVERSELLERS AND ONLINE SELLERS AND ONLINE SELLERS AND ONLINE SELLERS. AND ONLINE SELLERS AND ONLINE SELLERS AND ONLINE SELLERS AND ONLINE SELLERS AND ONLINE SELLERS. AND ONLINE SELLERS AND ON

- 1. THIS WARRANTY SHALL NOT COVER ADJUSTMENT OF CUSTOMER OPERATED CONTROLS AS EXPLAINED IN THE APPROPRIATE MODEL'S INSTRUCTION MANUAL OR PRODUCTS WHICH HAVE BEEN ALTERED. ABUSED. OR HAVE MISSING OR ALTERED SERIAL NUMBERS.
- 2. THIS WARRANTY SHALL NOT APPLY TO UNCRATING, SETUP, INSTALLATION, OR THE REMOVAL AND REINSTALLATION OF PRODUCTS AFTER REPAIR.
- AT IER REPAIR.

  3. THIS WARRANTY SHALL NOT APPLY TO REPAIRS OR REPLACEMENTS NECESSITATED BY ANY CAUSE BEYOND THE RESULT OF MANUFACTURE INCLUDING, BUT NOT LIMITED TO, ANY MALFUNCTION, DEFECTS OR FAILURE CAUSED BY OR RESULTING FROM UNAUTHORIZED SERVICE OR PARTS, IMPROPER MAINTENANCE, MODIFICATION OR REPAIR BY THE USER, USES, INSELECT, ACCIDENT, FIRE, FLOOD, OR OTHER ACTS OF NATURE, INCORRECT LINE VOLTAGE, DANAGE OR IMAGE BURNS TO TELEVISION PICTURE TUBES CAUSED BY OR ATTRIBUTABLE TO THE USE OF ANY ACCESSORY, ELECTRONICS GAME OR DEVICE, OR DANAGE CAUSED TO IMAGE PICKUP DEVICES BY EXCESSIVE LIGHT.

  THE FOREGOING IS IN LIED OF ALL OTHER EXPRESSED WARRANTIES AND WE DO NOT AUTHORIZE ANY PARTY TO ASSUME FOR US ANY OTHER OBLIGATION OR LIABILITY. IN NO EVENT SHALL WE BE LIABLE FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES ARISING FROM

THE USE OF THIS PRODUCT, OR FOR ANY DELAY IN THE USE OF THIS PRODUCT DUE TO CAUSES BEYOND OUR CONTROL. SOME STATES DO NOT ALLOW HIS EXCLUSION OR LIMITATIONS OF HOULONG AN IMPLIED WARRANTY LASTS ANDIOR DO NOT ALLOW THE EXCLUSION OR LIMITATION SOME THE ADOVE LIMITATION SOME THE WARRANTY AND CONSEQUENTIAL DAMAGES. THE ABOYE LIMITATIONS ON IMPLIED WARRANTY AND CONSEQUENTIAL DAMAGES MAY NOT APPLY TO YOU.

THIS WARRANTY GIVES YOU SPECIFIC LEGAL RIGHTS. YOU MAY HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

NOTE: FOR YOUR PROTECTION IN THE EVENT OF THEFT OR LOSS OF THIS PRODUCT, PLEASE FILL IN THE INFORMATION REQUESTED

BELOW AND RET	TAIN WITH YOUR SALES REC	EIPT.		
MODEL NO.:(LOCATED ON BACK OR BOTTOM OF UNIT)			SERIAL NO.:	
DATE OF PURC	HASE:		-	
WHERE PURCHASED:			PURCHASE PRICE:	
	Speco Technologies 200 New Highway Amityville, NY 11701		MATION REGARDING SERVICE OR RETURN, FE: 1,200,645,556 IN METRO NV: 631,957,8700	

ALWAYS USE DISCRETION WHEN INSTALLING VIDEO ANDIOR AUDIO SURVEILLANCE EQUIPMENT ESPECIALLY WHEN THERE EXPECTATION OF PRIVACY, INQUIRE REGARDING FEDERAL, STATE ANDIOR LOCAL, REQULATIONS APPLICABLE TO THE UNSTALLATION OF VIDEO ANDIOR AUDIO RECORDING OR SURVEILLANCE EQUIPMENT, PARTY CONSENT MAY BE REQUIRED

Speco Technologies is constantly developing product improvements. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Rev. 240315