

# **2MP HD-TVI IR Motorized Dome Camera** with Junction Box

## VLD6M

2.8-12mm motorized lens, white housing













#### **Features**

- Supports up to 2MP @ 30fps
- Full HD resolution over coax
- Supports HD-TVI, CVI, AHD, and 960H Analog
- IR Range: up to 98' (depending on scene reflection)
- True WDR (wide dynamic range)
- 12VDC Operation (power supply not included)
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant

- Junction box included
- 5 year warranty
- NDAA Compliant\*





Camera Specifications			
Image Sensor	1/2.8" CMOS, 2MP		
Minimum Illumination	Color: 0.001 lux @F1.2, (AGC ON); BW: 0 lux (IR ON)		
Image Size	1920 x 1080		
Video Output	AHD/TVI/CVI/CVBS		

PAL/NTSC Image System

**Electronic Shutter** Auto: 1/25s ~ 1/50000s (PAL); 1/30s ~ 1/50000s (NTSC)

IR Distance 65.6ft ~ 98.4.ft

Frame Rate 30fps (60Hz); 25fps (50Hz)

Lens Mount D14

≥ 52dB (AGC OFF) S/N Ratio

Operatina	&	Unit	Sr	ecifications
Operaning	~	011111	~	Centeanons

Power	12VDC (power supply not included)
Power Consumption	IR OFF: < 1.5W; IR ON: < 5W
Operating Temperature	-22°F ~ 122°F
Operating Humidity	10% ~ 90% RH
Unit Dimensions	5.55" (Dia.) x 3.94" (L)
Unit Weight	1.81 lbs.



<sup>\*</sup> Products are in compliance with NDAA Section 889 Part B Guidelines

#### **Functions**

Function Control	OSD (COC Control)
Day & Night	Yes, Smart IR
WDR	Yes
DNR	3D DNR
AGC	Yes
Auto White Balance	Yes
Compensation	BLC
Sharpness	Yes
Mirror	Yes
Image Setting	Yes
Defect Correction	Auto
Angle Adjustment	Pan (0° ~ 345°); Tilt (0° ~ 77°); Rotation (0° ~ 345°)

### **Optional Accessories**



PSW5 12VDC **Power Supply** 



TVIUTPPT HD Video Transceiver with Pigtail (Balun)



TVILITP HD Video Transceiver



PMT1 Pole Mount (use with wall mount)



CLT3 Ceiling Mount



CMT1 Corner Mount



WMT1 Wall Mount



CLTX1 Ceiling Mount 4" Extension



Ceiling Mount 8" Extension

