

H8T7M

2.8-12mm motorized lens, white housing

Features

- Supports up to 8MP@15fps
- IR Distance : Up to 164 feet (depending on scene reflection)

1/2.5" CMOS

8MP: 3840 x 2160

- Full OSD operation through UTC (up the coax)
- 12VDC operations (power supply not included)
- IP67 compliant, weather resistant
- 5 year warranty

Image Sensor

NDAA Compliant*

Maximum Resolution

Camera Specifications



IR 4K ZOOM IP67

Operating & Unit Specifications

	oporanig a oni opocincanons	
	Power	12VDC (power supply not included) (± 10%)
	Power Consumption	IR OFF : (≤ 2W) IR ON: (≤ 4.5W)
i de la companya de l	Operating Temperature	-22°F - 122°F ; 10% ~ 90% (RH)
GC ON: B/W: 0 lux with IR	Unit Dimensions	4.39" (Dia) x 3.92" (L)
	Unit Weight	1.21 lbs.
e reflection)	*Products are in compliance with NE	DAA Section 889 Part B Guidelines

Frame Rate	15fps	
Video Output	TVI / CVI / AHD / CVBS	
Minimum Illumination	Color: 0.01 lux @ F1.2 AGC ON: B/W: 0 lux with IR	
S/N Ratio	≥ 52dB (AGC OFF)	
Image System	PAL/NTSC	
Electronic Shutter	Auto	
IR Range	164' (depending on scene reflection)	
Day/Night	IR cut filter	
Digital WDR	No	
3D NR	Yes	
AGC	No	
AWB	Yes	
BLC	Yes	
Defog	No	
LSC	No	
Saturation	Yes	
Sharpness	Yes	
Contrast	Yes	
Smart IR	Yes	
Image Setting	Yes	
Defect Correction	Auto	
Language	11 languages	
Angle Adjustment	Pan: 0° ~ 360°; Tilt: 0° ~ 80°; Rotation: 0° ~ 360°	

Optional Accessory







12VDC

Power Supply

TVIUTP HD-TVI Balun over UTP



CMT1

Corner Mount

(use with wall mount)

PMT1

Pole Mount

(use with wall mount)



TVIUTPPT HD-TVI Balun over UTP with Pigtail



CLTX2 Ceiling Mount 8″ Extension

*Camera defaulted to HD-TVI.Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 1/18/22

