



4MP IP Vandal Resistant Dome Camera, NDAA Compliant

O4VD1N

2.8mm fixed lens, white housing



Features

- Supports up to 4MP @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264 compression supported
- True Day/Night operation (IR cut filter)
- MicroSD card slot up to 256GB max (card not included)
- IR range: 100' (depending on scene reflection)
- Conformant with ONVIF Profile G/S/T
- Line crossing, object detection, region intrusion and video blurring detection
- IP67 weather resistance
- IK10 vandal resistance
- 5 year warranty
- NDAA Compliant*



Camera Specifications

Image Sensor	Progressive scan 1/3" CMOS, 4MP
Maximum Resolution	2560 x 1440
Minimum Illumination	0.005 lux @ F1.6 AGC ON; 0 lux with IR
Field of View	102.5° (H), 55° (V), 122° (D)
Compensation	True WDR, BLC, HLC
Day/Night	Smart IR
Electronic Shutter Speed	1/2s ~ 1/100000s
DNR	3D DNR
Angle Adjustment	Pan 0° ~ 355°, Tilt 0° ~ 67°, Rotation 0° ~ 180°

Video Specifications

Main Resolutions	2560 x 1440; 2304 x 1296; 1920 x 1080 @ 30fps
Sub Stream	720p (1-15fps), D1, CIF (1-30fps)
Third Stream	D1, CIF, 480 x 240 (1-30fps)
Video Settings	Region of interest, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Defog, Sharpen, Noise Reduction
Compression	H.265, H.264
Bitrate Control	VBR, CBR (64Kbps ~ 5Mbps)
Multiple Streaming	3 streams

Network Specifications

Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, 802.1x, UPnP, HTTPs, HTTP, QoS
DDNS Support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/MAC address filtering, digest authentication
User Access	Max. 3 simultaneous users. Actual number of users may vary depending on bandwidth

Interfaces

Ethernet	10/100 Mbps (RJ 45 Jack)
Power	DC jack
Card Slot	MicroSD, up to 256GB (not included)
Reset	Yes
Audio In	3.5mm input, Built-in mic
Audio Out	No

System Specifications

PoE	Standard (IEEE 802.3af)
Detection Events	Line crossing, object detection, region intrusion and video blurring detection
Alert Triggers	Motion detection, SD card error, Detection events
Image Settings	Watermark, IP address filtering, video mask, password protection, Corridor mode
Analytics	People and vehicle detection

Client Specifications

Web Browser Support	Chrome, Edge, Safari, Firefox, Internet Explorer
PC Application	SecureGuard® VMS, SecureGuard® CMS
Mobile	SecureGuard® Client (iPhone® and Android™)

Operating & Unit Specifications

Power	PoE, 12VDC (power supply not included)
Power Consumption	<6W
Operating Temperature	-40°F - 140°F
Operating Humidity	less than 95% (non condensing)
Unit Dimensions	4.6" (Φ) x 3.54" (H)
Unit Weight	1.38 lb (without junction box)
Certifications	FCC

Optional Accessories



Cameras Interfaces



NDAA COMPLIANT Onvif® GSSI

*Products are in compliance with NDAA Section 889 Part B Guidelines



ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 7/1/24

Apps available from the following:



ONVIF® 800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com

speco technologies®