

# 4MP Intensifier® IP Dome Camera with Advanced Analytics

# **04iD1**

### 2.8mm fixed lens, dark gray housing















### **Features**

- $\bullet$  Intensifier  $^{\circledR}$  Technology captures in full color in extreme low-light scenes
- Captures up to 4MP @ 30fps real time
- True WDR operation
- Micro SD card slot (card not included)
- Conformant with ONVIF Profile G/S/T
- IP67 compliant, weather resistant

- IK10 compliant, vandal resistant
- Built-in standard PoE (IEEE 802.3af)
- Line crossing with counting/Intrusion detection\*
- Face/Person/Vehicle detection\*
- NDAA Compliant\*\*
- Junction box included (works with NPT/BSP specifications)
- 5 year warranty





<b>Camera Specifications</b>
Image Sensor
Maximum Resolution

Progressive scan 1/1.8"CMOS 2560 × 1440 Field of View H.FoV: 110°; V.FoV:60°; D.FoV:130° 0.0006 lux@F1.0, AGC ON Minimum Illumination Auto, Indoor, Outdoor, Manual White Balance True WDR (120dB), BLC, HLC Compensation **Electronic Shutter Speed** 1s~1/100000s

3D DNR DNR Pan  $0^{\circ}$  ~  $355^{\circ}$ , Tilt  $0^{\circ}$  ~  $67^{\circ}$ , Rotation  $0^{\circ}$  ~  $180^{\circ}$ Angle Adjustment

# **Video Specifications**

Main Resolution	2560×1440/2304×1296/1920x1080/1280x720/D1/ CIF/480×240 @30fps	
Sub Stream	1280x720/D1/CIF/480×240 @30fps	
Third Stream	D1/CIF/480×240 @30fps	
Compression	Main stream: H.265+ / H.265 / H.264+ / H.264 Sub stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG Third stream: H.265+ / H.265 / H.264+ / H.264 / MJPEG	
Video Settings	Region of Interest, Privacy masking, Brightness, Contrast, Hue, Saturation, Denoise, Antiflicker, Intensifier® presets, Exposure, Gain, Corridor Pattern, Image flip/mirror	
Bitrate Control	VBR, CBR (64Kbps ~ 8Mbps)	
Multiple Streaming	3 streams	

### **Network Specifications**

Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTP, HTTPS
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/MAC address filtering, digest authentication
User Access	Max. 10 simultaneous users Actual number of users may vary depending on bandwidth





























### **Client Specifications**

•	
Web Browser Support	Google Chrome, Microsoft Edge, Internet Explorer, Apple Safari
PC Application	SecureGuard® VMS and SecureGuard® CMS
Mobile	SecureGuard® Client, Speco Blue

## Audio Specifications

Action opening	
Audio Codec	G.711 A / G.711 U
Audio Input	Built-In Mic and 3.5mm Input
Audio Output	No

interraces		
Ethernet	RJ45 Jack, 10/100 Mbps, PoE	
Power	12VDC input jack	
Audio	Built-in mic and 3.5mm Input	
Card Slot	MicroSD, up to 256GB (not included)	
Alarm	1CH alarm input; 1CH alarm output	
Reset	Yes	

# **System Specifications**

PoE	Standard (IEEE 802.3af)
Analytics	Motion detection, region entrance/exiting/intrusion detection (human/vehicle classification), line crossing detection (human/vehicle classification), video tampering detection, scene change detection, face detection
Alarm Triggers	Motion detection, Sensor detection, SD card error, SD card full, IP address conflict, cable disconnection
Alarm Events	FTP upload, email upload
Image Settings	Watermark, IP address filtering, video mask, heartbeat, illegal login lock, image distortion correction

# **Operating & Unit Specifications**


Power	PoE, 12VDC (power supply not included)
Power Consumption	3.5W (max)
Operating Temperature	-40°F - 140°F
Operating Humidity	Less than 95% (non-condensing)
Unit Dimensions	4.68" (φ) x 3.5" (H)
Unit Weight	1.43 lbs
Certifications	FCC



\*with compatible Speco Blue recorder \*\* Compliant with NDAA Section 889 Part B Guidelines















speco technologies

