



# 8MP (4K) IP Dome Camera with Line Crossing & Intrusion Detection

## O8VD3

2.8mm fixed lens, white housing

### Features

- Captures up to 8MP @ 20fps
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- True Day/Night operation (IR cut filter)
- IR range: Up to 100' (depending on scene reflection)
- Micro SD slot up to 256GB (card not included)
- True WDR
- Line crossing, region intrusion and video blurring detection\*
- Built-in microphone
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Conformant with ONVIF Profile G/S/T
- 5 year warranty
- NDAA Compliant\*\*

\*With compatible Speco recorder

\*\*Products are in compliance with NDAA Section 889 Part B Guideline



### Camera Specifications

Image Sensor	Progressive scan 1/2.8" CMOS, 8MP
Maximum Resolution	3840 x 2160 (8MP)
Field of View	108.9°(H); 76.4°(V); 116.2°(D)
Minimum Illumination	0.02 lux @ F1.6, AGC ON, 0 lux with IR
Day/Night	Smart IR
White Balance	Auto, indoor, outdoor, manual
Compensation	True WDR, BLC, HLC
Electronic Shutter Speed	1 - 1/100000 sec.
DNR	3D DNR
Angle Adjustments	Pan 0° - 355°, tilt 0° - 67°, rotation 0° - 180°

### Video Specifications

Main Resolution	8MP/ (1 - 20fps) 6MP/5MP/4MP/2K/3MP/2MP/720p @30fps
Sub Stream	720p/D1/480x240 (1 - 30fps)
Third Stream	D1/CIF/480 x 240 (1 - 30fps)
Compression	H.265, H.264, MJPEG
Image Settings	Region of interest, saturation, brightness, chroma, contrast, wide dynamic, defog, sharpen, noise reduction, corridor mode
Bitrate Control	VBR, CBR (64Kbps - 12Mbps)

### Audio Specifications

Audio Codec	G.711A / G.711U
-------------	-----------------

### Network Specifications

Protocols	UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS
DDNS support	Speco DDNS (free of charge)
Security	User ID & password protection, IP/Mac address filtering, digest authentication
User Access	Max. 10 simultaneous users; actual number of users may vary depending on bandwidth

### Interfaces

Network	RJ45 jack
Power	DC jack
Microphone Input	3.5mm
Card Slot	MicroSD, up to 256GB (not included)
Alarm	No
Reset	Yes

### Client Specifications

Web Browser Support	Chrome, Edge, Safari, Firefox
PC Application	SecureGuard® VMS, SecureGuard® CMS
Mobile	SecureGuard® Client, Speco Blue (iPhone® and Android™)

## System Specifications

PoE	Standard (IEEE 802.3af)
Analytics	Motion, exception, line crossing, region intrusion, people/vehicle detection and video blurring detection
Alarm Triggers	Motion, analytics, SD card error
Security Settings	Watermark, IP address filtering, video mask, password protection

## Operating & Unit Specifications

Power	PoE, 12VDC (power supply not included)
Power Consumption	< 7.0W
Operating Temperature	-40°F - 140°F (40°C - 60°C)
Operating Humidity	Less than 95 % (non-condensing)
Unit Dimensions	4.68" (Dia.) x 3.45" (H); 119mm (Dia.) x 87.8mm (H)
Unit Weight	1.41 lbs. (0.64kg)
Certifications	FCC, RoHS

## Optional Accessories



**POEINJ**  
25.5W  
PoE Injector



**PSW5**  
12VDC  
Power Supply



**CMT1**  
Corner Mount



**PMT1**  
Pole Mount



**CLTX1**  
Ceiling Mount  
4" Extension



**CLTX2**  
Ceiling Mount  
8" Extension



**O5VLWMJ**  
Wall Mount



**CLT2J**  
Ceiling Mount



**FMT1**  
Flush Mount



**JB2**  
Junction Box  
(included)

## Camera Interfaces

DC 12V



RJ45 PoE



3.5mm  
Audio In



Built-in Mic



up to 256GB