



4MP HD-TVI Flexible Intensifier Technology® Bullet Camera with Junction Box

H4FB1M

2.7-12mm motorized zoom focus lens



Features

- Flexible Intensifier Technology® fits any lighting application
- Supports 4MP @ 30fps (default)
- Adaptive IR LED's
- IR range: up to 98' (depending on scene reflection)
- Motorized Lens with autofocus
- True WDR Operation
- Full OSD operation through onboard control and UTC (TVI)
- IP67 Compliant, weather resistant
- TAA Compliant
- NDAA Compliant*



Included Junction Box



| Camera Specifications | |
|-----------------------|---------------------------------------|
| Image Sensor | 1/2.8" Sony Starvis, 5MP |
| Effective Pixels | 2616(H) x 1964(V) |
| Total Pixels | 2704(H) x 2104(V) |
| Minimum Illumination | 0 lux |
| Scanning System | Progressive |
| Video Output | 1080p 25 / 30, 1440p 25/30, 1944p 20 |
| Output | AHD (or TVI) / CVBS Concurrent Output |
| AGC | AGC |
| S/N Ratio | More than 52dB (AGC OFF / Weight ON) |
| Shutter Speed | Auto / Manual / Flicker |
| WDR | Normal / ROI/Weight |
| Day/Night | Auto / Color / BW/AGC/AGC+IR |
| White Balance | Auto / AUTOext / Preset / Manual |

| Operating & Unit Specifications | |
|---------------------------------|-------------------------|
| Power | 12VDC, 24VAC |
| Operating Temperature | -4°F ~ 122°F |
| Storage Temperature | -4°F ~ 122°F |
| Operating Humidity | 0% - 90% RH |
| Dimensions | 10.2" (L) x 2.8" (Dia.) |

Optional Accessories



TVIUTPPT
HD Video
Transceiver with
Pigtail (Balun)



TVIUTP
HD Video
Transceiver



PSW5
12VDC
Power Supply



INTPMT
Pole Mount

**NDAA
COMPLIANT**

*Products are in compliance with NDAA Section 889 Part B Guidelines

*Camera is defaulted to HD-TVI. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 6/10/22