



# 4MP IP Dome Camera with Advanced Analytics

Integrated with and

## O4D9M

2.8-12mm motorized lens, white housing

### Features

- Supports up to 4MP @ 30fps
- 4x Optical Zoom
- Two-way Audio Support
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- True Day/Night operation (IR cut filter)
- Adaptive IR LEDs reduce IR saturation
- IR range: Up to 165 ft. (depending on scene reflection)
- Micro SD slot up to 256GB (card not included)
- True WDR (wide dynamic range) operation
- IP67 compliant, weather resistant
- IK10 compliant, vandal resistant
- Junction box included (works with NPT/BSP specifications)

NDAACOMPLIANT

ONVIF

GMS1



Junction Box Included



### Camera Specifications

Image Sensor	Progressive scan 1/3" CMOS, 4MP
Maximum Resolution	2592 x 1520
Field of View	100° ~ 28.9°(H), 54.5° ~ 16.7°(V), 104.8° ~ 33.1°(D)
Minimum Illumination	0.003 lux @ F1.3, AGC ON; 0 lux with IR
Day/Night	Smart IR
White Balance	Auto, Indoor, Outdoor, Manual
Compensation	True WDR (120dB), BLC, HLC
Electronic Shutter Speed	1/3 - 1/1000000 sec.
DNR	3D DNR

### System Specifications

PoE	Standard (IEEE 802.3af)
Analytics	Motion, exception, line crossing, region intrusion, object detection, vehicle/people detection, face detection, people/vehicle counting and tampering detection <b>All listed analytics may be triggered simultaneously, except face detection</b>
Alarm Triggers	Analytics, SD card error
Alarm Events	FTP upload, email upload
Image Settings	Watermark, IP address filtering, video mask, password protection

### Interfaces

Ethernet	10/100 Mbps (PoE)
Video	CVBS output (BNC x 1)
Power	DC jack
Microphone Input	Mono 3.5mm + built-in mic
Audio Out	Mono 3.5mm
Card Slot	MicroSD, up to 256GB (not included)
Alarm	1-CH alarm input; 1-CH alarm output
Reset	Yes

### Audio Specifications

Audio Codec	G.711A / G.711U
-------------	-----------------

### Network Specifications

Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTP, HTTPS
DDNS support	Speco DDNS (free of charge)
Security	User ID & password protection, IP/Mac address filtering, digest authentication
User Access	Max. 10 simultaneous users, actual number of users may vary depending on bandwidth

### Video Specifications

Main Resolution	2592x1520 / 2560x1440 / 2304x1296 1920x1080 / 1280x720 @ 30fps
Sub Stream	720P/ D1, CIF
Third Stream	D1/ CIF/ 480 X 240
Compression	H.265, H.264 (HP/MP/BP), MJPEG
Video Settings	Region of interest, privacy masking, brightness, contrast, hue, saturation, denoise, antiflicker, day/night mode, infrared settings, exposure, gain, corridor pattern, image flip/mirror
Bitrate Control	VBR, CBR (64Kbps - 10Mbps)
Multiple Streaming	3 streams

### Client Specifications

Web Browser Support	Google Chrome®, Edge®, Safari, Fire Fox®, Windows *(Internet Explorer® 8 and up)
PC Application	Speco Blue VMS, SecureGuard® CMS
Mobile	SecureGuard® Client, Speco Blue (iPhone® and Android™)

## Operating & Unit Specifications

Power	PoE, 12VDC (power supply not included)
Power Consumption	< 8W
Operating Temperature	-40°F ~ 140°F
Operating Humidity	Less than 95 % (non-condensing)
Unit Dimensions	5.55" (φ) x 4.01" (H)
Unit Weight	1.96 lb.
Certifications	FCC, UL Listed, ONVIF Profile G/M/S/T

\*With compatible Speco Silver Recorder

\*\*Products are in compliance with NDAA Section 889 Part B Guidelines

## Optional Accessories



**POEINJ**  
25.5W  
PoE Injector



**PSW5**  
12VDC  
Power Supply



**CMT1**  
Corner Mount



**PMT1**  
Pole Mount



**CLTX1**  
Ceiling Mount  
4" Extension



**CLTX2**  
Ceiling Mount  
8" Extension



**WMT1**  
Wall Mount



**CLT3**  
Ceiling Mount



**FMT1**  
Flush Mount

## Cameras Interfaces

**3.5mm**  
Audio In



**3.5mm**  
Audio Out



**CVS Out**



**DC 12V**



**Built-in**  
mic



**RJ45 PoE**



**Alarm**  
In/Out



**Micro**  
SD  
up to 256GB

NDAA  
COMPLIANT

ONVIF | GMS-T

UL  
LISTED

GET IT ON  
Google Play

Download on the  
App Store

available at  
amazon appstore

Products are in compliance with NDAA Section 889 Part B Guidelines. Google Chrome® and Firefox® use Java™ which requires an initial internet connection. This product has earned the UL® Listed Mark. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™, Google Play® and the Google Play logo® are trademarks of Google Inc. Amazon® is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 4/4/24

**BLUE**  
SERIES