

## **5MP IP Dome Camera with Advanced Analytics, NDAA** Compliant

**Audio Specifications** 

Audio Codec

# **O5D2M**

#### 2.8-12mm motorized lens, white housing

#### **Features**

- Supports up to 5MP @ 30fps
- Up to 4x Optical Zoom
- Built-in standard PoE (IEEE 802.3af)
- Cloud recording and playback support\*\*
- Face/Human/Vehicle/Scene Change Detection\*\*\* • H.265/H.264/MJPEG compression supported
- True Day/Night operation (IR cut filter)
- Adaptive IR LEDs reduce IR saturation
- IR range: Up to 165' max (depending on scene reflection)
- Micro SD slot up to 256GB (card not included)
- True WDR (wide dynamic range) operation

#### • Two Way Audio Ready • IP67 compliant, weather resistant

- IK10 compliant, vandal resistant
- Junction box included
- (works with NPT/BSP specifications)
- Conformant with ONVIF Profile T
- UL-listed\*
- 5 year warranty
- NDAA Compliant\*\*\*\*



2-WAY AUDIO

G.711A / G.711U

Camera Specifications					
Image Sensor			Progressive scan 1/2.7" CMOS, 5MP		
Maximum Resolution			2592 x 1944		
Field of View			95.1°~ 30° (H), 78.7°~22.8° (V), 107.6°~37.1°(D)		
Minimum Illumination		n	0.01 lux @ F1.4, AGC ON; 0 lux with IR		
Day/Night			Smart IR		
White Balance			Auto, Indoor, Outdoor, Manual		
Compensation			True WDR (120dB), BLC, HLC		
Electronic Shutter Speed		eed	1 - 1/100000 sec.		
DNR			3D DNR		
Video Specifications					
Main Resolution		2592x1944 / 2592x1520 / 2560x1440 / 2304x1296 / 1980x1080 / 1280x720 @ 30fps			
Compression		H.265, H.264 (HP/MP/BP), MJPEG			
Video Settings		Region of Interest, Privacy masking, Brightness, Contrast, Hue, Saturation, Denoise, Antiflicker, Day/Night mode, Infrared settings, Exposure, Gain, Corridor Pattern, Image flip/mirror			
Bitrate Control		VBR, CBR (64Kbps ~ 8Mbps)			
Multiple Streaming		3 streams			
Network Specifications					
Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTP, HTTPS				
DDNS support	Speco DDNS (free of charge)				
Security	User ID & Password protection, IP/Mac address filtering, digest authentication				
User Access	Max. 10 simultaneous us bandwidth		ultaneous users, Actual number of users may vary depending on		
Client Specifications					
Web Browser Support		rt	Google Chrome, Edge, Safari, Fire Fox, Windows (Internet Explorer 8 and up)		
PC Application			SecureGuard® VMS, SecureGuard® CMS		

SecureGuard<sup>®</sup> Client, Speco Blue (iPhone<sup>®</sup> and Android<sup>™</sup>)

Audio Codec		0.711A7 0.7110			
Interfaces					
Ethernet		10/100 Mbps RJ45			
Video		CVBS output (BNC x 1)			
Power		DC jack			
Microphone Inp	ut	Mono 3.5mm + built-in mic			
Audio Output		Mono 3.5mm			
Card Slot		MicroSD, up to 256GB (not included)			
Alarm		1CH alarm input, 1 CH alarm output			
Reset		Yes			
System Specifications					
PoE	Standard (IEE	EE 802.3af)			
Analytics	Motion, missing object, abandoned object, intrusion, vehicle, human, tamperi scene change, and face detection				
Alarm Triggers	Analytics, SD	card error			
Alarm Events	FTP upload, e	email upload			
Image Settings	Watermark, IP address filtering, video mask, password protection				
Operating & Unit Specifications					
Power		PoE, 12VDC (power supply not included)			
Power Consump	tion	< 9.0W			
Operating Temp	erature	-40°F ~ 140°F			
Operating Humi	dity	Less than 95 % (non-condensing)			
Unit Dimensions		5.55″ (φ) × 4.01″ (H)			
Unit Weight		1.96 lb.			
Certifications		FCC, RoHS, UL-listed			
as of March 2023 *with Speco Cloud subscription service * with compatible Speco recorder ***Products are in compliance with NDAA Section 889 Part B Guidelines					





ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademarks of Apple Inc., registered in the U.S. and other councertainty of the service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Mobile

App Store

▶ Google Play amagina pipstore O⊓VIF\* 800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com

### **speco** technologies