High Performance Outdoor 1G PoE Surge Protector

SPPOEO

Features

- Supports bandwidth up to 1000 Mbps
- Supports IEEE 802.3 af, 802.3 at, 802.3bt PoE standard
- Supports Mid-Span and End Span PoE
- Meets IP66 Waterproof rating
- Response time less than 1 ns















Specifications	SPPOEO
Support	
Compliance	IEEE 802.3 af, 802.3 at, 802.3bt IEC 61000-4-5, IEC 61000-4-2, EN61000-4-5
Network Bandwidth	10/100/1000 Mbps
Response Time	Less than 0.7nS
ESD Protection	30KV (Air)/30KV(Contact)
Lightning Protection	10KA (8/20 us), 20KV (8/20 us)
Waterproof Rating	IP66
Ports & Interfaces	
Equipment End	1 x RJ45
Cable End	1 x RJ45
Ambient Temperature	
Operation	-40 to 158°F (-40 to 70°)
Storage	-40 to 194°F (-40 to 90°)
Humidity	Up to 95%
Physical Characteristics	
Size	3.1 × 6.5 × 2.75" (80 × 166 × 70mm)
Weight	0.5 Lbs (230g)

ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 11/14/22









