HD-TVI Video and Power Surge Protector

SPTVIVP

Features

- Helps protect HD-TVI cameras, as well as AHD/HD-CVI/CVBS formats, from lightning strikes and power surges
- Resolution up to 4K
- Supports power input up to AC40V/ DC56V
- Response time less than 1 ns







Specifications	SPTVIVP
Support	
Response Time	Less than 1 ns
Max. Surge Voltage	4 KV
Surge Life	300 Times/ 100A Surge
Normal Resistance Across Coax	10,000 ΜΩ
Band Pass	0 to 1 GHz
Power Passing Capability	DC / AC 130V, 65 Vrms@10 A
Insertion Loss	Less than 0.2dB
Return Loss (75Ω)	16dB
Max. Power Input	AC 40V, DC56V
Ports & Interfaces	
Equipment End	1 x BNC Female, 1 x 2-pin Terminal Block
Cable End	1 x BNC Female, 1 x 3-pin Terminal Block
Ambient Temperature	
Operation	14 to 185°F (-10 to 85°)
Storage	-40 to 221 °F (-40 to 105°)
Humidity	95%
Physical Characteristics	
Dimensions	2.6 x 3.4 x 1" (67 x 87 x 27mm)
Weight	0.3 Lbs (145g)

ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 11/14/22









