

# 8MP (4K) Flexible Intensifier® IP Bullet Camera with Advanced Analytics

Integrated with immix

## **08FB1**

2.8mm fixed lens, dark gray housing

#### **Features**

- Flexible Intensifier® Technology to fit any lighting application
- Captures up to 8MP @ 30fps real time
- · Captures color in extreme low light conditions and monochrome in absolute darkness.
- IR range: up to 164 ft. (depending on scene reflection)
- · True WDR operation
- Micro SD card slot (card not included)
- Built-in standard PoE (IEEE 802.3af)
- · Line crossing with counting/Intrusion detection\*
- Face/People/Vehicle detection\*



NDAA Onvir 10000























## **Camera Specifications**

Image Sensor	Progressive scan 1/1.8" CMOS
Maximum Resolution	3840 x 2160 (8MP)
Field of View	Horizontal: 110°; Vertical: 57.5°; Diagonal: 133.5°
Minimum Illumination	0.008 lux@F1.6, AGC ON; 0 lux with IR
White Balance	Auto, indoor, outdoor, manual
Compensation	True WDR (120dB), BLC, HLC
Day/Night	Smart IR
Electronic Shutter Speed	1/2s ~ 1/100000s
DNR	3D DNR
Angle Adjustment	Pan: 0°~360°;
	Tilt: 0°~90°; Rotation: 0°~360°

## **Interfaces**

Ethernet	RJ45 Jack, 10/100 Mbps, PoE
Power	12VDC input jack
Audio	3.5mm input
Card slot	MicroSD, up to 256GB (not included)
Alarm	No
Reset	Yes

## **Client Specifications**

Web Browser Support	Google Chrome®, Microsoft Edge®, Internet Explorer®, Apple Safari®
PC Application	SecureGuard® VMS and SecureGuard® CMS
Mobile	SecureGuard® App, Speco Blue

## **Network Specifications**

	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE,
Protocols	DDNS, SMTP, FTP, SNMP, 802.1x, UPnP,
	HTTP, HTTPS
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/MAC address filtering, digest authentication, Watermark, and illegal login lock
User Access	Max. 10 simultaneous users actual number of users may vary depending on bandwidth

#### **Audio Specifications**

Audio Compression	G.711A / G.711U
Audio Input	3.5mm input
Audio Output	No

#### **System Specifications**

PoE	Standard (IEEE 802.3af)
Analytics	Motion detection, region entrance/ exiting/intrusion detection (people/ vehicle classification), line crossing detection (people/vehicle classification), video tampering detection, scene change detection, face detection, face capture. All listed analytics may be triggered simultaneously, except face detection.
Alarm Triggers	Motion detection, Sensor detection, SD card error, SD card full, IP address conflict, cable disconnection
Alarm Events	FTP upload, email upload





## **Operating & Unit Specifications**

Power	PoE, 12VDC (power supply not included)
Power Consumption	9.5W (max)
Operating Temperature	-40°F - 140°F
Operating Humidity	Less than 95% (non-condensing)
Unit Dimensions	10.95" (L) x 3.93" (W) x 3.49" (H)
Unit Weight	1.5 lbs
Certifications	FCC, ONVIF Profile G/M/S/T

## **Video Specifications**

Main Resolution	8MP/6MP/4MP/2K/3MP/1080p, 2560x1440, 2304x1296, 1920x1080, 1280x720, D1, CIF, 480240 @ 30fps
Substream	1080p, 720p, D1, CIF, 480x240 @ 30fps
Third Stream	D1, CIF, 480x240 @ 30fps
Compression	Main stream: H.265+/H.265 /H.264+ /H.264 Sub stream: H.265+/H.265 /H.264+ /H.264 /MJPEG Third stream: H.265+/ H.265 /H.264+ /H.264 /MJPEG
Bitrate Control	VBR, CBR (64Kbps ~ 8Mbps)
Multiple Streaming	3 streams
Video Settings	Region of interest, privacy masking, brightness, contrast, hue, saturation, denoise, antiflicker, day/night mode, exposure, gain, corridor pattern, image flip/mirror

## **Optional Accessories**







**POEINJ** 25.5W PoE Injector

12VDC Power Supply

Corner Mount



PMT1G Pole Mount



**O5VLWMJG** Wall Mount

## Camera Interfaces

3.5mm Audio In DC 12V

RJ45 PoE







NDAA COMPLIANT













