

5MP HD-TVI IR Bullet Camera with Included Junction Box

V5B2

2.8mm fixed lens, white housing

Features

- Supports up to 5MP @ 20FPS
- IR Distance: 98' (depending on scene reflection)
- DWDR
- 12VDC Operation (power supply not included)
- IP67 weather resistance
- NDAA Compliant*
- 5 year warranty





Camera Specifications

Image Sensor	Progressive scan 1/2.7" CMOS
Resolution	5MP 2560 x 1936
Video Output	AHD/TVI/CVI/CVBS (*camera
	comes defaulted to HD-TVI)
Image System	PAL/NTSC
Electronic Shutter Speed	Auto; 1/50s~1/100000s(PAL);
	1/60s~1/100000s (NTSC)
Minimum Illumination	Color: 0.01lux @ F1.2(AGC ON);
	B/W: 0 lux @ IR ON
S/N Ratio	≥ 52dB (AGC OFF)
Function Control	OSD (UTC Control)
Day/Night	Yes
WDR	Yes
DNR	Yes
Gain Control	Auto
White Balance	ATW
Defog	No
BLC	Yes
LSC	Yes
Mirror	Yes
Sharpness	Yes
Smart	Yes
Image Setting	Yes
Defect Correction	Auto

NDAA COMPLIANT

*with compatible Speco recorder **Products are in compliance with NDAA Section 889 Part B Guidelines

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 1/30/24



800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • www.specotech.com

Operating & Unit Specifications

Power	12VDC (power supply not included)
Power Consumption	IR OFF \leq 1W; IR ON \leq 4W
Operating Temperature	-22°F - 122°F
Relative Humidity	10% ~ 90%
Unit Dimensions	6.74"(L) x 3.27"(W) x 3.26"(H)
Unit Weight	1.87lbs

