



5MP HD-TVI IR Turret Camera with Built-in Microphone and Junction Box

V5T3

2.8mm fixed lens, white housing

Features

- Supports up to 5MP @20FPS
- IR Distance: 98' (depending on scene reflection)
- DWDR
- 12VDC Operation (power supply not included)
- IP67 weather resistance
- Audio over coax

NDA
COMPLIANT



Junction Box Included



Camera Specifications

Image Sensor	Progressive scan 1/2.5" CMOS
Resolution	5MP 2944 x 1656 (16:9)
Video Output	AHD/TVI/CVI/CVBS (*camera comes defaulted to HD-TVI)
Image System	Image System
Electronic Shutter Speed	Auto; 1/50s-1/1000000s(PAL);1/60s-1/1000000s (NTSC)
Minimum Illumination	Color: 0.01lux @ F1.2(AGC ON); B/W: 0 lux @ IR ON
S/N Ratio	≥ 52dB (AGC OFF)
Function Control	OSD (UTC Control)
Day/Night	✓
WDR	✓
DNR	✓
Gain Control	Auto
White Balance	ATW
Defog	✗
BLC	✓
LSC	✓
Mirror	✓
Sharpness	✓
Smart IR	✓
Image Setting	✓
Defect Correction	Auto
IR Range	~98ft (depending on scene reflection)

NDA
COMPLIANT

Products are in compliance with NDAA Section 889 Part B Guidelines. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 8/29/24

Operating & Unit Specifications

Power	12VDC (power supply not included)
Power Consumption	IR OFF ≤ 1W; IR ON ≤ 4W
Operating Temperature	-22°F - 122°F
Relative Humidity	10% - 90%
Unit Dimensions	4.67"(H) x 3.9"(Dia.)
Unit Weight	2.21lbs

Optional Accessories



PSW5
12VDC
Power Supply



CMT1
Corner Mount



PMT1
Pole Mount



WMT1
Wall Mount



CLT3
Ceiling Mount



CLTX1
Ceiling Mount
4" Extension