

# 8MP IP Multi-Sensor 180° Wide Angle Camera with White Light Intensifier® and Advanced Analytics

Integrated with OCHEKT and immix

## **O8LMST1**

2.5mm fixed lens, white housing

#### **Features**

- · 8MP 180° multi-sensor with image stitching
- · Advanced face and vehicle detection
- Built-in Standard PoE (IEEE 802.3 af)
- · Two-way audio supported
- Micro SD card 256GB support (card not included)
- · IP67 compliant, weather resistant
- · IK10 compliant, vandal resistant
- Face, people and vehicle detection
- · Line crossing and region detection





**Camera Specifications** 

Image	2/2.5 Progressive scan CMOS both lens
Max. Resolution	4096x1800, 8MP
Field of view	Horizontal: 180°; vertical: 65°
	0.005 lux @ (F1.1, IRE 50);
Illumination	B/W: 0.0005 lux @ (F1.1, IRE 50);
	0 lux with Smart IR
White balance	Auto / manual / indoor / outdoor
DNR	3D DNR
Day/Night	White Light Intensifier®

1/30s-1/30,000s

#### **Interfaces**

Shutter Speed

Ethernet	10m / 100m
Power	12V DC (input jack)
Mic	3.5mm jack with line in supported
Micro SD	Up to 256GB
Alarm	1-CH alarm input; 1-CH alarm output; alarm INR with ground input & ground cable
Reset	Yes

### **Operating & Unit Specifications**

Power	PoE or 12VDC (power supply not in-
	cluded)
Power Comp	12W max
Operating Temperature	-40°F - 131°F
Operating Humidity	Less than 95% (non-condensing)
Unit Dimensions	6.06" (L) x 5.07" (W)
Unit Weight	2.86 lbs.
Certifications	FCC and RoHS

























### **Client Specifications**

Web browser support	IE8-11 with plug-in; Microsoft Edge®,
	Google Chrome®, FireFox®
	with plug-in free
PC Application	SecureGuard® VMS, SecureGuard®
	CMS, Speco Blue VMS
Mobile	SecureGuard® Client, Speco Blue
	(iPhone® & Android™)

#### **Audio Specifications**

•	
Speaker	1 built-in speaker, 4, 2W nom, 750Hz
	LFR, 100dB @ 0.1m, two-way audio
Microphone	1 built-in microphone, omnidirectional,
	2K, -36dB @ 1 KHz sensitivity, THD
	115dB SPL @ 1 KHz
Input Codec	G.711A/G.711U

#### **Video Specifications**

Main	4K / 1080p / 720p @ 20fps
Codec	H.265, H.264, H.265+, H.264+, MJPG
Bitrate	VBR/CBR (64 Kbps to 16MBs)
Streams	3 Streams
Compression	Main stream, sub stream

#### **Network Specifications**

Protocols	HTTP, HTTPS, IPv4/IPv6, 802.1x,
	QoS, FTP, SMTP, UPnP, SNMP, DNS,
	DDNS, NTP, RTSP, RTCP, RTP, TCP/
	IP, UDP, DHCP, PPPoE, P2P, SSL/TLS
DDNS Support	Speco DDNS (free of charge)
Security	User ID & password protection, IP/Mac
	address filtering, digest authentication







### Camera Interfaces

3.5mm Audio In

3.5mm **Audio Out** 







Built-in Speaker

**DC 12V** 





#### **Optional Accessories**











PSW5 12VDC Power Supply



CLTX1 Ceiling Mount 4" Extension



CMT1 Corner Mount



PMT1 Pole Mount



Ceiling Mount





















