



HRLN Series H.265 Hybrid DVR with Smart Analytics

Integrated with **immix**

H6HRLN

6-Channel Hybrid Digital Video Recorder

4 Configurable Hybrid Channels (TVI or IP) plus 2 IP Channels

H16HRLN

16-Channel Hybrid Digital Video Recorder

8 Configurable Hybrid Channels (TVI or IP) plus 8 IP Channels

H24HRLN

24-Channel Hybrid Digital Video Recorder

8 Configurable Hybrid Channels (TVI or IP) plus 8 IP Channels
plus 8 TVI Channels

Product Summary

Speco's NDAA compliant HRLN recorders, will take your footage quality to the next level supporting up to 8MP cameras @ 30 fps

Features

- Supports up to 5MP (HD-TVI + IP) on all channels and 4K (IP) on 1-channel (H6HRLN)
- Supports up to 5MP (HD-TVI + IP) on all channels and 4K (IP) on 8-channels (H16HRLN, H24HRLN)
- H.265 compression - Store up to 2x more than H.264!
- 1 SATA port for up to 20TB of storage (H6HRLN)
- 2 SATA ports for up to 40TB of storage (H16HRLN, H24HRLN)
- 1 eSATA port for an additional 8TB of storage
- 4K HDMI out and VGA monitor output
- Object and line crossing detection and alerts*
- Smart Search -specify a region on the camera view and search on changes in that area*
- 2-way audio communication
- Alarm 4/8/16 inputs, 1/2/4 outputs
- Free US-based DDNS and P2P services
- Remote viewing via web browser, your Apple TV®, Amazon Fire TV®, or your mobile device
- Easy video exporting via USB
- Rack ears included (H16HRLN and H24HRLN)

*with Speco Smart Analytic IP Cameras

Additional Features

- Supports different recording types: continuous, motion, analytics, and sensor
- Create bookmark pins on playback for easy reference
- Instant playback for individual channels directly from the live view screen
- Customizable channel view placement
- Remote monitoring, recording, playback, configuration, upgrades, and PTZ control via the internet
- Simultaneous HDMI & VGA video output
- Built-in S.M.A.R.T technology (Self-Monitoring, Analysis and Reporting Technology for HDD)
- Supports 2-way audio communication (speaker required)

Compatible Apps



One app to view your Speco Devices on the go (Speco Silver Line not supported at this time).



Access your NR and HR Series Recorder to view and playback videos from your camera.



Front View H24HRLN



Back View H24HRLN



specoaccess



Storage 2TB - 40TB

H6HRLN2TB	H6HRLN8TB	H6HRLN16TB
H6HRLN4TB	H6HRLN10TB	H6HRLN20TB
H6HRLN6TB	H6HRLN12TB	
H16HRLN2TB	H16HRLN10TB	H16HRLN24TB
H16HRLN4TB	H16HRLN12TB	H16HRLN32TB
H16HRLN6TB	H16HRLN16TB	H16HRLN40TB
H16HRLN8TB	H16HRLN20TB	
H24HRLN2TB	H24HRLN10TB	H24HRLN24TB
H24HRLN4TB	H24HRLN12TB	H24HRLN32TB
H24HRLN6TB	H24HRLN16TB	H24HRLN40TB
H24HRLN8TB	H24HRLN20TB	

Included Accessories



(1) USB Mouse



(1) Remote Control



For H16HRLN & H24HRLN
(1) Included Rack ears

Optional Accessories



P4S5G
5-Port Gigabit Network Switch
(4 ports PoE, 1 ports uplink)



P8S10G
10-Port Gigabit Network Switch
(8 ports PoE, 2 port Uplink)



ERS1V
Vented Rack Shelf



P24S26G
26-Port Gigabit Network Switch
(24 ports PoE, 2xSFP Uplink)



P32S36GM
36-Port Managed Gigabit Switch
(32 ports PoE, 4xSFP Uplink)

Technical Specifications Video Recorder

Model		HRLN Series		
Channels		6	16	24
System	Compression	Standard H.265		
	OS	Embedded Linux		
Video	Analog Only Input	BNC x4	BNC x8	BNC x16
	Configurable Analog Inputs	4	8	8
	IPC Only Input	2CH (up to 6-CH)*	8CH (up to 16-CH)*	8-CH*
	Network Access & Transfer Bandwidth	16/40Mbps	32/96Mbps	64/192Mbps
	Network Access Format	8MP/5MP/4MP/3MP/1080P/960P/720P@ 25/30fps		
	Output	HDMIx1: 4Kx2K/1920x1080/1280x1024 VGAx1: 1920x1080/1280/x1024/1024x768 BNCx1: CVBS (used as the main or spot output)		
Audio	Input	RCAx4	RCAx8	
	2-way Audio	Take up channel one audio input		
	Local Output	RCAx1		
Record	Record Stream	Dual stream recording		
	Resolution	4K/5MP/4MP/1080P/720P/WD1		
	Frame Rate	Analog: 5MP@ 12fps (PAL/NTSC), 4MP/3MP@ 12fps/15FPS (PAL/NTSC), Under 4MP@ 25fps/30fps (PAL/NTSC) IP: 8MP@ 20fps (PAL/NTSC), Under 8MP@ 25fps/30fps (PAL/NTSC)	Analog: 5MP@ 12fps (PAL/NTSC), 4MP/3MP@12fps/15FPS (PAL/NTSC), Under 4MP@ 25fps/30fps (PAL/NTSC) IP: 8MP and under@ 25/30fps (PAL/NTSC)	
	Bit Rate	32-78Mbps		
	Mode	Manual, schedule, motion, sensor, intelligence		
	IP Input	Resolution	8MP/5MP/4MP/3MP/1080P/960P/720P@25fps/30fps	
Playback	Simultaneous Playback	Max 4-CH	Max 8-CH	Max 16-CH
	Search Mode	EZ Search, museum search, time search, event search, bookmark search, snapshot search		
	Smart Search	Highlighted color to display camera records in a certain period of time, different colors refer to different record events		
	Function	Play, pause, FF, FB, etc.		
Alarm	Mode	Manual, sensor, motion, exception, intelligence		
	Input	4-CH local alarm input; Support IPC alarm input	8-CH local alarm input; Support IPC alarm input	16-CH local alarm input; Support IPC alarm input
	Output	1-CH local alarm input; Support IPC alarm input	2-CH local alarm input; Support IPC alarm input	4-CH local alarm input; Support IPC alarm input
	Linkage	Record, snapshot, preset, e-mail, pop-up window, etc.		
Network	Interface	RJ45 10M/100Mbps x1	RJ45 10M/100M/100Mbps x1	
	Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, HTTP, HTTPS, RTSP		
	Web Client	Multiple online users monitoring		
Mobile Device	OS	Speco Blue iOS®, Android™, SecureGuard® Client		
Other Viewing Platforms		Apple TV® and Amazon Fire TV®		
Storage	HDD	SATAx1, max 20TB per HDD	SATAx2, max 40TB per HDD	
	eSATA	eSATAx1 max 8TB		
Export	Local	USB, USB mobile HDD		
	Network	Yes		
Interface	USB	USB2.0x2		
	Remote Control	Yes		
Dimensions	Power Supply	DC12V/2A	DC12V/4A	
	Power Consumption	≤10W(without HDD)	≤15W(without HDD)	≤30W(without HDD)
	Dimensions(WxDxH)	11.8" x 9.8" x 1.8" (300mm x 248mm x 45mm)	15" x 10.6" x 1.8" (380mm x 268mm x 45mm)	
	Working Environment	14°F to 122°F (-10°C to 50°C)		



Products are in compliance with NDAA Section 889 Part B Guidelines. Google Chrome® and Firefox® use Java™ which requires an initial internet connection. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™, Google Play® and the Google Play logo® are trademarks of Google Inc. Amazon® is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 4/15/25

