



# HD-TVI 2MP IR Bullet Camera with Junction Box

## VLBT6W

2.8-12mm varifocal lens, white housing



### Features

- Full HD resolution over coax (HD-TVI)
- Supports up to Full HD 1080p @ 30fps
- 35 built-in IR LEDs
- Signal distance up to 1600 ft.
- Full OSD operation through on-board control and UTC (up the coax)
- 12VDC operation (power supply not included)
- True WDR
- Multi-format HD (TVI, CVI, AHS, CVBS) \*
- IP66 compliant, weather resistant
- 5 year warranty



Included Junction Box



### Camera Specifications

Image Sensor	1/2.8" CMOS
Maximum Resolution	1920 x 1080
Minimum Illumination	Color: 0.001lux @ F1.2
S/N Ratio	greater than 52dB
Motion Detection	Yes
Number IR LEDs	35
IR Range	98' (depending on scene reflection)
Day/Night	IR cut filter
DNR	Yes
Video Output	TVI / CVI / AHD / CVBS
Field of View (Horizontal)	99.8° - 36.8°
Field of View (Vertical)	67.4° - 21.2°

### Operating & Unit Specifications

Power	12VDC (power supply not included)
Power Consumption	IR on (less than 1W) IR off (less than 4W)
Operating Temperature	-4°F - 104°F
Unit Dimensions	3.43" (Dia.) x 8.62" (L)
Unit Weight	1.3 lbs.

### Optional Accessories



CMT1  
Corner Mount



PMT1  
Pole Mount



CLT1  
Ceiling Mount



PSW5  
12VDC  
Power Supply



TVIUTPPT  
HD Video Transceiver  
with Pigtail (Balun)



TVIUTP  
HD Video  
Transceiver



CLTX1  
Ceiling Mount  
4" Extension



CLTX2  
Ceiling Mount  
8" Extension

\* Camera is defaulted to HD-TVI. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 5/26/20