

# 4K Plug & Play Network Wall Mount Video **Recorder with Built-In PoE**

### N8WNU

8 Channel NVR with 8 Built-In PoE+ Ports

#### **N16WNU**

16 Channel NVR with 16 Built-In PoE+ Ports

#### **N8WNUM**

8 Channel NVR with 8 Built-In PoE+ Ports with Built-In Monitor

#### N16WNUM

16 Channel NVR with 16 Built-In PoE+ Ports with Built-In Monitor















Use





# **Key Features**

### EZ Wizards - For ease of use and setup

Camera: quickly discover and install all Speco IP cameras

Setup: for quick setup of general settings

Network: network setup and port forwarding

Record: quickly setup recording resolutions and recording type

Search: quickly search for events from thumbnails

Copy: quickly copy what you are playing onto a USB flash drive

- Supports up to 4K (3840x2160) resolution for live view, recording, and playback
- Video out: 1 HDMI, 1 VGA, 1 Main, Spot
- Plug & play feature for Speco IP cameras with isolated traffic on the PoE ports
- Find and install IP cameras on the local network without needing to locate the cameras manually
- Supports H.265 and H.264 streams
- Programmable recording on motion detection, sensor, schedule, continuous and manual modes
- Smart (Museum) Search Quickly search for a specific video event without the need for motion setup
- Networkable with free US-Based Speco DDNS service
- Up to 40TB storage from 4 internal SATA ports
- RAID 1/5/10 support, RAID maximum capacity 16TB
- eSATA port for additional storage
- External DAS supported, up to 40TB
- 2-way audio communication
- Digital Deterrent® for triggering audio message via an event
- Built-in S.M.A.R.T technology (Self-Monitoring, Analysis and Reporting Technology for HDD)



















#### **Additional Features**

- Remote monitoring / recording / playback / configuration / software upgrades and PTZ control via internet
- Mass alert notification via Twitter
- HTTPS support for third party SSL certificates
- Switch between low and high quality stream during simultaneous continuous + motion + sensor recording modes for storage optimization
- Easy firmware upgrade by USB port or network
- Network software supports Static IP, DHCP and DDNS
- Network accessible via SpecoTech Multi-Client Software, SecureGuard® VMS, Internet Explorer Web-Viewer and Speco Player Mobile Viewer, Apple TV and Amazon Fire TV
- PC and MAC® compatible
- IR remote control & mouse included
- 5 year limited warranty
- Ul listed

1 For supported IP camera models. 2 Limited Warranty/Hard drives excluded. Check www.specotech.com for more details. iPhone is a trademark of Apple Inc., registered in the U.S. and other countries. Android is a trademark of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 4/25/22













## **Technical Specifications:**

WNU 4K Plug & Play Network Wall Mount Video Recorder with Built-In PoE

Model			NU	
Video		Max. IP Channels	8 16	
	Input	Camera	H.265/H.264 Auto Detection (Max. 4K)	
	Output	Main Monitor	HDMI (Max. 4K) and VGA (Max. Full HD)	
		Sub Monitor	CVBS or SPOT (Selectable)	
		Input/Output	8/1	16/1
Audio	Audio Codec		G.711	
	2-Way Audio		Local Audio - Network Client, Local Audio - IP Camera	
Alarm	Input/Output		4/1	
Serial	RS-485		1	
	Compression		H.265/H.264 (Auto Detection)	
	M	ax Bitrate per Channel	4K @ 8Mbps	
	Max Frame Rate per Channel		Any Resolution @ 30fps	
Recording	Recording Mode		Continuous / Motion / Sensor / Schedule / Manual	
	Pre-Recording		Max. 20 seconds	
	Post Recording		Max. 60 seconds	
Playback	Search		Quick, Date/Time, Archive, Log	
	Multi-Decoding		1, 4, 8	
	Playback Speed		x0.25, x0.5, x2, x4, x8, x16, x32, & x64	
Васкир	Media		USB flash drive, External HDD, Network	
	Format		BMP, AVI, EXE (Player + Data), NSF (Proprietary Format)	
	Huge Backup		Yes (Max. 24 hours)	
	HDD	Capacity of 1 HDD	Up to 10TB	
		Internal HDDs	4	
		RAID	RAID 1/5/10, RAID Maximum Capacity 16TB	
Storage		e-SATA	1	
		Extension	External DAS (Max. 40TB, RAID)	
		Front	2	
	ОЗВ	Rear	1	
User I/F	er I/F Input Method		IR Remote Controller, Mouse, Keyboard Controller (Option)	
	Network Interface		1 Gbps + 8 PoE 1 Gbps + 16 PoE	
Network	Dynamic DNS		Yes (Free Speco US-based DDNS)	
	Sub-stream for Network		Max. 640x360 @ 30fps / Channel	
	Digital Zoom		Free Size on Live & Playback mode	
Features	NTP (Network Time Protocol)		Once, Time, and Periodic	
	S.M.A.R.T.		Temperature, Power on Time, Bad Sector and Health	
	Multi-Language		Support	
	System Event Notification		Health, Restart, Shutdown, Panic, Alarm, Motion, HDD, Fan	
Network	3G/4G Mobile		iPad / iPhone / Android	
	Web Viewer		Windows (IE Ver.11)	
Access	PC Client		SecureGuard® VMS and SpecoTech Multi Client (Live Search, Backup, PTZ, Remote Setup)	
	Remote Setup and Upgrade		Simple Web Setup and Upgrade	
	Power Supply Voltage		100~240V AC	
_	PoE Ports		8	16
Power	Power Per PoE Ports		8 Ports @ 7W, 7 Ports 15.4W, or 3 Ports @ 30.8W	16 Ports @ 7W, 12 Ports 15.4W, or 6 Ports @ 30.8W
	Total PoE Power Budget		110W	185W
Temperature	Operation		41°F ~ 104°F (5°C ~ 40°C)	
Temperature	Storage		14°F ~ 122°F (-10°C ~ 50°C)	
Humidity	Operation		20% ~ 80% (Non-condensing)	
Weight	Unit Weight (Gross Weight)		9.0 lbs (13.6 lbs) 4.1 Kgs (6.2 Kgs)	
Dimensions	Unit	Dimensions (W x H x D)	16" (W) × 19" (H) × 3.5" (D)	









Please note that specifications and unit exterior design are subject to change without notification. Rev. 4/25/22











