



# 2MP Intensifier<sup>®</sup> Board IP Camera

## O2iBD3

2.9mm fixed lens and 3.6mm pinhole lens included



### Features

- See color in low light without IR LEDs
- Miniature board design is perfect for tight spaces
- Supports up to 1080p @ 30fps
- Built-in standard PoE (IEEE 802.3af)
- No problems caused by objects that reflect or absorb IR light sources
- 2-way audio communication
- Sensor input and relay output
- Micro SD card slot (card not included)
- Conformant with ONVIF Profile S
- 5 year warranty\*



### Camera Specifications

Image Sensor	Progressive scan 1/2.8" CMOS, 2MP
Maximum Resolution	1920 x 1080
Minimum Illumination	F1.4, color: 0.2 lux (max. Intensify)
Field of View	86° Horizontal, 45° Vertical
White Balance	ATW / AWB
Intensify	Selectable (max. 32x) / Off
Compensation	WDR
Electronic Shutter Speed	1/30 - 1/10000 sec
DNR	2D/3D

### Video Specifications

Main Resolution	1920x1080 / 1280x720 @ 30fps
Compression	H.264 (HP/MP/BP), MJPEG
Bitrate Control	VBR, CBR
Multiple Streaming	3 streams

### Network Specifications

Protocols	IPv4, TCP, UDP, RTP, RTSP, HTTP, SMTP, FTP, DHCP, UPnP, DNS
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP address filtering, digest authentication
User Access	Max. 8 simultaneous users, Actual number of users may vary depending on bandwidth

### Audio Specifications

Mono Input	G.711
Mono Output	G.711

### Client Specifications

Web Browser Support	Windows (Internet Explorer 8 and up)
PC Application	SecureGuard <sup>®</sup> VMS
Mobile Application	SecureGuard <sup>®</sup> Mobile (iPhone <sup>®</sup> and Android <sup>™</sup> )
Other Viewing Platforms	Apple TV and Amazon TV

### External Terminal Specifications

Ethernet	10/100 Mbps
Alarm	1 sensor input, 1 relay output (terminal block)
Audio	1 mic in, 1 line out (terminal block)
Power	Terminal block

### System Specifications

PoE	Standard (IEEE 802.3af)
Analytics	Motion detection, tampering, sensor input
Alarm Triggers	Analytics
Alarm Events	FTP upload, email upload, micro SD card recording, relay output
Image Settings	Privacy mask

### Operating & Unit Specifications

Power	PoE, 12VDC (power supply not included)
Power Consumption	4W
Operating Temperature	14°F - 122°F
Operating Humidity	0% - 90% RH
Unit Dimensions	2.59" (W) x 1.24" (H) x 4.21" (D)
Unit Weight	4 oz.
Certifications	FCC, RoHS

**NDA A**  
COMPLIANT

\*Products are in compliance with NDA A Section 889 Part B Guidelines

### Optional Accessories



POEINJ  
12.95W  
PoE Injector

PSW5  
12VDC  
Power Supply

\* Effective on all new purchases as of 2/1/17. ONVIF<sup>®</sup> is a trademark of ONVIF, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/24/22