

2MP H.265 Intensifier® Bullet IP Camera with Junction Box

O2iB92

2.8mm fixed lens, dark gray housing













Features

- Supports up to 2MP (1920 x 1080) @ 30fps
- Intensifier® amplifies color and light in dark scenes Supports H.265 and H.264 codecs

• 5 Year Warranty

- Built-in standard PoE (IEEE 802.3af)
- IP66 compliant
- Conformant to ONVIF Profiles S
- UL Listed





Camera Specifications	
Image Sensor	Progressive scan, 2M pixels
Maximum Resolution	1920 x 1080
Main Field of View (H)	110°
White Balance	Auto
Compensation	WDR (108dB), BLC, HLC
Electronic Shutter Speed	1/25(30) ~ 1/100,000 sec.
S/N Ratio	>40dB

Compensation	WDR (108dB), BLC, HLC
Electronic Shutter Speed	1/25(30) ~ 1/100,000 sec.
S/N Ratio	>40dB
Video Specifications	
Main Resolution	1280x 720 (720P) 1920x 1080 (1080P)

Video Specifications	
Main Resolution	1280x 720 (720P) 1920x 1080 (1080P)
Compression	H.265, H.264
Bitrate Control	20Kbps to 10Mbps
Multiple Streaming	2 streams

Network Specifications	
Protocols	TCP/IP, UDP, SMTP, PPPoE, DDNS, SNTP, DHCP, FTP, UPnP, RTSP, HTTPS, IPv6
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/Mac address filtering, digest authentication
Maximum Users	10

Client Specifications	
Web Browser Support	IE 10/11
PC Application	SecureGuard® VMS
Mobile	SecureGuard® Mobile (iPhone® and Android™)

Audio Specifications	
Mono Input	N/A
Mono Output	N/A

External Terminal Specifications	
Ethernet	10/100 Mbps
Power	DC12V±10%, POE
Analog Video Output	N/A
Microphone Input	N/A

System Specifications	
PoE	Standard (IEEE 802.3af)
Analytics	Manual, Timing, Motion Detection
Alarm Triggers	Motion Detection
Alarm Events	Snapshot, Video, Alarm Output, Email Upload
Image Settings	Hue, Contrast, Brightness, Sharpness, Saturation

Operating & Unit Specifications	
Power	DC12V±10%, POE (power supply not included)
Power Consumption	250mA (Max.)
Operating Temperature	-22°F - 104°F
Operating Humidity	0% - 90% relative humidity
Unit Dimensions	3.66" (W) x 5.1" (H) x 6.5"(D)
Unit Weight	1.63 lbs.
Certifications	FCC, RoHS, CE & UL

Optional Accessories



O3PMT Pole Mount



POEINJ 12.95W PoE Injector



PSW5 12VDC **Power Supply**

ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 4/16/19







