


Analog Specialty Camera Comparison Chart

Category	Intensifier® K	1000 TV Lines	Intensifier H®	Intensifier H®	960H	960H	960H
Model	HTINT40K	CVC521BCK	HINT600H	HINT600VH	CVC585RC	CVC605CM	CVC607CMTP
Product Image							
Resolution	1000 TV Lines	1000 TV Lines	700 TV Lines	700 TV Lines	700 TV Lines	700 TV Lines	700 TV Lines
Lens	3.6mm fixed lens	3.6mm fixed lens	2.9mm fixed lens	2.8-12mm lens	3.6mm wide angle lens	3.6mm lens	3.6mm lens
Image Sensor	1/3" 1.3MP Sensor	1/3" 1.3 Mega Exmor Sensor	1/3" color 960H CCD	1/3" color 960H CCD	1/3" Super HAD II™ color CCD	1/3" Super HAD II™ color CCD	1/3" Super HAD II™ CCD
Minimum Illumination	0.0001 lux	0.00001 lux	CDS Off: 0.1 lux CDS On: 0.00002 lux	CDS Off: 0.1 lux CDS On: 0.00002 lux	0.001 lux (sense-up on)	0.001 lux (sense-up on)	0.001 lux (sense-up on)
Effective Pixels	1305 (H) x 1049 (V)	1305 (H) x 1049 (V)	976 (H) x 494 (V)	976 (H) x 494 (V)	976 (H) x 494 (V)	976 (H) x 494 (V)	976 (H) x 494 (V)
Total Pixels	1312 (H) x 1069 (V)	-	1020 (H) x 508 (V)	1020 (H) x 508 (V)	1020 (H) x 508 (V)	1020 (H) x 508 (V)	1020 (H) x 508 (V)
WDR	Yes	-	-	-	-	-	-
Number of IR LEDs	-	-	-	-	-	-	-
IR Range (depending on scene reflection)	-	-	-	-	-	-	-
Power Supply	12VDC	12VDC	12VDC	12VDC	12VDC	12VDC	12VDC
Power Consumption	120mA	80mA	150mA	150mA	230mA	230mA (color) / 90mA (BW)	230mA
Operating Temperature	-4° F - 140° F	14° F - 122° F	14° F - 122° F	14° F - 122° F	14° F - 122° F	14° F - 122° F	14° F - 122° F
Dimensions	1.34" (W) x 1.34" (H) x 1.18" (Dia.)	1.65" (W) x 1.65" (H)	1.6" (W) x 1.4" (H) x 2.5" (L)	1.6" (W) x 1.4" (H) x 3.5" (L)	1.5" (L) x 11" (W) x 11" (H)	9" (W) x 7" (H) x 4 (L)	5.1" (W) x 3.3" (H)
Weight	10.56 oz.	3.5 oz.	5.5 oz.	6 oz.	1.5 lbs.	1.4 lbs.	1.5 lbs.
Additional Features	Miniature Board Camera	Miniature Board Camera	Miniature Board Camera	Miniature Board Camera	Clock Camera	92° Corner Mount Camera	90° Corner Mount Camera, Vandal Resistant

Analog Specialty Camera Comparison Chart

Category	960H	960H	960H	960H	960H	960H, PIR	Analog, IR
Model	CVC675	CVC695AM	TC23	VL562SD	WDR705H	VL572PIR	TC25VF
Product Image							
Resolution	700 TV Lines	700 TV Lines	700 TV Lines	700 TV Lines	700 TV Lines	700 TV Lines	580 TV Lines
Lens	3.6mm lens	3.6mm wide angle lens, horizontal 72° / vertical 53°, color	2.9mm lens	3.7mm lens	4mm fixed lens	3.6mm pinhole lens, non-operating PIR	2.6-6mm lens
Image Sensor	1/3" Super HAD II™ color CCD	1/3" Super HAD II™ color CCD	1/3" Super HAD II™ color CCD	1/3" Super HAD II™ color CCD	1/3" 960H HAD™ CCD (dual scan)	1/3" 960H CCD	1/3" double speed Super HAD II™ CCD
Minimum Illumination	0.001 lux (sense-up on)	0.001 lux (sense-up on)	0.01 lux low light sensitivity	0.001 lux (sense-up on)	0.000006 lux	1.0 lux	0 lux within a 10 ft. range, 0.03 lux beyond 10 ft.
Effective Pixels	976 (H) x 494 (V)	976 (H) x 494 (V)	-	-	976 (H) x 494 (V)	-	-
Total Pixels	-	-	-	-	1028 (H) x 508 (V)	-	-
WDR	-	-	-	-	Yes	-	-
Number of IR LEDs	-	-	-	-	-	-	16
IR Range (depending on scene reflection)	-	-	-	-	-	-	-
Power Supply	12VDC regulated	12VDC	12VDC / 24VAC dual voltage operation	12VDC regulated	12VDC	12VDC	12VDC / 24VAC auto sensing dual voltage operation
Power Consumption	110mA	210mA	12VDC, 230mA / 24VAC, 5.5W	230mA	160mA	120mA (non-operating PIR), 130mA (operating PIR)	12VDC, 230mA / 24VAC, 5.5W
Operating Temperature	14° F - 122° F	14° F - 122° F	14° F - 122° F	14° F - 122° F	-4° F - 140° F	14° F - 122° F	14° F - 122° F
Dimensions	2.75" (W) x 4.25" (H) x 2.75" (L)	2.25" (W) x 2.75" (H) x 2.5" (L)	24" (H) x 2.75" (D)	3.4" (Dia.) x 1.75" (H)	1.34" (W) x 1.34" (H) x 1.38" (L)	2" (L) x 2.75" (W) x 4.75" (H)	24" (H) x 4.7" (D)
Weight	3.45 oz.	6.08 oz.	5 lbs.	4.5 oz.	12.48 oz.	9 oz.	4.5 lbs.
Additional Features	In-Wall Camera, Color or BW	Angle Mount Camera, Color	Color Facial Identification Camera	Discreet Ceiling Mount Camera	Indoor Color Board Camera	CCTV Operating PIR Housing	Color Facial Identification IR Tower Camera