

SP6CSL 2 x 3", white housing, 8 Ohms

Features

- Mounting depth of 2" means this speaker can fit into the tightest of ceilings
- 5 total speakers (2 Woofers, 2 Midrange and 1 Tweeter) helps maintain great sound even with the limited space
- Magnetic Grille helps ensure an easy installation

| Speaker Specifications | |
|----------------------------|--|
| RMS Output Power | 30W |
| Max Output Power | 60W |
| Sensitivity (1W/1M) | 90dB |
| Maximum SPL (Pmax/1M) | 106dB |
| Impedance | Woofer: 16 Ohms Midrange: 16 Ohms Tweeter: 8 Ohms |
| Magnet Material and Weight | Ferrite, 3 oz woofer, 2.6 oz midrange |
| Frequency Response Range | 125Hz - 20kHz |
| Dispersion | 150° |
| Driver | 3" coated paper cone, rubber edge woofer 3" coated paper cone, rubber midrange .75 silk dome tweeter |

| Operating Specifications | |
|--------------------------|--------------------|
| Dimensions | 11" (D) x 2.3" (H) |
| Mounting Depth | 2" |
| Cutout Dimensions | 9.6" |
| Speaker Weight | 4.4 lbs |
| Speaker Body Material | ABS |
| Speaker Grille Material | Steel |







Includes Grille



Side View

Optional Accessories

| | | | |
|---|--|---|--|
|  BRC8F Ceiling Tile Mount Bracket |  T7020 20W 70V Line Transformer |  T7010 10W 70V Line Transformer |  T70255 5W 70/25V Dual Transformer |
|---|--|---|--|