

# A&E Specification

## D8HU, D16HU Hybrid Video Recorder

**Speco Technologies**  
200 New Highway, Amityville NY 11701  
Tel. 1-800-645-5516 Fax. 1-631-957-3880  
Web site: [www.specotech.com](http://www.specotech.com)

---

<b>Division 28</b>	Electronic Safety and Security
<b>Section 28 00 00</b>	Electronic Safety and Security
<b>Section 28 20 00</b>	Electronic Surveillance
<b>Section 28 23 00</b>	Video Surveillance

**Notes to Security System Specifiers** - This A&E specification is written according to Construction Specifications Institute (CSI) 3-Part Format, based on MasterFormat™ (2016 Edition) and The Project Resource Manual – CSI Manual of Practice. CSI MasterFormat 2016 incorporates numerous significant changes affecting electronic safety and security. This document is written to provide flexibility in using either format, although adoption of MasterFormat 2016 is encouraged. All trademarks are properties of their respective owners.

---

## Part 1 General

### 1.1. Summary of Requirements

#### A. HU Series Hybrid Video Recorder (HVR)

1. The HVR shall collect multiple channels of HD-TVI/IP video, multiple channels of audio and digitize them for the purpose of display, archive and requested distribution across the Ethernet network.

#### B. Related Requirements

1. Section 28 05 00 Common Work Results for Electronic Safety and Security
2. Section 28 05 19.11 Digital Video Recorders
3. Section 28 05 19.13 Hybrid Digital Video Recorders
4. Section 28 05 19.15 Network Video Recorders
5. Section 28 21 00 Surveillance Cameras
6. Section 28 21 13 IP Cameras
7. Section 28 23 13 Digital Video Recorders and Analog Recording Devices

### 1.2. References

#### A. Abbreviations

1. DDNS Dynamic Domain Name Server
2. DHCP Dynamic Host Configuration Protocol
3. DNS Domain Name Server
4. FTP File Transfer Protocol
5. GUI Graphical User Interface
6. HTTP Hypertext Transfer Protocol
7. HTTPS Secure HTTP
8. ICMP Internet Control Message Protocol
9. IGMP Internet Group Management Protocol
10. IP Internet Protocol

# A&E Specification

## D8HU, D16HU Hybrid Video Recorder

**Speco Technologies**  
200 New Highway, Amityville NY 11701  
Tel. 1-800-645-5516 Fax. 1-631-957-3880  
Web site: [www.specotech.com](http://www.specotech.com)

---

11. JPEG	Joint Photographic Experts Group
12. MPEG	Moving Pictures Experts Group
13. NAS	Network Attached Storage
14. NIC	Network Interface Controller
15. NTP	Network Time Protocol over Ethernet
16. NVR	Network Video Recorder
17. HVR	Digital Video Recorder
18. HVR	Hybrid Video Recorder
19. PoE	Power over Ethernet
20. PPPoE	Point-to-Point Protocol over Ethernet
21. P2P	Peer-to-Peer
22. PTZ	Pan Tilt Zoom
23. QoS	Quality of Service
24. RTP	Real-Time Transport Protocol
25. RTSP	Real-Time Streaming Protocol
26. SD Card	Secure Digital Flash Memory Card
27. SMTP	Simple Mail Transfer Protocol
28. TCP	Transmission Control Protocol
29. UDP	User Datagram Protocol
30. UPnP	Universal Plug and Play
31. VMS	Video Management System
32. ESD	Electrostatic discharge
33. MSIE	Microsoft Internet Explorer
34. HDD	Hard Disk Drive
35. EZ	Easy
36. FF	Fast Forward
37. FR	Fast Reverse
38. DAS	Direct Attached Storage
39. LAN	Local Area Network
40. WAN	Wide Area Network

### 1.3. Certifications, Standards and Ratings

#### A. Reference Standards

1. Networking
  - a. IEEE – 802.3 Ethernet Standards
2. Video
  - a. ISO/IEC 14496 Standards for MPEG-4
  - b. ITU-T Recommendation H.264/H.265

**1.4. Submittals**

**A. Product Data**

1. Provide manufacturer's datasheets in printed or electronic form.
2. Provide manufacturer's Installation and operating manuals/guides.
3. Provide manufacturer's warranty statement.

**1.5. Qualifications**

**A. Manufacturer**

1. Company specializing in manufacturing products at least ten years experience.

**C. Supplier**

1. Authorized distributor of specified manufacturer with at least 5 years.

**D. Installer**

1. Authorized installer of specified manufacturer with a least 5 years experience.

**1.6. Delivery, Storage and Handling**

**A. Delivery**

1. Deliver materials in original, unopened and undamaged packaging in accordance with manufacturer's instructions.

**E. Storage**

1. Store and guard materials from environmental and temperature conditions in accordance with manufacturer's instructions.

**F. Handling**

1. Handle and operate products and systems in accordance with manufacturer's instructions.

**1.7. Warranty**

**A. Warranty Period**

1. Manufacturer shall warranty HVR (except HDD) for a period of [5] years for the repair or replacement of defective equipment.
2. Manufacturer shall warranty HDD for a period of [3] years.

**1.8. Certifications**

**B. Certification Types**

1. CE (EMC/LVD)
2. FCC, Class A
3. RoHS

**1.9. Tech Support**

**A. Support**

1. Technical support shall be based in North America.
2. Technical support support shall be via email or toll-free phone number.
3. Technical support shall be available weekdays from 6 a.m. to 6 p.m. EST.

## **Part 2 Product**

### **2.1. Manufacturer**

#### **A. Manufacturer**

1. Speco Technologies  
200 New Highway  
Amityville, NY 11701  
Tel. 1-800-645-5516 Fax. 1-631-957-3880  
Web Site: [www.specotech.com](http://www.specotech.com)

#### **G. Product**

1. HU Series
2. Models:
  - a. D8HU1TB, D8HU2TB, D8HU3TB, D8HU4TB,  
D8HU6TB, D8HU8TB, D8HU12TB, D8HU16TB,  
D8HU20TB, D8HU24TB, D8HU30TB, D8HU32TB,  
D8HU40TB
  - b. D16HU2TB, D16HU4TB, D16HU6TB, D16HU8TB,  
D16HU12TB, D16HU16TB, D16HU20TB, D16HU24TB,  
D16HU30TB, D16HU32TB, D16HU40TB

#### **H. Product Description**

1. A 4K HD-TVI/IP HVR capable of up to 16 channels of video.

## **2.2. Product Description**

#### **A. General**

1. All equipment and materials used shall be standard components, regularly manufactured, regularly utilized in the manufacturer's system.
2. All systems and components shall have been thoroughly tested and proven in actual use.
3. All systems and components shall be provided with the availability of a toll free technical support phone number from the manufacturer. The phone number shall allow for immediate technical assistance for either the dealer/installer or the end user at no charge.
4. All systems and components shall be provided with an explicit manufacturer warranty.

#### **B. Description**

1. HVR shall meet the requirements of business, government and general security surveillance applications.
2. HVR shall offer remote network connectivity to a properly specified PC computer that allows transmission of video and control data over the Ethernet network.

## A&E Specification

### D8HU, D16HU Hybrid Video Recorder

**Speco Technologies**  
200 New Highway, Amityville NY 11701  
Tel. 1-800-645-5516 Fax. 1-631-957-3880  
Web site: [www.specotech.com](http://www.specotech.com)

3. HVR shall offer a GUI incorporating video display areas, toolbars, control palettes and site/device trees.
4. HVR shall support 8MP over coax (HD-TVI)
5. HVR shall support network based cameras.
6. HVR shall employ a high profile H.264 compression algorithm in the video digitizing scheme. Network IP cameras shall be the primary video input devices.
7. HVR shall support plug-n-play feature with Speco's OnSIP/VIP/ZIP cameras.
8. HVR shall offer simultaneously view live or playback while continuing to record and network transfer. The HVR shall provide full digital video and audio surveillance over a standard 100Base-T network.
9. HVR shall allow playback of 1 channel while the rest stays in live mode.
10. HVR shall support signal distance of up to 1600 feet while preserving signal quality.
11. HVR shall offer multiple continuously recorded digital video and audio channels onto a hard drive medium. Each channel of video data shall have the capability of being recorded, displayed, played back, archived and distributed simultaneously across the network.
12. The video shall also be capable of alarm notification based on motion via a built-in utility to configure motion detection of objects in the individual camera scenes. Each camera can be customized for motion area and sensitivity using grid blocks through the camera's setup tool. The motion events shall be transmitted to authorized users via an email notification utility.
13. The video shall also have selectable digital zoom on any camera in live view and playback mode. The video recording capability shall be fully scheduled using the built-in utility.
14. HVR shall also have full WAN and Internet connection capability. The HVR will require a broadband internet connection of a minimum 256 Mbps using either a static or dynamic type IP address. When using a dynamic IP address, DDNS shall be an available feature to track the IP address via a customized URL. The HVR supports TCP/IP and DHCP protocol.
15. HVR shall record user selectable resolution and frame rate set from within the GUI of the IP cameras.
16. HVR shall support RAID 1/5/10 user-selectable configurations.
17. HVR shall utilize a Digital Signature video authentication algorithm. It is a standard authentication that is based on a 128-bit message used to verify data integrity
18. HVR shall incorporate a series of EZ (easy) features used to simplify installation and configuration of the unit. These features shall include EZ-Setup, EZ-Network, EZ-Camera, EZ-Record, EZ-Copy and EZ-Search.
19. HVR shall support searching of recorded video from EZ Search, motion events, analytic events, date/time, museum, bookmarks, snapshots and logs.
20. HVR shall support the following playback functions: play, pause, FF, FR, and Digital Zoom.

## A&E Specification

### D8HU, D16HU Hybrid Video Recorder

**Speco Technologies**  
200 New Highway, Amityville NY 11701  
Tel. 1-800-645-5516 Fax. 1-631-957-3880  
Web site: [www.specotech.com](http://www.specotech.com)

21. On event, HVR shall trigger recording, control PTZ, Alarm Out, Pop-up alarm preview, send email, FTP, record snapshot, and activate buzzer and screen tips.
22. HVR shall be able to record events to Google Drive.
23. HVR shall offer 2 network interface to allow one interface for separating camera and LAN network traffic.
24. HVR shall support ONVIF Profile S compliant cameras.
25. HVR shall be TAA compliant.
26. HVR shall offer a full multi-user authorization logon function. This function shall offer five levels of authorization based on Main Menu functions. There shall be an Administrator and User level offered. Anyone with a correct password shall log into the HVR.
27. HVR shall offer a GUI capable of complete recorder configuration and operation. Sub-features such as defined video display and control, component setup, recording setup, network setup and the use of dialog messages shall be provided in a comprehensive menu structure.
28. Operation of the system shall be facilitated by the use of a monitoring screen whereby a security operator can perform a full scope of surveillance duties using the front panel controls and indicators, the remote application software, the CMS software or a mouse.
29. HVR shall use a HDMI / VGA Main Monitor output for video display sequencing
30. HVR shall be configurable for several foreign languages, other than English.
31. HVR shall support the use of PTZ type cameras either on an RS-485 bus using built-in protocols from several manufacturers or through the network of the PTZ IP camera.
32. HVR shall support alarm in and relay out functions. The alarm events shall be transmitted to users via a built-in email utility.
33. HVR shall support a variety of different capacity hard drives.
34. The front panel shall contain a lights to indicate status of power on/off, HDD health and network connectivity.
35. HVR shall contain 2 x USB ports with one available on the front panel and one at the back of the unit.
36. HVR shall also be equipped for installation in a standard rack shelf. The rear panel shall contain WAN network port (RJ45) to connect to internet, HDMI Main Monitor, VGA Main Monitor Output, Audio In/Out inputs, eSATA, LAN (Network) port, and USB connector.
37. HVR shall support exporting of video in AVI format with a stand-alone player.
38. HVR shall support exporting video to the following media types: DAS and NAS
39. HVR shall support and be equipped with an IR remote control.
40. HVR shall support and include a Multi-Client application for multi-HVR remote access.
41. HVR shall support bi-directional audio.
42. HVR shall meet or exceed the following design and performance specifications
43. HVR shall support multi-time zone and DST.



# A&E Specification

## D8HU, D16HU Hybrid Video Recorder

**Speco Technologies**  
200 New Highway, Amityville NY 11701  
Tel. 1-800-645-5516 Fax. 1-631-957-3880  
Web site: [www.specotech.com](http://www.specotech.com)

---

3840x2160 (8MP)

f. HD-TVI Frame Rate	3840x2160 – 15fps/channel 2592x1944 – 20fps/channel 2688x1520 – 30fps/channel 2560x1440 – 30fps/channel 2304x1296 – 30fps/channel 1920x1080 – 30fps/channel
g. IP Frame Rate	3840x2160 – 15fps/channel
h. Pre-record	20 minutes max
i. Post-record	60 seconds max
j. Display Modes	1x1, 2x2, 3x3, 4x4, Custom
3. Audio	
a. Inputs	8 (D8HU) 16 (D16HU)
b. Outputs	1 (RCA)
c. Codec	G.711
4. Serial	1 x RS-485
5. Network	
a. WAN	1 x 10/100/1000 Base-TX (RJ45)
b. Protocol	TCP/IP, DHCP, DNS, DDNS, UPnP, NTP, SMTP
6. PTZ	Remote client
7. Alarms	
a. Inputs	8 (D8HU), 16 (D16HU)
b. Outputs	1
8. Auxiliary	
a. USB	2 x USB 2.0 Port (Front) 2 x USB 2.0 Port (Rear)
9. Front Panel	
a. Power Indicator	Power On, Blue
b. HDD Status	Recording, Blue
c. Network Indicator	Network access, Blue
10. User Interface	IR Remote, Mouse, Keyboard Controller
11. Remote Surveillance	
a. Web Viewer	MSIE, Firefox
b. Control System	Speco Technologies SecureGuard
c. Mobile Devices	iOS, Android
12. Storage	1 x eSATA (10TB, RAID 1/5/10) 4 x Internal HDD (10TB per HDD)



## **Part 3 Execution**

### **3.1 Examination**

- A. Device shall be inspected for physical and cosmetic defects.
- B. Package box shall include device, power supply, mouse, remote control unit, installation and user guides on disk.

### **3.2 Preparation**

- A. ESD-sensitive parts shall be properly protected against static buildup through the use of static shielding material.
- B. Package box shall contain adequate padding to prevent damage to device and parts during shipping.

### **3.3 Installation**

- A. Device shall be installed in accordance with the manufacturers' installation guide provided.
- B. Device shall be installed by qualified service professionals.
- C. Device shall be installed in accordance with the National Electric Code or applicable local codes.
- D. Device shall be installed in locations which adequately supports the device's environmental and electrical requirements.

### **3.4 Field Quality Control**

- A. Test for proper communication between device and supporting devices.
- B. Test for proper operation of device's system software and related software programs.
- C. Determine and report all problems to the manufacturers' customer service representatives.

### **3.5 Adjusting**

- A. Make all necessary adjustments to the device and supporting devices to ensure the proper operation of the device.
- B. Make all necessary adjustments to the devices to satisfy end-user requirements.

### **3.6 Demonstration and Training**

- A. Perform final inspection to validate and ensure proper functioning of device.