

# Gigabit Network Switches

**P4S5G** 5 Port Gigabit Network Switch (4 ports PoE, 1 port Uplink)

**P8S9G** 9 Port Gigabit Network Switch (8 ports PoE, 1 port Uplink)



## Features

- Gigabit performance on all ports (uplink and downlink)
- CCTV mode isolates each port from one another for added security and performance
- Includes built-in surge immunity

## Specifications

Model	P4S5G	P8S9G
Downlink Ports	4 x 10/100/1000 Base-T (PoE)	8 x 10/100/1000Base-T (PoE)
Uplink Ports	1 x 10 /100/1000 Base-T	1 x 10/100/1000BaseT & 1 x 1000Base-X SFP Port
Network Standards	IEEE 802.3/IEEE803.2u/IEEE802.3ab/IEEE802.3x	
PoE Standards	802.3af/at (PSE)	
Switch Capacity	10GBps	20GBps
Packet Forwarding Rate	7.44Mpps	14Mpps
Exchange Type	Storage & Forwarding	
MAC Address List	2K	4K
PoE Power Supply	1/2(+), 3/6(-)	
PoE Output	Single port ≤ 30W (54V DC), Total for all ports ≤ 60W	Single port ≤ 30W (54V DC), Total for all ports ≤ 120W
Surge Immunity	6KV : IEC61000-4-5	
ESD Protection	Contact discharge 6K, Air discharge 8KV, Per: IEC61000-4-2	Contact Discharge 6K, Air Discharge 8KV, Per: IEC61000-4-2
Voltage Input	DC 48V ~ 57V	
Power Consumption	5W	
Operation Temperature	14°F to 131 °F (-10°C to 55°C)	
Storage Temperature	-40°F to 185°F (-40°C to 85°C)	
Operation Humidity	5% - 95% (Non-condensing)	
Dimensions	(L x W x H): 5.3" x 3.4" x 1" (135mm x 85.6mm x 27mm)	(L x W x H): 7.9" x 4" x 1" (200mm x 101.8mm x 27mm)
Material	Metal	
Weight	0.7lbs (315g)	1.1lbs (500g)



Shown P4S5G



Shown P8S9G

**NDAA**  
COMPLIANT

\*Products are in compliance with NDAA Section 889 Part B Guidelines

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 2/24/22