

O8VB1

2.8mm fixed lens, white housing

Features

- Captures up to 8MP @ 20fps
- H.265/H.264 compression supported
- Built-in standard PoE (IEEE 802.3af)
- $\bullet\,$ True Day/Night operation (IR cut filter)
- IR range: up to 100' (depending on scene reflection)
- Digital WDR
- Micro SD card slot up to 128GB (card not included)
- Line crossing, region intrusion and video blurring detection
- ONVIF Profile T CompliantIP67 Weather Resistance
- Junction box included
- (works with NPT/BSP specifications)
- 5 year warranty



IR 4K H.265 (*) SD POE IP67

Included Junction Box

Camera Spe	cifications	5		
Image Sensor		Progressive scan 1/2.7" CMOS, 8MP		
Maximum Resolution		3840 x 2160 (8MP)		
Minimum Illumination		0.09 lux @ F2.0, AGC ON; 0 lux with IR		
Field of View (H)		12°		
Image Settings		Region of interest, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Defog, Sharpen, Noise Reduction		
Day/Night		Smart IR		
Compensation		Digital WDR / BLC / HLC		
Electronic Shutter Speed		/25 ~ 1/100000 sec.		
DNR		3D DNR		
Angle Adjustment		2an 0° - 360°, Tilt 0° - 80°, Rotation 0°- 360°		
Video Specifications				
Main Stream Resolution		3MP/6MP/5MP (1~20fps)		
Sub Stream Resolution		720P/D1/CIF (1~20fps)		
Third Stream		D1/CIF/480x240 (1~20fps)		
Compression		H.265, H.264		
Bitrate Control		/BR, CBR (64Kbps ~ 8Mbps)		
Multiple Streaming		3 streams		
Network Specifications				
Protocols	UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPs, QoS			
DDNS support	Speco DDNS (free of charge)			
Security	User ID & Password protection, IP/Mac address filtering, digest authentication			
User Access	Max. 3 simultaneous users (Actual number of users may vary depending on bandwidth)			
Interfaces				
Network		RJ45 jack		
Power		DC jack		
Microphone Input		3.5mm		
Card Slot		MicroSD, up to 128GB (not included)		
Alarm		No		
Reset		Yes		
Audio Specifications				
Audio Compression		G.711A / G.711U		

Chem Specifications				
Web Browser Support		Windows (Internet Explorer 8 and up)		
PC Application		SecureGuard® VMS, SecureGuard® CMS		
Mobile		SecureGuard [®] Client, Speco Blue (iPhone [®] and Android [™])		
Other Viewing Platforms		Apple TV®, Amazon Fire TV®		
System Specifica	tions			
PoE	Standard (IEEE 802.3af)			
Detection Events	Motion, Exception, Line Crossing, Region Intrusion and video blurring detection			
Alarm Triggers	Motion, Detection Events, SD card error			
Image Settings	Watermark, IP address filtering, video mask, password protection, Corridor mode			
Operating & Unit Specifications				
Power	PoE,	PoE, 12VDC (power supply not included)		
Power Consumption	<6.5	<6.5W		
Operating Temperatu	re -40	-40°F ~ 140°F (-40°C ~ 60°C)		
Operating Humidity	Less	Less than 95 % (non-condensing)		
Unit Dimensions	2.93	2.93" (W) x 2.93" (H) x 6.59" (D); (74.5mm x 74.5mm x 167.5mm)		
Unit Weight	0.93	0.93 lbs. (0.44kg)		
Certifications	FCC	FCC, RoHS		

*Products are in compliance with NDAA Section 889 Part B Guidelines

Client Specifications





ONVIF is a trademark of Onvif, Inc. Chrome and Firefox use Java which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 8/23/22



amazon appstore

800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • specotech.com

