

## **2MP HD-TVI IR Bullet Camera** with Junction Box

## VLB6

2.8-12mm varifocal lens, white housing









## **Features**

- Supports up to 2MP @ 30fps
- Full HD resolution over coax
- Supports HD-TVI, CVI, AHD, and 960H Analog
- IR Range: 165' (depending on scene reflection)
- 12VDC Operation (power supply not included)
- IP67 compliant, weather resistant
- Junction box included
- 5 year warranty
- NDAA Compliant\*





Camera Specifications	
Image Sensor	1/2.9" CMOS, 2MP
Minimum Illumination	0 lux (IR ON)
Image Size	1920 x 1080
Video Output	AHD/TVI/CVI/CVBS
Image System	PAL/NTSC
Electronic Shutter	Auto: 1/50s ~ 1/100000s (PAL); 1/60s ~ 1/100000s (NTSC)
IR Distance	32.8ft ~ 65.6ft
Frame Rate	30fps (60Hz); 25fps (50Hz)
Lens Mount	M12
S/N Ratio	≥ 52dB (AGC OFF)
=	

Functions		
Function Control	OSD (COC Control)	
Day & Night	Yes, Smart IR	
Digital WDR	Yes	
DNR	3D DNR	
AGC	Yes	
Auto White Balance	Yes	
Compensation	BLC	
Front Light Compensation	Yes	
Sharpness	Yes	
Mirror	Yes	
Image Setting	Yes	
Defect Correction	Auto	
Angle Adjustment	Pan (0° ~ 360°); Tilt (0° ~ 90°); Rotation (0° ~ 360°)	

Operating & Unit Specifications		
Power	12VDC (power supply not included)	
Power Consumption	IR OFF: < 1W; IR ON: < 3W	
Operating Temperature	-22°F ~ 122°F	
Operating Humidity	10% ~ 95% RH	
Unit Dimensions	8.57" (L) x 3.17" (W) x 3.17" (H)	
Unit Weight	1.23 lbs.	



\*Products are in compliance with NDAA Section 889 Part B Guidelines

## **Optional Accessories** PSW5 **TVIUTP** PMT1 CMT1 **TVIUTPPT** HD-TVI Balun 12VDC HD-TVI Balun over Pole Mount Corner Mount Power Supply over UTP UTP with Pigtail CLTX1 CLTX2 O5VLWMJ Ceiling Mount Ceiling Mount Wall Mount Ceiling Mount 8" Extension 4" Extension