

# Video Surveillance & Access Control Product Catalog

Intelligent Solutions for Today's Complex World Providing a Path Towards Increased RMR





**Digital Deterrent**®



**Vehicle Detection** 



**People Detection** 



**Facial Recognition** 



### **License Plate Recognition**



SecureGuard® Dashboard



### **Table of Contents**

IP Cameras | pages 3-29

B HD-TVI Cameras | pages 30-47

- SecureGuard<sup>®</sup> | pages 58-60
- Access Control | pages 62-68
- Recorders & ZIPKITS | page 48-56

### Using cutting edge technology to **DETECT**, **DETER**, and **ALERT**!



**FACIAL RECOGNITION:** With Facial Recognition an alarm can be triggered if a face is detected in a designated area. Alarms can also be triggered on specific faces, or recognized vs. unrecognized faces. Facial Recognition **Captures, Recognizes,** and **Stores** faces and you can search by face during playback. Send real time alerts when there is a friendly or unfriendly face in view. It's a self-contained system (camera & recorder) with no licenses or monthly fees.

**LINE CROSS COUNTING:** Line Crossing has the ability to maintain counts of people and/or vehicles. Alarms can also be triggered on excessive counts to control crowd density, which is an important feature. Line Crossing alerts you when someone enters an area they are not supposed to be in.

**PEOPLE DETECTION:** Virtually eliminates false motion alarms! Speco's analytic cameras and recorders with people detection can notify you of people in the scene and ignore everything else such as animals and precipitation. Alarms can be triggered if people enter view or a pre-defined region. Alarms can also be tailored to trigger upon entrance or exit of region.

**LICENSE PLATE RECOGNITION:** Taking Vehicle Detection to the next level with the addition of License Plate Recognition. **Capture** and **Search** by license plate or by date and time.

**VEHICLE DETECTION:** Trigger motion that matters! Speco's analytic cameras and recorders with Vehicle Detection will detect vehicles, motorcycles, and even bicycles. Alarms can be triggered if vehicles enter entire view or a pre-defined region. Alarm can also be tailored to trigger upon entrance or upon exit of a region.

**VIDEO BLURRING/SCENE CHANGE (TAMPERING DETECTION):** Be alerted when your surveillance camera is moved, loses focus or is physically altered.

Speco's Intelligent Solutions provide you with answers for today's problems.

### INDOOR/OUTDOOR | 8MP (4K) ADVANCED ANALYTIC IP CAMERAS



PoE Injecto

ver Supply

People/Vehicle Detection\*

3

Extension

### INDOOR/OUTDOOR | 8MP (4K) ADVANCED ANALYTIC IP CAMERAS



- Face/People/Vehicle/Scene **Change Detection\***

PSW5 PoE Injecto Power Supply

Pole Mount Ceili

Mount Wall Moun Extension

### INDOOR/OUTDOOR | 8MP (4K) VALUE LINE IP CAMERAS



PoE Injecto

ver Supply

Built-in microphone

### INDOOR/OUTDOOR | 8MP (4K) VALUE LINE IP CAMERAS



## INDOOR/OUTDOOR | 8MP (4K) IP CAMERAS

**O8FD1** 2.8mm fixed lens, dark gray housing

## 8MP (4K) Flexible Intensifier<sup>®</sup> IP Dome Camera with Advanced Analytics

- Captures up to 8MP @ 30fps
- Flexible Intensifier® Technology to fit any lighting application
- Captures color in extreme low light conditions and monochrome in absolute darkness.
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- IR range: up to 98' (depending on scene reflection)
- True WDR operation
- Micro SD card slot up to 256GB (card not included)

- Conformant with ONVIF Profile G/S/T
- Line crossing, region intrusion, and video blurring detection\*
- Face/Person/Vehicle Detection\*
- IP67 Weather Resistance
- IK10 Vandal Resistance
- Junction box included
- 5 year warranty
  NDAA Compliant\*\*
- \*with compatible Speco Blue Recorder
- \*\*Products are in compliance with NDAA Section 889 Part B Guidelines
- speco technologies®

#### **Optional Accessories**

IP 4K INTERSFERE IR AI H.265 TRUE WDR

POEINJ PSW5 CMTIG 25.5W 12VDC Corner PoE Injector Power Supply

ITIG PMTIG



PMT1G O5VLWMJG Pole Mount Wall Mount

(\*) DAY NIGHT

(5)

PoE

-

\*) DAY NIGHT 5

SVLWMJG FMT1 Wall Mount Ceiling Flush Mount

NDA

## **O8FB1**

2.8mm fixed lens, dark gray housing

# 8MP (4K) Flexible Intensifier<sup>®</sup> IP Bullet Camera with Advanced Analytics

- Captures up to 8MP @ 30fps
- Flexible Intensifier<sup>®</sup> Technology to fit any lighting application
- Captures color in extreme low light conditions and monochrome in absolute darkness.
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- IR range: up to 164' (depending on scene reflection)
- True WDR operation
- Micro SD card slot up to 256GB
- (card not included)

- Conformant with ONVIF Profile G/S/T
- Line crossing, region intrusion, and video blurring detection\*
- Face/Person/Vehicle Detection\*
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*\*
  - \*with compatible Speco Blue Recorder
  - \*\*Products are in compliance with NDAA Section 889 Part B Guidelines

POEINJ PSW5 25.5W 12VDC PoE Injector Power Supply

**Optional Accessories** 



Mount

**P**oE



### **O8FT1**

2.8mm fixed lens, dark gray housing

# 8MP (4K) Flexible Intensifier<sup>®</sup> IP Turret Camera with Advanced Analytics

- Captures up to 8MP @ 30fps
- Flexible Intensifier<sup>®</sup> Technology to fit any lighting application
- Captures color in extreme low light conditions and monochrome in absolute darkness.
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- IR range: up to 98' (depending on scene reflection)
- True WDR operation
- Micro SD card slot up to 256GB (card not included)

- Conformant with ONVIF Profile G/S/T
- Line crossing, region intrusion, and video blurring detection\*
- Face/Person/Vehicle Detection\*
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*\*
- \*with compatible Speco Blue Recorder
- \*\*Products are in compliance with NDAA Section 889 Part B Guidelines



#### Optional Accessories









# INDOOR/OUTDOOR | 8MP (4K) IP CAMERAS



### INDOOR/OUTDOOR | 8MP (4K)/6MP SPECIALTY IP CAMERAS

# **O8FBMS1**

3.3mm x 4 fixed lens, white housing

#### 8MP (4K) Panoramic Multi-sensor IP Camera with Flexible Intensifier<sup>®</sup> and Advanced Analytics

- Provides an 8MP stitched panoramic view
- Captures up to 8MP (2MP x 4) @ 30fps
- Flexible Intensifier<sup>®</sup> Technology to fit
- any lighting application
- Built-in standard PoE (IEEE 802.3af) Smart IR with range up to 65'
- (depending on scene reflection) • Micro SD card slot up to 128GB
- (card not included)
- Detects faces, people, and vehicles to reduce false motion alerts\*

4.0mm x 4 fixed lens, white housing

with Advanced Analytics

Quad-view Provides 4 separate views

8MP – Max resolution stream @ 30fps

8MP (2MP x 4) Quad-View IP Camera

Object/Intrusion detection

360° View from 4 cameras

with one channel

(card not included)

· Each camera can pan and tilt

Power via PoE+ (IEEE 802.3at)

or 24VDC (adapter included) • Smart IR with radius range up to 82'

(depending on scene reflection) Micro SD card slot up to 256GB

Conformant with ONVIF Profile G/S

**084S** 



- Junction box included
- 5 year warranty
- \*with Speco NRE Recorder

People/Vehicle Detection\*

IP66 Weather Resistance

IK10 Vandal Resistance

Ceiling mount included

\*with compatible Speco Blue Recorder

5 year warranty



**Optional Accessories** 





CI TX1 ng Mount 4" Extension



WMT1

IP67

SD SLOT PoE IK10 IP IP66 **Optional Accessories** LWMT1 Wall Mount LCMT1 Corner Mount LPMT1 Pole Mount SBPMJ CWMTPTZ Parapet Mount Conduit Wall Mount

## O6MDP3N

1.1mm fisheye lens, white housing

### 6MP Indoor/Outdoor 360° Panomorph IP Camera

- Captures up to a 360° view @ 30fps
- Provides a 360° view from ceiling or 180° view from wall
- De-warp views from the camera or recorder\*
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- Smart IR with range up to 100' (depending on scene reflection)
- True Day/Night operation (IR cut filter)
- Micro SD card slot up to 256GB (card not included)
- Conformant with ONVIF Profile G/S

- IP67 Weather Resistance
- Junction box included 5 year warranty
- NDAA Compliant\*\* \*with Speco NRE Recorder
  - \*\*Products are in compliance with NDAA Section 889 Part B Guidelines

#### **Optional Accessories**

IP

6MP

IR

POEINJ PSW5 12VD PoE Injector Power Supply

Pole Mount

PMT1



PoE

H.265

\*) DAY IIGH1

5



Wall Mount

WMT2



**O5LT1** 2.8mm fixed lens, white housing 5MP IP Advanced Analytics Turret Camera with White Light Intensifier® Captures up to 5MP @ 30fps · Line crossing, region intrusion, • Built-in standard PoE (IEEE 802.3af) and scene change detection\* Full Color capture in Day and Night Face/People/Vehicle Detection\* with white LED Built-in microphone • H.265/H.264/MJPEG compression and 1 channel audio line-in • IP67 Weather Resistance supported • White LED range: up to 98' Junction box included (depending on scene reflection) 5 year warranty True WDR operation NDAA Compliant\*\* Micro SD card slot up to 256GB \*with compatible Speco Blue Recorder -(card not included) \*\*Products are in compliance with POEINJ NDAA Section 889 Part B Guidelines Conformant with ONVIF Profile G/S/T 25.5W PoE Injector

ND (5) 0 c (UL) us **Optional Accessories** 

PMT1

Pole Moun

CLTX1

5MP

PSW5

IP

PoE

O5VLWMJ

Wall Mount

СІ Т2.

#### Ceiling Mount Power Supply 4" Extension **O5LB1** ₽ oE 5MP ΄ΑΙ È H.265 IP **IP67** 2.8mm fixed lens, white housing NDA (5) **5MP IP Advanced Analytics Bullet Camera** with White Light Intensifier® Captures up to 5MP @ 30fps · Line crossing, region intrusion, • Built-in standard PoE (IEEE 802.3af) and scene change detection\* (VL)us • Full Color capture in Day and Night • Face/People/Vehicle Detection\* with white LED • Built-in microphone • H.265/H.264/MJPEG compression and 1 channel audio line-in supported • IP67 Weather Resistance • White LED range: up to 98' Junction box included **Optional Accessories** (depending on scene reflection) 5 year warranty True WDR operation NDAA Compliant\*\* - Micro SD card slot up to 256GB \*with compatible Speco Blue Recorder (card not included) \*Products are in compliance with POEINJ PSW5 PMT1 CLTX1 O5VLWMJ CLT2 NDAA Section 889 Part B Guidelines Ceiling Mount 4" Extension Wall Mount Corner Mount Pole Mount Ceiling Mount 25.5W 12VDC Conformant with ONVIF Profile G/S/T PoE Injector Power Supply **O5D2** PoE \*) DAY NIGHT SLOT 2.8mm fixed lens, white housing **5MP IP Dome Camera with Advanced Analytics** Captures up to 5MP @ 30fps Face/People/Vehicle/Scene • Built-in standard PoE (IEEE 802.3af) Change Detection\*\* • True Day/Night operation (IR cut filter) Search analytic events with recorder\*\* H.265/H.264/MJPEG compression Built-in microphone c(VL)us supported IP67 Weather Resistance Adaptive IR LEDs reduce IR saturation IK10 Vandal Resistance • IR range: up to 100' (depending on Junction box included scene reflection) • 5 year warranty • True WDR operation NDAA Compliant\*\*\* **Optional Accessories** Micro SD card slot up to 256GB \*with Speco Cloud subscription service (card not included) \*\*with compatible Speco Blue Recorder 111 Conformant with ONVIF Profile G/S/T

· Line crossing, region intrusion, and video blurring detection\*\*

10

Cloud recording and playback support\*



CLT2J

FMT1 Flush Mount

POEINJ

\*\*\*Products are in compliance with

NDAA Section 889 Part B Guidelines

25.5W PoE Injector

PSW5

12VC Power Supply

CMT1

PMT1 Pole Mount

CLTX1 Ceiling Mount 4" Extension Mount

O5VLWMJ Wall Mount



INDOOR	OUTDOOR   SMP IP CAMERAS	
<b>05B2</b> 2.8mm fixed lens, white housing		
5MP IP Bullet Camera with Adv	inced Analytics	T
<ul> <li>Captures up to 5MP @ 30fps</li> <li>Built-in standard PoE (IEEE 802.3af)</li> <li>True Day/Night operation (IR cut filter)</li> <li>H.265/H.264/MJPEG compression supported</li> <li>Adaptive IR LEDs reduce IR saturation</li> <li>IR range: up to 100' (depending on scene reflection)</li> <li>True WDR operation</li> <li>Micro SD card slot up to 256GB (card not included)</li> <li>Conformant with ONVIF Profile G/S/T</li> <li>Cloud recording and playback support*</li> </ul>	<ul> <li>Face/People/Vehicle/Scene Change Detection**</li> <li>Search analytic events with recorder**</li> <li>IP67 Weather Resistance</li> <li>Junction box included</li> <li>S year warranty</li> <li>NDAA Compliant***</li> <li>*With Speco Cloud subscription service</li> <li>*With Speco Cloud subscription service</li> <li>*With Speco Cloud subscription service</li> <li>*Products are in compliance with NDAA Section 889 Part B Guidelines</li> </ul>	S
<ul> <li>Line crossing, region intrusion, and video blurring detection**</li> </ul>	POEINJ PSW5 CMT1 PMT1 CLTX1 O5VLWMJ CLT2J 25.5W 12VDC Corner Pole Mount Ceiling Mount Wall Mount Ceiling PoE Injector Power Supply Mount 4" Extension Mount	
<b>05T2</b> 2.8mm fixed lens, white housing	IP 5MP IR (AI) H.265 TRUE POE (CARATE SIGNATION OF SLOT (P67	
5MP IP Turret Camera with Adv	anced Analytics	T
<ul> <li>Captures up to 5MP @ 30fps</li> <li>Built-in standard PoE (IEEE 802.3af)</li> <li>True Day/Night operation (IR cut filter)</li> <li>H.265/H.264/MJPEG compression supported</li> <li>Adaptive IR LEDs reduce IR saturation</li> <li>IR range: up to 100' (depending on scene reflection)</li> <li>True WDR operation</li> <li>Micro SD card slot up to 256GB</li> </ul>	<ul> <li>Face/People/Vehicle/Scene Change Detection**</li> <li>Search analytic events with recorder**</li> <li>IP67 Weather Resistance</li> <li>Junction box included</li> <li>S year warranty</li> <li>NDAA Compliant***</li> <li>*With Speco Cloud subscription service</li> </ul>	S
<ul> <li>(card not included)</li> <li>Conformant with ONVIF Profile G/S/T</li> <li>Cloud recording and playback support*</li> <li>Line crossing, region intrusion, and video blurring detection**</li> </ul>	**with compatible Speco Blue Recorder **Products are in compliance with NDAA Section 889 Part B Guidelines POEINJ 25.5W PoE Injector Power Supply Power Supply Pow	
O5P2		
2.8mm fixed lens, white housing		
5MP IP Mini-Dome Camera with	Advanced Analytics	Т
• Captures up to 5MP @ 30fps	• Face/People/Vehicle/Scene	-
<ul> <li>Built-in standard PoE (IEEE 802.3af)</li> <li>True Day/Night operation (IR cut filter)</li> </ul>	Change Detection**  • Search analytic events with recorder**	
H.265/H.264/MJPEG compression supported     Adaptive IR LEDs reduce IR saturation	IP67 Weather Resistance     Wall mount included	S
<ul> <li>IR range: up to 65' (depending on scene reflection)</li> </ul>	• 5 year warranty	
True WDR operation	NDAA Compliant****     'with Speco Cloud subscription service	
<ul> <li>Micro SD card slot up to 256GB</li> </ul>	**with compatible Speco Blue Recorder	

with compatible Speco Blue Recorder

\*\*\*Products are in compliance with NDAA Section 889 Part B Guidelines

- Micro SD card slot up to 256GB
   (card not included)
- Conformant with ONVIF Profile G/S/T
- Cloud recording and playback support\*
- Line crossing, region intrusion, and video blurring detection\*\*

#### **Optional Accessories**









IP

4MP

**O4iB2** 

2.8mm fixed lens, dark gray housing

#### 4MP Intensifier<sup>®</sup> IP Bullet Camera with Advanced Analytics

- Captures up to 4MP @ 30fps
- Intensifier<sup>®</sup> Technology captures in full color in extreme low-light scenes
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- True WDR operation
- Micro SD card slot up to 256GB
- (card not included)
- Conformant with ONVIF Profile G/S/T
- Line crossing, region intrusion,
- and video blurring detection\*
- Face/Person/Vehicle Detection\*

- IP67 Weather Resistance
- Junction box included
- 5 vear warrantv
- NDAA Compliant\*\* \*with compatible Speco Blue Recorder

• IP67 Weather Resistance

Built-in microphone

5 year warranty

NDAA Compliant\*\*

Junction box included

\*with compatible Speco Blue Recorder

NDAA Section 889 Part B Guidelines

\*\*Products are in compliance with

\*\*Products are in compliance with NDAA Section 889 Part B Guidelines



**Optional Accessories** 

PSW5

Power Supply

H.265

- -----POFINJ

25.5W PoE Injector

AI



2.8mm fixed lens, dark gray housing

#### 4MP Intensifier<sup>®</sup> IP Turret Camera with Advanced Analytics

- Captures up to 4MP @ 30fps
- Intensifier<sup>®</sup> Technology captures in full color in extreme low-light scenes
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- True WDR operation
- Micro SD card slot up to 256GB
- (card not included)
- Conformant with ONVIF Profile G/S/T
- Line crossing, region intrusion, and video blurring detection\*
- Face/Person/Vehicle Detection\*



#### **Optional Accessories**

PoE

POEINJ 5.5W PoE Injector Pov





### O4iD2M

#### 2.8-12mm motorized lens, dark gray housing

#### 4MP Intensifier<sup>®</sup> IP Dome Camera with Advanced Analytics

- Captures up to 4MP @ 30fps
- Intensifier<sup>®</sup> Technology captures in full color in extreme low-light scenes
- Built-in standard PoE (IEEE 802.3af)
- H.265/H.264/MJPEG compression supported
- True WDR operation
- Micro SD card slot up to 256GB (card not included)
- Conformant with ONVIF Profile G/S/T
- Line crossing, region intrusion, and video blurring detection\*
- Face/Person/Vehicle Detection\*

- IP67 Weather Resistance
- Built-in microphone
- IK10 Vandal Resistance
- Junction box included
- 5 year warranty NDAA Compliant\*\*
- \*with compatible Speco Blue Recorder
- \*\*Products are in compliance with NDAA Section 889 Part B Guidelines



CMT1G

#### **Optional Accessories**



PoE Iniecto



PMT1G Pole Mount

WMT1G FMT3 Wall Mount Flush Mount

14









PoE

PoE

(5)



NDA

O5VLWMJG

Wall Mount



- True Day/Night operation (IR cut filter)
- H.265/H.264/MJPEG compression supported
- IR range: up to 98' (depending on scene reflection)
- True WDR operation
- Micro SD card slot up to 256GB (card not included)

- Built-in microphone
- IK10 Vandal Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*\*
- \*with compatible Speco Blue Recorder \*\*Products are in compliance with NDAA Section 889 Part B Guidelines

**Optional Accessories** 

POEINJ PoE Iniecto







Wall Mount



Flush Mount



- IR range: up to 164' (depending on scene reflection)
- True WDR operation
- Micro SD card slot up to 256GB
   (card not included)
- 5 year warranty
- NDAA Compliant\*\*
- \*with compatible Speco Blue Recorder
- \*\*Products are in compliance with NDAA Section 889 Part B Guidelines

POEINJ PSW5 25.5W 12VDC PoE Injector Power Supply

**Optional Accessories** 

- -

CMT1G PMT1G Corner Pole Mount

G WMT1G

G FMT3 unt Flush Mount





- Conformant with ONVIF Profile G/S/T
- Cloud recording and playback support\*
- Line crossing, region intrusion,
- and video blurring detection\*\*
- 18



PSW5

wer Supply



Ceiling Mount 4" Extension

Corne Mount

Power Supply

PoE Injector

Pole M

- Face Detection and Capture\*
- People/Vehicle Detection\*
- Search analytic events with recorder\*\*



Ceiling Mount









### **O4P4X2**

2.8-12mm 4x optical zoom lens, white housing

### **4MP 4X PTZ Advanced Analytics IP Camera** with Audio and Visual Digital Deterrent

- Captures up to 4MP @ 30fps
- Up to 4x Optical Zoom
- Power with built in PoE+ support (IEEE 802.3at) or 12VDC power adapter (not included)
- True Day/Night operation (IR cut filter)
- H.265/H.264 compression supported
- IR range: up to 164' (depending on scene reflection)
- White LED range up to 98ft
- True WDR operation
- Micro SD card slot up to 256GB (card not included)
- Conformant with ONVIF Profile G/S/T
- · Line crossing, object detection, region intrusion and video blurring detection\*

 People/Vehicle Detection with Smart Tracking\*

IP

- Face Detection and Recognition\*
- Search analytic events with recorder\*
- Two-way audio built-in
- IP66 Weather Resistance
- Ceiling bracket included
- Built-in speaker and microphone
- Audio line in/out
- 1 year warranty
- NDAA Compliant\*\*
- \*with compatible Speco Blue Recorder

\*\*Products are in compliance with NDAA Section 889 Part B Guidelines



\*) DAY NIGHT

**Optional Accessories** 

POEINJ

PoE Injecto

Wall Mount

CLTX1

Ceiling Mount



## INDOOR/OUTDOOR | 4MP AND 2MP IP CAMERAS



- (card not included)
- Conformant with ONVIF Profile G/S/T
- · Line crossing, region intrusion,
- and video blurring detection\*

- -----POFIN I

22.5W

PoE Injector

PSW5 12VDC Mount Power Supply

PMT1 Pole Mount

CLTX1 **Ceiling Mount** 4" Extension

O5VLWMJ Wall Mount eiling



POEINJ

25.5W PoE Injecto PMT1

Pole Mount

CLTX1

Ceiling Mount 4" Extension WMT1 Wall Mount

(card not included)



TMLDSK

TMLPMT

Pole Stand

TMLFLR

Floor Stand Desk Stand

N8NRT

nent

Smart Manage Terminal

12VDC power supply included (PSW5)

\*This device is not FDA approved and is not intended for use in the diagnosis or treatment of any disease or other conditions, nor should it be solely or primarily relied upon to diagnose or exclude a diagnosis of COVID-19 or any other disease, or in the cure, mitigation, treatment, or prevention of any disease.

# 2MP IP CAMERAS | IP ACCESSORIES



- Port 1 supports up to 40W and all ports support 802.3at/802.3af.
- Ports 3 and 4 can be extended up to 800' (250M) @10mbps
- VLAN Mode: When the VLAN mode is selected, each PoE port is isolated and independently connects with cameras, computers or other switches, while the uplink port connects with a router.
- The VLAN function helps avoid broadcast storms and ARP spoofing.

### P4S5G

#### **5 Port Gigabit Network Switch**

- (4 Ports PoE, 1 Port Uplink)
- Gigabit performance on all ports
   (uplink and downlink)
- PoE watchdog mode: PoE will continuously monitor for lost device connections and reset the wport when detected
- Port 1 supports 802.3bt 60W and all ports support
  802.3at/802.3af
- All ports can be extended up to 800' (250M) @ 10MBPs
   using high quality CAT6 cable





### **10-Port Gigabit Network Switch**

\*Products are in compliance with NDAA Section 889 Part B Guidelines

lost device connections and reset the port when detected

• Port 1 supports 802.3bt 60W and all ports

All ports can be extended up to 800' (250M)

**9 Port Gigabit Network Switch** 

 CCTV mode isolates each port from one another for added security and performance

(8 Ports PoE, 1 Port Uplink)
Gigabit performance on all ports (uplink and downlink)

Includes built-in surge immunity

2 year warranty

NDAA Compliant\*

@ 10MBPs using high quality CAT6 cable

support 802.3at/802.3af

**P8S9G** 

(8 Ports PoE, 2 Port Uplink)

**P8S10G** 

- Gigabit performance on all ports (uplink and downlink)
- CCTV mode isolates each port from one another for added security and performance
- Includes built-in surge immunity
- 2 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



NDAA

# **IP | ACCESSORIES**

## P24S26G



#### 26 Port Gigabit Network Switch

(24 Ports PoE, 2xSFP Uplink)

- VLAN mode to isolate ports
- Extend mode for port 17-24 to extend signal up to 820'
- Support for IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z
- Compatible with IEEE802.3at (30W) and IEEE802.3af (15.4w)
- Supports port lightning protection Surge: common mode
- 2KV, differential mode 1KV; static ESD: air 15KV, contact 8KV • 2 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# P32S36GM



----

#### **36 Port Gigabit Managed Network Switch**

(34 Ports PoE, 4xSFP Uplink)

- Layer-2 managed switch (supporting PoE function)
- 32 x 10/100/1000Mbps adaptive RJ45 ports and 4 x SFP Gigabit optical ports. Two SFP to RJ45 adapters included.
- Each RJ45 port supports MDI/MDIX auto flip and wire-speed forwarding functions.
- Ports 1-32 support Power over Ethernet and follows the IEEE802.3af/at standard.
  Can automatically detect and identify a power-receiving device
- and supply power to it through a network cable.
- Uses store-and-forward mode, combined with QoS technology, to ensure that the bandwidth is effectively allocated to each port.
- Provides stable and reliable power and data transmission for high-power AP, network cameras, PTZ network dome cameras, PoE lighting and other security monitoring equipment.
- 2 year warranty
- NDAA Compliant\*
- \*Products are in compliance with NDAA Section 889 Part B Guidelines

# POESPL

### 802.3at/af PoE Splitter

- Power non-PoE IP cameras via a PoE signal by splitting the signal into Ethernet and power
- POESPL can handle up to 20W 802.3at PoE power
- Ethernet speed up to 10/100MBPS
- 2 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# POEINJ

### 802.3at/af PoE Injector

- Used in conjunction with Ethernet switch to power
   PoE cameras
- Meets IEEE 802.3af/at Ethernet standard
- Ethernet speed up to 10/100MBPS
- 2 year warranty

28

NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# POECOAX

#### PoE Over Coax Kit

- Send data and power over RG59 coaxial cable up to 1600'
- Extend the normal 330' range of PoE to up to 1300' via Cat5 cable.
- Includes a transmitter (IPC and receiver (SV)
- 2 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# **IPPOERPT**

### **PoE Repeater**

- Extends both power and data 330' per repeater
- Purchase a second repeater for total run of 1000'
- No external power required
- Compatible with the 802.3af standard
- Supports gigabit network speeds
- Built-in LED status indicator
- Plug and play for easy installation
- 2 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# IPRPT

### **Gigabit Ethernet Repeater**

- •Ethernet signal extension up to 393' (120M) over CAT5e cable
- •Bandwidth up to 1000Mbps
- •Chainable with multiple IPRPT for longer distances
- (Up to 3, with a loss of bandwidth) •Built-in 8kV (Contact) 15kV (Air) surg<u>e protection</u>

# SPPOE2

### **PoE Surge Protector**

- Protects PoE equipment from high voltage surges
- Offers protection to power and signal line
- 10/100 Base-T compatible
- Supports Midspan and Endspan PoE units
- IEEE 802.3af, IEEE 802.3a compatible
- Complies with IEC61000-4-5 2nd edition
- 2 year warranty NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# SPPOEO

### **PoE Surge Protector**

- Supports bandwidth up to 1000 Mbps
- Supports IEEE 802.3 af, 802.3 at, 802.3bt PoE standard
- Supports Mid-Span and End Span PoE
- Meets IP66 Waterproof rating
- Response time less than 1ns





NDAA



NDA









NDAA



NDAA

### **IP | AUDIO ACCESSORIES & AUDIO DETERRENT CAMERAS**

# CAMMIC

#### **Pre-Amplified Line Level Mic**

- Add-on mini-microphone for all systems
- High sensitivity microphone with 1.5 ft. power/audio cable
- · Easy to install and ideal for all security surveillance voice recording applications
- Line level output
- 2 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# CAMMIC3.5

#### 3.5mm Line Level Mic

- 3.5mm plug for a direct connection to a camera's 3.5mm audio input
- Supports sensitivity at -65dB.
- Includes an 18" DC jack/audio cable.
- 2 year warranty
- NDAA Compliant\*
- \*Products are in compliance with NDAA Section 889 Part B Guidelines

# CAMMICV

#### **Mini Line Level Mic with Volume Adjustment**

- · Perfect companion product for any camera needing an audio input source
- Open board design makes the microphone compact and potentially covert
- High sensitivity microphone with 19.7" (500mm) power/audio cable
- 3.5mm connection for easy hookup to camera
- 12VDC power operation (PSW5 power supply not included)
- It is recommended to install this microphone over 15' away from the speaker to minimize the impact of potential feedback.
- 2 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

### CAMMIC2

#### Surface Mount Line Level Mic

- Can be wall or ceiling mounted
- Designed for indoor spaces
- Ideal pickup range of 10 to 120 square feet
- · Gain control to increase or reduce pick-up sensitivity
- 2 vear warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# CAMMICW

### **Pre-Amplified Line Level Mic**

- Constructed out of Aluminum alloy for outdoor use
- Pickup indoors in rooms up to 120 square feet
- Integrated pre-amplification processing circuit
- Built-in high-speed voice processing
- 2 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

NDAA COMPLIANT DD1

2.8-12mm motorized lens, white housing

Indoor Digital Deterrent<sup>®</sup> Alert Box with Built-in Strobe, **4MP IP Bullet Camera with Advanced Analytics** and Selectable Audio Voice Warning

IP

4MP

IR

- Use loud sounds and bright lights
- to deter crime and unwanted visitors
- One cable connection to your Speco Blue Recorder\*
- Captures up to 4MP @ 30fps
- IR range: up to 230' (depending on scene reflection)
- Face Detection and Capture\*
- People/Vehicle Detection\*
- 3 built-in selectable deterrent messages
- Up to 105dB
- 2 year warranty
- \*requires compatible Speco Blue Recorder





### DD2

2.8-12mm motorized lens, white housing

IR IP 4MP

#### Indoor/Outdoor Digital Deterrent<sup>®</sup> Alert Box with Built-in Flood Light, 4MP IP Bullet **Camera with Advanced Analytics and Siren**

- Use loud sounds and bright lights to deter crime and unwanted visitors
- One cable connection to your Speco Blue Recorder\*
- Captures up to 4MP @ 30fps
- IR range: up to 230' (depending on scene reflection)
- Face Detection and Capture\*
- People/Vehicle Detection\*
- Warbling Siren
- Volume adjustment up to 120dB
- Weather Resistance
- 2 year warranty
- \*requires compatible Speco Blue Recorder





#### DDAK4



**Digital Deterrent®** 

ASPC20, PSDC24 &

Connector Adapter

Kit for DVRs w/

#### 2WAK2



Two-way Audio

Kit for DVR's with

**PVL15A Amplifier** 

2WAK3

Two-way Audio Kit for DVR's with PBM30 Amplifier

29



NDAA

NDAA COMPLIANT



03

NDAA



## INDOOR/OUTDOOR | 8MP (4K) HD-TVI CAMERAS

### H8D8M

2.8-12mm motorized lens, white housing

### 8MP (4K) HD-TVI IR Motorized Dome Camera

- Captures up to 8MP @ 15fps
- 30 built-in IR LEDs
- Signal distance up to 1600ft.
- True Day/Night operation (IR cut filter)
- IR range: up to 98' (depending on scene reflection)
- Full OSD operation through UTC (up the coax)
- 12VDC operation (power supply not included)
- IP67 Weather Resistance
- IK10 Vandal Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



2.8-12mm motorized lens, white housing

#### 8MP (4K) HD-TVI IR Motorized Bullet Came

- Captures up to 8MP @ 15fps
- 35 built-in IR LEDs
- Signal distance up to 1600ft.
- True Day/Night operation (IR cut filter)
- IR range: up to 65' (depending on scene reflection)
- Digital WDR
- Full OSD operation through UTC (up the coax)
- 12VDC operation (power supply not included)
- IP66 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

### **H8T8M**

2.8-12mm motorized lens, white housing

#### 8MP (4K) HD-TVI IR Motorized Turret Camera

- Captures up to 8MP @ 15fps
- True Day/Night operation (IR cut filter)
- IR range: up to 164' (depending on scene reflection)
- Digital WDR
- Full OSD operation through UTC (up the coax)
- 12VDC operation (power supply not included)
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

	Power supply	10unt -	+ Extension	Mot	int.
			HD	4K IR	
ra		æ		5	COMPLIANT
		apeco fecterolation			
o	ptional Accessories				_

speco technologie

PMT1

**Optional Accessories** 

AY NIGHT

PSW5

TVIUTP HD Video HD Video ransceiver wit Pigtail (Balun)

Cornei Pole Mount

Ceiling Moun Wall № 4" Extension

\*) DAY NIGHT

WMT1

Wall Moun

CLT3

EMT3

Flush Mou

Moun

#### **Optional Accessories**







PMT1 CLTX

Ceiling Mount 4" Extension Wall Mou

30

TVIUTF

HD

Pigtail (Balun)

### INDOOR/OUTDOOR | 5MP HD-TVI CAMERAS

### H5B1M

2.7-13.5mm motorized lens, white housing

#### **5MP HD-TVI Motorized Bullet Camera**

- Captures up to 5MP TVI, 2MP AHD/CVI and CVBS by dip switch
- IR range: up to 65' (depending on scene reflection)
- True WDR operation
- Full OSD operation through UTC (up the coax)
- 12VDC operation (power supply not included)
- IP66 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



HD TVI

5MP





IR



## HTD5TG

2.8mm fixed lens, dark gray housing

#### **5MP HD-TVI Vandal Dome Camera**

- Captures up to 5MP @ 20fps
- Built-in high powered IR LEDs
- True Day/Night operation (IR cut filter)
- IR range: up to 65' (depending on scene reflection)
- Digital WDR operation
- Chameleon Cover ™ : snaps on and can be painted to match any décor!
- 12VDC operation (power supply not included)
- IP66 Weather Resistance
- Junction box included
- 5 year warranty
- TAA Compliant
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

## HTB5TG

2.8mm fixed lens, dark gray housing

#### **5MP HD-TVI Bullet Camera**

- Captures up to 5MP @ 20fps
- Built-in high powered IR LEDs
- True Day/Night operation (IR cut filter)
- IR range: up to 65' (depending on scene reflection)
- Digital WDR operation
- 12VDC operation (power supply not included)
- IP66 Weather Resistance
- Junction box included
- 5 year warranty
- TAA Compliant
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



#### **Optional Accessories**

PSW5 12VDC Power Supply

TVIUTPPT HD Video Transceiver with Pigtail (Balun)

TVIUTP

HD Video Transceiver







#### **Optional Accessories**





PSW5 I 12VDC I Power Supply Trar





## INDOOR/OUTDOOR | 5MP HD-TVI CAMERAS

### **V5D2**

2.8mm fixed lens, white housing

#### 5MP HD-TVI IR Dome Camera

- Captures up to 5MP @ 20fps
- True Day/Night operation (IR cut filter)
- IR range: up to 65' (depending on scene reflection)
- Digital WDR
- 12VDC operation (power supply not included)
- IP67 Weather Resistance
- IK10 Vandal Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



**O5VLWMJ** 

5MP

CLT2.

IR

# V5B2

2.8mm fixed lens, white housing

#### **5MP HD-TVI IR Bullet Camera**

- Captures up to 5MP @ 20fps
- True Day/Night operation (IR cut filter)
- IR range: up to 98' (depending on scene reflection)
- Digital WDR
- 12VDC operation (power supply not included)
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*
- \*Products are in compliance with NDAA Section 889 Part B Guidelines



Ceiling Mount 4" Extension

> HD TVI

#### **Optional Accessories**

PSW5 12VDC Power Supply

PSW5

Power Supply

CMT

PMT1

CMT1 Corner Pol Mount

PMT1 CLTX1 Pole Mount Ceiling Mount 4" Extension

5MP

IR



Mount

IP67

FMT1 Flush Mount

**IP67** 

## **V5T2**

2.8mm fixed lens, white housing

#### 5MP HD-TVI IR Turret Camera

- Captures up to 5MP @ 20fps
- IR range: up to 98' (depending on scene reflection)
- Digital WDR
- 12VDC operation (power supply not included)
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



#### **Optional Accessories**



I PMT1

CLTX1 WMT1 Ceiling Mount 4" Extension CLT3 Ceiling

### INDOOR/OUTDOOR | 5MP HD-TVI CAMERAS

### V5D2M

2.8-12mm motorized lens, white housing

#### 5MP HD-TVI IR Motorized Dome Camera

- Captures up to 5MP @ 20fps
- Up to 4x optical zoom
- True Day/Night operation (IR cut filter)
- IR range: up to 98' (depending on scene reflection)
- Digital WDR
- 12VDC operation (power supply not included)
- IP67 Weather Resistance
- IK10 Vandal Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



PMT1

PSW5

12VDC Power Supply

HD TVI

5MP



IR

AY NIGHT

(5

ZOOM FOCUS

(\*) DAY NIGHT

IR



**IP67** 

NDA

### **V5B2M**

2.8-12mm motorized lens, white housing

#### **5MP HD-TVI IR Motorized Bullet Camera**

- Captures up to 5MP @ 20fps
- Up to 4x optical zoom
- True Day/Night operation (IR cut filter)
- IR range: up to 165' (depending on scene reflection)
- Digital WDR
- 12VDC operation (power supply not included)
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

## **V5T2M**

2.8-12mm motorized lens, white housing

#### **5MP HD-TVI Motorized Turret Camera**

- Captures up to 5MP @ 20fps
- Up to 4x optical zoom
- True Day/Night operation (IR cut filter)
- IR range: up to 165' (depending on scene reflection)
- Digital WDR
- 12VDC operation (power supply not included)
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*
- \*Products are in compliance with NDAA Section 889 Part B Guidelines



HD TVI

5MP













#### \*) DAY NIGHT HD TVI IR 5MP



#### **Optional Accessories**



Power Supply







ng Mount



33

Mount

### H4FD1M

2.7-12mm motorized lens, dark gray housing

### 4MP Flexible Intensifier® HD-TVI Dome Camera

- Captures up to 4MP @ 30fps
- Flexible Intensifier<sup>®</sup> Technology to fit any lighting application
- Adaptive IR LEDs
- True Day/Night operation (IR cut filter)
- IR range: up to 98' (depending on scene reflection)
- True WDR operation
- Full OSD operation through onboard and UTC (up the coax)
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- TAA Compliant
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



**Optional Accessories** 

PSW5 12VDC Power Supply P

TVIUTPPT



PSW5 PSW4 2VDC 24VAC er Supply Power Supply

(AUC)

4MP

TVIUTPPT TVIUTP HD Video HD Video Transceiver with Pigtail (Balun)

IR

0

**Optional Accessories** 

÷) DAY NIGHT

6

INTWMT PNDM1 Wall Mount Pendant Mount

# H4FB1M

2.7-12mm motorized lens, dark gray housing

#### 4MP Flexible Intensifier® HD-TVI Bullet Camera

- Captures up to 4MP @ 30fps
- Flexible Intensifier® Technology to fit any lighting application
- Adaptive IR LEDs
- True Day/Night operation (IR cut filter)
- IR range: up to 98' (depending on scene reflection)
- True WDR operation
- Full OSD operation through onboard and UTC (up the coax)
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- TAA Compliant
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

## VLT4DG

2.8mm fixed lens, dark gray housing

#### **4MP HD-TVI Vandal Dome Camera**

- Captures up to 4MP @ 15fps
- Built-in high powered IR LEDs
- True Day/Night operation (IR cut filter)
- IR range: up to 66' (depending on scene reflection)
- Digital WDR operation
- Chameleon Cover ™: snaps on and can be painted to match any décor!
- 12VDC operation (power supply not included)
- IP66 Weather Resistance
- Junction box included
- 5 year warranty
- TAA Compliant

NDAA Compliant\*

34

\*Products are in compliance with NDAA Section 889 Part B Guidelines





#### **Optional Accessories**







## INDOOR/OUTDOOR | 4MP/2MP HD-TVI CAMERAS

## VLT4BG

2.8mm fixed lens, dark gray housing

#### 4MP HD-TVI Bullet Camera

- Captures up to 4MP @ 15fps
- Built-in high powered IR LEDs
- True Day/Night operation (IR cut filter)
- IR range: up to 66' (depending on scene reflection)
- Digital WDR operation
- 12VDC operation (power supply not included)
- IP66 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines







IR

## HT471TG/HT471TW

2.9mm fixed lens, dark gray/white housing

#### **4MP HD-TVI Mini-Turret Color Cameras**

- Captures up to 4MP @ 15fps
- 12 built-in IR LEDs
- Signal distance up to 1600ft.
- Cast aluminum construction
- True Day/Night operation (IR cut filter)
- IR range: up to 35' (depending on scene reflection)
- Full OSD operation through onboard and UTC (up the coax)
- 12VDC operation (power supply not included)
- Vandal Resistant
- IP66 Weather Resistance
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# H2LT1

2.8mm fixed lens, white housing

#### 2MP HD-TVI Turret Camera with White Light Intensifier®

- Captures up to Full HD @ 30fps
- Full Color capture in Day and Night with white LED
- White LED range: up to 98' (depending on scene reflection)
- Digital WDR operation
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines





HD TVI

#### **Optional Accessories**

PSW5

Τνιυτρρτ HD Video



HD Video Transceive

Transceiver with Pigtail (Balun)





#### **Optional Accessories**











12VD Power Supply

Ceiling Moa. 4" Extension

35



IR

4MP



4MP

## INDOOR/OUTDOOR | 2MP HD-TVI CAMERAS

### H2LB1 2.8mm fixed lens, white housing

### 2MP HD-TVI Bullet Camera with White Light Intensifier®

- Captures up to Full HD @ 30fps
- Full Color capture in Day and Night with white LED
- White LED range: up to 98' (depending on scene reflection)
- Digital WDR operation
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



PMT1

PSWS Power Supply

CLTX1 ling Moun Extension O5VLWMJ

## H2AT2

2.8mm fixed lens, white housing

#### 2MP HD-TVI Turret Camera with White Light Intensifier® and Built-in Microphone

- Captures up to Full HD @ 30fps
- Full Color capture in Day and Night with white LED
- White LED range: up to 98' (depending on scene reflection)
- Audio over coax capability works with
- Speco HRN series (6ch and 24ch) and HRLN Series
- Digital WDR operation
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\* \*Products are in compliance with NDAA Section 889 Part B Guidelines



PSW5 Power Supply

PMT1 CMT

CLTX1 Ce Extension

HD TVI

2MP



### **H2AB2**

2.8mm fixed lens, white housing

#### 2MP HD-TVI Bullet Camera with White Light Intensifier® and Built-in Microphone

- Captures up to Full HD @ 30fps
- Full Color capture in Day and Night with white LED
- White LED range: up to 98' (depending on scene reflection)
- · Audio over coax capability works with
- Speco HRN series (6ch and 24ch) and HRLN Series
- Digital WDR operation
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



#### **Optional Accessories**



Power Supply



Mount




# HiD8

3.6mm fixed lens, dark gray housing

### 2MP HD-TVI Ultra Intensifier<sup>®</sup> Dome Camera

- Captures up to Full HD @ 30fps
- Next generation of Intensifier<sup>®</sup> technology provides an even more vivid color image in low light situations
- Preset image modes offer convenient settings for different environments
- True Day/Night operation (IR cut filter)
- True WDR operation
- Chameleon Cover <sup>™</sup> : snaps on and can be painted to match any décor!
- IP66 Weather Resistance
- IK10 Vandal Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



**Optional Accessories** 

PSW5 Power Supply

HD TVI

2MP





HD V Transceiver wit Pigtail (Balun)

**Optional Accessories** 

PSW5

**Power Supply** 

c**UL**us

辮

(5)

Wall Mount Transceive

**IP68** 

# HiB68

3.6mm fixed lens, dark gray housing

### 2MP HD-TVI Ultra Intensifier<sup>®</sup> Bullet Camera

- Captures up to Full HD @ 30fps
- Next generation of Intensifier<sup>®</sup> technology provides an even more vivid color image in low light situations
- · Preset image modes offer convenient settings for different environments
- Built-in temperature and humidity sensor control automatic heater operation
- True Day/Night operation (IR cut filter)
- True WDR operation
- IP68 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



2.8-12mm auto iris varifocal lens, dark gray housing

### 2MP HD-TVI Intensifier<sup>®</sup> Dome Camera

- Captures up to Full HD @ 30fps
- Color in low light without IR LEDs
- Additional 960H analog output
- Built-in heater
- True Day/Night operation (IR cut filter)
- True WDR operation
- Chameleon Cover <sup>™</sup> : snaps on and can be painted to match any décor!
- Full OSD operation through onboard
- and UTC (up the coax)
- 12VDC & 24VAC dual voltage operation (power supply not included)

- Vandal/Tamper Resistant
- IP67 Weather Resistance
- UL listed
- Junction box included
- 5 year warranty
- TAA Compliant
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



### **Optional Accessories**

2MP







PNDM Pendan Mount

- Power Supply
  - Transceiver with Transceive Pigtail (Balun)
- 37



TVIUTP Transceiver

# **HT7250TM**

5-50mm motorized lens, dark gray housing

### 2MP HD-TVI Intensifier<sup>®</sup> Dome Camera

- Captures up to Full HD @ 30fps
- Signal distance up to 1600ft.
- Superior low-light performance
- Amplify existing light with no distance limitation
- Presets: Indoor, Outdoor, Low Light, Lobby, Elevator
- Additional 960H analog output
- Built-in heater and anti-fog glass reduces condensation
- True Day/Night operation (IR cut filter)
- True WDR operation
- Chameleon Cover <sup>™</sup> : snaps on and can be painted to match any décor!
- Full OSD operation through onboard and UTC (up the coax)

- · 3-axis for wall and ceiling mounting
- 12VDC & 24VAC dual voltage operation (power supply not included)

12VDC & 24VAC dual voltage operation

(power supply not included)

Vandal/Tamper Resistant

• IP67 Weather Resistance

Products are in compliance with NDAA Section 889 Part B Guidelines

5 year warranty

TAA Compliant

NDAA Compliant\*

- Vandal/Tamper Resistant
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- TAA Compliant
- NDAA Compliant \*Products are in compliance with NDAA Section 889 Part B Guidelines

**Optional Accessories** 

Ó ★ ) DAY NIGHT

:(UL)u



TAA

# HTINT70TA/HTINT702TA

2.7-12mm auto iris varifocal lens/5-50mm auto iris varifocal lens, dark gray housing

### 2MP HD-TVI Intensifier<sup>®</sup> Bullet Cameras

- Captures up to Full HD @ 30fps
- Color in low light without IR LEDs
- Additional 960H analog output
- Built-in heater
- True Day/Night operation (IR cut filter)
- True WDR operation
- Full OSD operation through onboard and UTC (up the coax)
- 12VDC & 24VAC dual voltage operation
- IP67 Weather Resistance
- UL listed
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# HTINT60TM/HTINT601TA

2.8-12mm motorized lens/3.6mm fixed lens, dark gray housing

### 2MP HD-TVI Intensifier® Turret Cameras

- Captures up to Full HD @ 30fps
- Signal distance up to 1600ft.
- Superior low-light performance
- Amplify existing light with no distance limitation
- Presets: Indoor, Outdoor, Low Light, Lobby, Elevator
- Additional 960H analog output
- Built-in heater and anti-fog glass reduces condensation
- True Day/Night operation (IR cut filter)
- True WDR operation
- Full OSD operation through onboard and UTC (up the coax)
- 3-axis for wall and ceiling mounting



2MP

HD TVI

LOW-LIGHT COLOR TECHNOLOGY

2MP

HD TVI

OPERATES

AY NIGHT

### **Optional Accessories**

PSW5





Power Supply Pigtail (Balun)

TVIUTPPT HD Video Transceive

10

(5)

INTPMT

### HD 2MP



### **Optional Accessories**





PSW5 12\ Power Supply

CVCJBD1 Junction Box

38

Cornei Mount



### VLT9 2MP IR 2.8mm fixed lens, white housing (5) **2MP HD-TVI IR Turret Camera** Captures up to Full HD @ 30fps Built-in IR LEDs • True Day/Night operation (IR cut filter) • IR range: up to 98' (depending on scene reflection) Digital WDR operation • Full OSD operation through onboard and UTC (up the coax) • 12VDC operation (power supply not included) • IP67 Weather Resistance **Optional Accessories** Junction box included • 5 year warranty NDAA Compliant\* \*Products are in compliance with NDAA Section 889 Part B Guidelines TVIUTP HD Video CLTX1 Ceiling Mount 4" Extension WMT1 Wall Mount TVIUTPPT PMT1 Pole Mount PSW5 HD Video Ce 12VDC ransceiver with Pigtail (Balun) ★ ) DAY NIGHT VLDT4G/VLDT4W IR 2MP IP66 3.6mm fixed lens, dark gray/white housing NDA 5 2MP HD-TVI Eveball Cameras Captures up to Full HD @ 30fps • 18 built-in IR LEDs aneee tooho Supports HD-TVI, CVI, AHD, and CVBS • True Day/Night operation (IR cut filter) • IR range: up to 65' (depending on scene reflection) • True WDR operation Full OSD operation through onboard and UTC (up the coax) IP66 Weather Resistance **Optional Accessories** Junction box included 5 year warranty NDAA Compliant\* \*Products are in compliance with NDAA Section 889 Part B Guidelines TVIUTPPT TVIUTP PSW5 HD Video HD Video Transceiver Power Supply Transceiver with Pigtail (Balun)

# VLDT3GM/VLDT3WM

2.8-12mm motorized lens, dark gray/white housing

### 2MP HD-TVI Motorized Eyeball Cameras

- Captures up to Full HD @ 30fps
- 18 built-in IR LEDs
- Supports HD-TVI, CVI, AHD, and CVBS
- True Day/Night operation (IR cut filter)
- IR range: up to 65' (depending on scene reflection)
- True WDR operation
- Full OSD operation through onboard and UTC (up the coax)
- IP66 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*
- \*Products are in compliance with NDAA Section 889 Part B Guidelines



\*) DAY NIGH

IR

### **Optional Accessories**



HD TVI

2MP



PSW5 TVIUTPPT 12VDC HD Video Power Supply Transceiver with Pigtail (Balun)



NDA

40

(HD TVI) (2MP

PSW5

12VD

IR

# VLD9M

2.8-12mm motorized lens, white housing

### 2MP HD-TVI IR Motorized Dome Camera

- Captures up to Full HD @ 30fps
- Supports HD-TVI, CVI, AHD, and 960H Analog
- True Day/Night operation (IR cut filter)
- IR range: up to 98' (depending on scene reflection)
- True WDR operation
- Full OSD operation through onboard and UTC (up the coax)
- 12VDC operation (power supply not included)
- IP67 Weather Resistance
- IK10 Vandal Resistance
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# VLB7

2.8-12mm varifocal lens, white housing

### 2MP HD-TVI IR Bullet Camera

- Captures up to Full HD @ 30fps
- Supports HD-TVI, CVI, AHD, and 960H Analog
- True Day/Night operation (IR cut filter)
- IR range: up to 65' (depending on scene reflection)
- True WDR operation
- Full OSD operation through onboard and UTC (up the coax)
- 12VDC operation (power supply not included)
- IP67 Weather Resistance
- IK10 Vandal Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# C

PMT1

Pole Mount

2MP





PMT1 Pole Mount

CLTX1 Mount



FMT3

Elush Mount

**IP67** 

NDA

IK10

# **HT5940TM**

2.8-12mm motorized lens, dark gray housing

### 2MP HD-TVI Intense IR Dome Camera

- Captures up to Full HD @ 30fps
- Signal distance up to 1600ft.
- Intense IR function no saturation, IR intensity adapts to subject to provide vivid image
- Additional 960H analog output
- Built-in heater and anti-fog glass reduces condensation
- True Day/Night operation (IR cut filter)
- True WDR operation
- Chameleon Cover <sup>™</sup> : snaps on and can be painted to match any décor!
- Full OSD operation through onboard and UTC (up the coax)

- 3-axis for lens mount
- 12VDC & 24VAC dual voltage operation (power supply not included)
- Vandal/Tamper Resistant
- IP67 Weather Resistance
- Junction box included
- 5 year warranty
- TAA Compliant
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



INTCM1

Mount

12VDC Power Supply wer Supply

PSW4

PSW5

INTWM1 CHAM59B

Chameleon

Cover



CLTX1

unt

Ceiling Moun 4" Extension

IR

WMT1

Wall Mount

Ó ★) DAY NIGHT

5

AY NIGHT

ZOOM

HD TVI

HD TVI

2MP

2MP

# **HT5940TMB**

2.8-12mm motorized lens, dark gray housing

### 2MP HD-TVI Intense IR Dome Camera

- Captures up to Full HD @ 30fps
- Signal distance up to 1600ft.
- Intense IR function no saturation, IR intensity adapts to subject to provide vivid image
- Additional 960H analog output
- Built-in heater and anti-fog glass reduces condensation
- True Day/Night operation (IR cut filter)
- True WDR operation
- Chameleon Cover <sup>™</sup> : snaps on and can be painted to match any décor!
- Full OSD operation through onboard and UTC (up the coax)

# **HT7040TM**

2.8-12mm motorized lens, dark gray housing

### 2MP HD-TVI Intense IR Bullet Camera

- Captures up to Full HD @ 30fps
- Signal distance up to 1600ft.
- Intense IR function no saturation, IR intensity adapts to subject to provide vivid image
- Additional 960H analog output
- Built-in heater and anti-fog glass reduces condensation
- True Day/Night operation (IR cut filter)
- True WDR operation
- Full OSD operation through onboard and UTC (up the coax)
- 12VDC & 24VAC dual voltage operation (power supply not included)

- Vandal/Tamper Resistant
- IP67 Weather Resistance

3-axis for lens mount

(power supply not included)

• Vandal/Tamper Resistant

• IP67 Weather Resistance

Products are in compliance with NDAA Section 889 Part B Guidelines

Junction box included

5 year warranty

TAA Compliant

NDAA Compliant\*

- Junction box included
- 5 year warranty
- TAA Compliant
- NDAA Compliant<sup>2</sup>
  - \*Products are in compliance with NDAA Section 889 Part B Guidelines



(5)

IR



# HLED33DTB/HLED33DTW

2.8-12mm auto iris varifocal lens, black/white housing

### 2MP HD-TVI IR Dome Camera

- Captures up to Full HD @ 30fps
- Smart DNR reduces noise in low light
- Smart IR reduces saturation of objects within close proximity to IR LEDs
- IR range: up to 65' (depending on scene reflection)
- Additional 960H analog output
- Digital WDR operation
- Full OSD operation through onboard and UTC (up the coax)
- 3-axis for wall and ceiling mounting
- 12VDC & 24VAC dual voltage operation (power supply not included)
- 5 year warranty
- TAA Compliant
- NDAA Compliant<sup>\*</sup>

\*Products are in compliance with NDAA Section 889 Part B Guidelines



### **Optional Accessories**







PSW5 12VDC 24VA0 Po

HD Video Transceiver witl Pigtail (Balun)

HD Video









# HTINT40T1

3.6mm fixed lens, dark gray housing

### 2MP HD-TVI Intensifier<sup>®</sup> Mini-Board Camera

- Captures up to Full HD @ 30fps
- Superior low-light performance
- Amplify existing light with no distance limitation
- With presets for different scenarios
- Additional 960H analog output
- True Day/Night operation (IR cut filter)
- True WDR operation
- Full OSD operation through onboard and UTC (up the coax)
- 12VDC voltage operation (power supply not included)
- 5 year warranty
- TAA Compliant
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines





960 H



2MP



Transceiv

HD Video

Transceiver with Pigtail (Balun)

HTINTT5T

Accepts C & CS auto iris & manual type lenses, dark gray housing

### 2MP HD-TVI Intensifier® T Traditional Camera

- Captures up to Full HD @ 30fps
- See color In almost complete darkness without IR LEDs
- No problems caused by objects that reflect or absorb IR light sources
- With presets for different scenarios
- True Day/Night operation (IR cut filter)
- True WDR operation
- Full OSD operation through onboard and UTC (up the coax)
- 12VDC & 24VAC dual voltage operation (power supply not included)
- 5 year warranty
- NDAA Compliant\*

**VL62T** 

 Captures up to Full HD • 12 built-in IR LEDs • Color Day/Night camera

True WDR operation

• 5 year warranty NDAA Compliant

• IP67 Weather Resistance

3.6mm fixed lens, black housing

\*Products are in compliance with NDAA Section 889 Part B Guidelines

2MP HD-TVI Bullet Camera with **Built-in IR LEDs and Sunshield** 

• IR range: up to 60' (depending on scene reflection)

\*Products are in compliance with NDAA Section 889 Part B Guidelines

True Day/Night operation (IR cut filter)

12VDC operation (power supply included)



**Optional Accessories** 

PSW4









TVIUTPPT HD Video

TVIUTP HD Video Transceive

VCH401HBM1 Housing with Heater Blower & Bracket



### **Optional Accessories**



(4) PSW5 12VDC Power Supply

TVIUTPPT HD Video Transceiver with Pigtail (Balun)

6











# VL572TPIR

3.7mm pinhole lens, operating PIR, white housing

### 2MP HD-TVI IR Bullet Camera

- Captures up to Full HD
- Camera encased in working PIR
- True Day/Night operation (IR cut filter)
- Fully adjustable wall/ceiling mount included
- 5 year warranty
- NDAA Compliant\*
- \*Products are in compliance with NDAA Section 889 Part B Guidelines



### **Optional Accessories**



PSW5 12VDC Power Supply T

TVIUTPPT HD Video Transceiver with Pigtail (Balun)

TVIUTP HD Video Transceiver





# CVC607CMT

3.6mm fixed lens, stainless steel housing

### 2MP HD-TVI Vandal Resistant Corner Mount Color Camera

- Captures up to Full HD @ 30fps
- Vandal resistant 90° corner mount camera
- Heavy duty housing is built to withstand blows from a 10 lb. sledgehammer
- Additional 960H analog output
- Full OSD operation through onboard and UTC (up the coax)
- 12VDC operation (power supply not included)
- 5 year warranty
- TAA Compliant
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines





### **Optional Accessories**





3.6mm fixed lens, stainless steel housing

### **2MP HD-TVI In-Wall Camera**

- Captures up to Full HD @ 30FPS
- Fits into a single gang electrical box (included)
- Brushed stainless steel faceplate
- Additional 960H analog output
- 12VDC operation (power supply not included)
- 5 year warranty
- NDAA Compliant\*
- \*Products are in compliance with NDAA Section 889 Part B Guidelines





**Optional Accessories** 



# HLPR1TW

9-22mm auto iris varifocal lens, white housing

### 2MP HD-TVI License Plate Capture Camera

- Captures up to Full HD @ 30fps
- High-contrast imaging performance that delivers sharp, clear license-plate captures
- Built-in IR LEDs
- IR range: up to 50' (depending on scene reflection)
- Captures license plates up to 30 mph
- True Day/Night operation (IR cut filter)
- True WDR operation
- Full OSD operation through onboard and UTC (up the coax)
- IP66 Weather Resistance
- Junction box included
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



### **Optional Accessories**



题 PSW/

# HTPTZ20T

4.7-94mm 20x optical zoom lens, white housing

### 2MP HD-TVI Full HD PTZ Camera

- Captures up to Full HD @ 30fps
- Up to 20x Optical Zoom and 16x Digital Zoom
- 240 preset positions
- 4 Alarm Inputs / 2 Alarm Outputs
- Max 380°/sec speed
- True Day/Night operation (IR cut filter)
- True WDR operation
- Additional 960H analog output

### **Optional Accessories**



PSW4 24VA0 er Supply





Transceiv



















WMA29DW PEN29DW Wall Mount

Pendant Arm

PMA29DW Pole Mount Adapter

POL28DW Pole Mount

APT32DW Adapter Plate for COR32DW or POL28DW

COR32DW Corner Mount Adapter

APT29DW Adapter Plate for COR32DW or POL28DW when using WMA29DW

WAC29DW Wall/Ceiling Mount

**KBDPTZ1** Keyboard Controller

46

- (up the coax) Pan, Tilt, Zoom • IP66 Weather Resistance 1 year warranty
- TAA Compliant
- NDAA Compliant\*
- \*Products are in compliance with NDAA Section 889 Part B Guidelines

• Full OSD operation through UTC







# HD-TVI | ACCESSORIES

# TVIUTP

### HD-TVI Balun over UTP

- Send HD-TVI signal up to 656' (200M) over UTP cable.
- BNC male to screw terminal for easy connection.
- Compact size allows mounting of multiple units behind multiplexers, Quads, DVRs, etc. Passive, No power required.
- Built in ESD, EFT (impulse noise), lightning (surge) and transient protection.
- · Sold individually but used in pairs. Could be used in conjunction with another
- TVIUTP, or with the pigtail model TVIUTPPT. 2 year warranty
- NDAA Compliant\*
- Also available with 4" pigtail: TVIUTPPT
- BNC male to screw terminal with 4" (10cm) mini coax. (TVIUTPPT) \*Products are in compliance with NDAA Section 889 Part B Guidelines **TVIUTPPT** shown
- **TVIUTP4**



0000

🚳 🚳 🚳

0)

### 4-Port HD-TVI Video Balun over UTP

- HD-TVI Resolution up to 5MP
- HD-TVI Signal extension up to 820' (250M) over UTP CAT5e/6 depending on resolution and cable quality.
- Male BNC to terminal block design.
- No power required.
- Built-in ESD, EFT (impulse noise) and transient protection.
- 2 year warranty
- NDAA Compliant\*
- Also available in 16 port: TVI16UTP

\*Products are in compliance with NDAA Section 889 Part B Guidelines

NDAA

(i) · 🗖

### **Active HD-TVI UTP Balun**

**TVIUTPA** 

- Resolution up to 4K (8MP).
- HD-TVI Signal extension up to 1312' (400M), depending on cable quality and resolution.
- Built in L, M, and H high frequency video gain.
- Built-in transient protection for ground lifting, voltage spike damage.
- Includes transmitter and receiver
- 2 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# SPTVIVP

### **HD-TVI Video and Power Surge Protector**

- Resolution up to 4K.
- Supports power input up to AC40V/ DC56V.
- Response time less than 1 ns.
- 2 year warranty
- NDAA Compliant\*
- \*Products are in compliance with NDAA Section 889 Part B Guidelines

# TVICOAXVP

### **HD-TVI Video and Power Balun over Coax**

• Send HD-TVI video signal up to 984' (300M) over Coax cable. • Send power up to 1312' (400M) over Coax cable. (Distance will vary greatly depending on Voltage and Amperage/power consumption of camera. Please refer to manual for exact distances.)

# NDAA TVIUTPPTP

### HD-TVI Video and Power Balun over Cat5e

- Send HD-TVI video signal up to 820' (250M)
- over Cat5e (or greater) cable. Send power up to 326' (100M) over Cat5e cable.



NDA

- (Distance will vary greatly depending on Voltage and Amperage/power consumption of camera. Please refer to manual for exact distances.)
- Built with DC jack for power transmission. • Male BNC to RJ45 connector with pigtail design.
- Built-in ESD, EFT (impulse noise) and transient protection.
- 2 vear warranty
- NDAA Compliant\*
- \*Products are in compliance with NDAA Section 889 Part B Guidelines

# TVIHD

### **TVI to HDMI Converter**

- Converts HD-TVI/AHD/HDCVI/NTSC/PAL/960H
- signals to HDMI, VGA or Composite Video. • Supports: 720p@25/30/50/60, 1080p@25/30Hz
- Built-in loopout
- Includes 12V power supply
- 2 year warranty
- NDAA Compliant<sup>®</sup>
- \*Products are in compliance with NDAA Section 889 Part B Guidelines

# **TVIGL**

### Ground Loop Isolator for TVI Cameras

- IMPORTANT: The TVIGL does not support UTC function. Please make any adjustments between camera and recorder prior to installation of the TVIGL. UTC commands WILL NOT work after this has been installed.
- Prevents video-signal distortion caused by video ground loops.
- Prevents power cables from interfering with the HD camera signal.
- Eliminates picture tearing, cross-talk and rolling.
- Passive, no power required.
- Supports resolutions up to 4K. Maximum distance: 7874' (200M)
- 2 year warranty
- NDAA Compliant\*
- Ground loop isolator for power only: VIDGLT \*Products are in compliance with NDAA Section 889 Part B Guidelines



**TVIFBR** 



### HD-TVI/AHD/HD-CVI/CVBS Fiber Extender with RS485

- · Digital and non-compression coding technology
- Supports HD-TVI/AHD/HD-CVI/CVBS and RS485 data
- signal over fiber optical cable Single signal mode: 12.42 miles (20KM),
- Multiple signal mode: 1.24 miles (2KM) • Supports resolutions up to 2MP: 720p/25, 30, 50, 60Hz; 1080p/25, 30Hz.
- 2 year warranty
- NDAA Compliant\*
- \*Products are in compliance with NDAA Section 889 Part B Guidelines
- Includes DC24V, 1.25A power adapter
- (will provide 12V to camera) 2 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines









TVI16UTP shown



NDAA

NDAA

# **RECORDERS | 5MP HVRS**



Record: guickly setup recording resolutions and recording type

EZ Search 2.0: quickly search events from thumbnails

EZ Copy: copy what you are playing onto a USB flash drive

- Supports up to 5MP (HD-TVI + IP) on all channels and 4K (IP) on 1 channel (H6HRLN)
- Supports up to 5MP (HD-TVI + IP) on all channels and 4K (IP) on 8 channels (H16HRLN, H24HRLN)
- H.265 compression Store up to 2x more than H.264!
- 1 SATA port for up to 16TB storage (H6HRLN)
- 2 SATA ports for up to 32TB storage (H16HRLN, H24HRLN)
- 1 eSATA port for an additional 8TB of storage
- 4K HDMI out and VGA monitor output

- Alarm 4/8/16 inputs, 1/2/4 outputs
- Free US-based DDNS and P2P services
- Remote viewing via web browser, your Apple TV, Amazon Fire TV, or your mobile device
- Easy video exporting via USB
- Rack ears included (H16HRLN and H24HRLN)
- 5 year limited warranty\*\*
- NDAA Compliant\*\*\*

\*with Speco Smart Analytic IP Cameras \*\*Excludes HDDs

\*\*\*Products are in compliance with NDAA Section 889 Part B Guidelines



speco access



Camera

- Event Tag
- MODEL HRLN CHANNELS 6 16 24 Analog Only Output BNC x 4 BNC x 8 **BNC x 16** Network Access & Transfer Bandwidth 16/40Mbps 32/96Mbps 64/192Mbps Video **Network Access Format** 8MP/5MP/4MP/3MP/1080P/960P/720P @ 25/30fps HDMI x 1: 4K x 2K / 1920 x 1080 / 1280 x 1024 Output BNC x 1: CVBS (used as the main or spot output) RCA x 4 RCA x 8 Input 2-way Audio Take up channel one audio input Audio Local Output RCA x 1 **Record Stream** Dual stream recording Resolution 4K/5MP/4MP/1080P/720P/WD1 Analog: 5MP @ 12fps (PAL/NTSC), 4MP/3MP @ 12fps/15fps (PAL/NTSC, Under 4MP @ 25fps/30fps (PAL/NTSC) Analog: 5MP @ 12fps (PAL/NTSC), 4MP/3MP @ 12fps/15fps (PAL/NTSC), Under 4MP @ 25fps/30fps (PAL/NTSC) IP: 8MP and under @ 25fps/30fps (PAL/NTSC) Recording Frame Rate IP: 8MP @ 20fps (PAL/NTSC), Under 8MP @ 25fps/30fps (PAL/NTSC) Mode Manual, schedule, motion, sensor, intelligence SATA x 1, up to 16TB per HDD HDD SATA x 2, up to 16TB per HDD Storage eSATA eSATA x 1, Max 8TB RJ 45 10M/100M/100Mbps x 1 RJ 45 10M/100Mbps x 1 Network Interface -----**Power Consumption** ≤ 10W (without HDD) ≤ 15W (without HDD) ≤ 30W (without HDD) Power P32S36GM **Viewing Clients** SecureGuard® Client, SecureGuard® CMS, Apple TV, Amazon Fire TV, Speco Blue iOS, Speco Blue Android 36 Port Managed Gigabit Network Switch

### **Optional Accessories**



P24S26G

(32 ports PoE, 4xSFP Uplink)

器 ⊕ ⊕ ⊠

6220 D

Speco

BLUE

# **RECORDERS | 2MP HVRS**

IP

HD TVI

HYBRID

D	N
Γ	

HRN Series - 2MP H.265 Hybrid DVR with Smart Analytics

H6HRN 6 Channel Hybrid Digital Video Recorder (4 TVI Channels plus 2 IP Channels) H12HRN 12 Channel Hybrid Digital Video Recorder (8 TVI Channels plus 4 IP Channels)

CONFIGURATIONS							
H6HRN2TB H6HRN12TB H12HRN8TB							
H6HRN4TB	H6HRN16TB	H12HRN12TB					
H6HRN6TB	H12HRN2TB	H12HRN16TB					
H6HRN8TB	H12HRN4TB						
H6HRN10TB	H12HRN6TB						



- Camera: quickly discover and install all Speco IP cameras
- Setup: for quick setup of general settings
- Network: network setup and port forwarding
- · Record: quickly setup recording resolutions and recording type
- EZ Search 2.0: quickly search events from thumbnails
- EZ Copy: copy what you are playing onto a USB flash drive
- EZ Mobile: easy mobile setup for viewing on desktop or mobile apps
- Supports up to 2MP (HD-TVI) on all channels and 5MP (IP) on 2 channels (H6HRN)
- Supports up to 2MP (HD-TVI) on all channels and 5MP (IP) on 4 channels (H12HRN)

MODE

- H.265 compression Store up to 2x more than H.264!
- 1 SATA port for up to 16TB storage (H6HRN, H12HRN)
- 1 eSATA port for an additional 8TB of storage (H12HRN)

speco lectrologies <sup>1</sup> <sup>1000</sup>	

H.265

2MP

EZP SEARCH 2.0

S.M.A.R.T

P2P



- HDMI out and VGA monitor output
- 2-way audio communication • Smart Search - Specify a region on the camera
- view and search on changes in that area\*

N6HRN shown

- Object and line crossing detection and alerts\*
- Alarm 4/8/16 inputs, 1/2/4 outputs
- Free US-based DDNS and P2P services
- Remote viewing via web browser, your Apple TV, Amazon Fire TV, or your mobile device
- Easy video exporting via USB
- 5 year limited warranty\*\*
- NDAA Compliant\*\*\*
  - \*with Speco Smart Analytic IP Cameras
  - \*\*Excludes HDDs

цр

\*\*\*Products are in compliance with NDAA Section 889 Part B Guidelines

MODEL		HRN		
	CHANNELS	6	12	
	Bandwidth	16Mbps	32Mbps	
Malaa	IP Video Input	Up to 2MP @ 30fps		
Video	Output	HDMI x 1: 1920 x 1080 / 1280 x 1024 / 1024 x 768 VGA x 1: 1920 x 1080 / 1280 x 1024 / 1024 x 768 BNC x 1: CVBS (used as the main or spot output)		
	Input RCA x 4 RCA x 8			
Audio	2-way Audio	Take up channel one audio input		
	Output	RCA x 1 (linear, 600ff)		
	Resolution	1080P/1080P Lite/720P/WD1/D1		
Recording	Frame Rate	Analog Channel: 1080P @ 15fps (NTSC) 720P/WD1/D1/ 30fps (NTSC) IP Channel: 30fps (NTSC)		
	Mode	Manual, timer, motion, smart event		
Storage	HDD	SATA x 1, up to 16TB		
Storage	eSATA	eSATA x 0	eSATA x 1, Max 8TB	
Network	Interface	RJ 45 1000Mbps x 1		
Power	Power Consumption	≤ 10W (without HDD)		
Viewing Clie	ents	SecureGuard® VMS, SecureGuar Apple TV, Amazon Fire TV, Speco Blue iOS		



# speco access



Auto Live Camera Pop-Up View A Ca Event Tag

ERS1V

**Optional Accessories** 



P4S5V 5-Port Gigabit Network Switch (4 ports PoE, 1 port uplink)

P24S26G

26 Port Gigabit Network Switch (24 ports PoE, 2xSFP Uplink)

P4S6G 6-Port Gigabit Network Switch (4 ports PoE, 2 ports uplink)

.....

P32S36GM 36 Port Managed Gigabit Network Switch (32 ports PoE, 4xSFP Uplink)

P8S9G 9 Port Gigabit Network Switch (8 ports PoE, 1 port Uplink)

P8S10G 10-Port Gigabit Network Switch (8 ports PoE, 2 ports uplink)

P4S5G



WALL MOUNT CONFIGURABLE

# NRN

NRN Series - 4K H.265 NVR with Smart Analytics

N4NRN 4 Channel Network Video Recorder with 4 Built-in PoE Ports
 N8NRN 8 Channel Network Video Recorder with 8 Built-in PoE Ports
 N16NRN 16 Channel Network Video Recorder with 16 Built-in PoE Ports

CONFIGURATIONS					
N4NRN2TB	N16NRN12TB				
N4NRN4TB	N4NRN16TB	N8NRN8TB	N16NRN4TB	N16NRN16TB	
N4NRN6TB	N8NRN2TB	N8NRN12TB	N16NRN6TB	N16NRN24TB	
N4NRN8TB	N8NRN4TB	N8NRN16TB	N16NRN8TB	N16NRN32TB	

- EZ Wizards: For ease of use and setup
- Camera: quickly discover and install all Speco IP cameras

EZ Copy: copy what you are playing onto a USB flash drive

• Real time recording up to 8MP resolution (4K) @ 30fps

• H.265 compression - Store up to 2x more than H.264!

• 1 SATA port for up to 16TB storage (N4NRN, N8NRN)

IP Camera Main Monitor

VGA

Supported Resolutions

Max Frame Rate per Channel

Front

Rear

- Setup: for quick setup of general settings
- Network: network setup and port forwarding

EZ Search 2.0: quickly search events from thumbnails

Record: quickly setup recording resolutions and recording type

EZ Mobile: easy mobile setup for viewing on desktop or mobile apps

4

VGA

RCA x 1

RCA x 1

4 CH. IPC audio input

4K/5MP/4MP/3MP/1080P/720P

Analytics, continuous, motion, sensor, schedule, manual

Temperature, Power On Time, Bad Sectors and Health

H.264 / H.265 Auto Detection

SATA x 1, up to 16TB per HDD

Live and Playback, Free Size

≤ 15W (without HDD)

Any Resolution @ 30fps

Max. 5 seconds

Max. 10 seconds

USB 2.0 x 1

USB 2.0 x 1

40Mbps

- Easy video exporting via USB
  - Level 1 UL 2900-2-3 Cybersecurity Certification

Free US-based DDNS and P2P services

Amazon Fire TV, or your mobile device

N4NRN shown

Object and line crossing detection and alerts\*

• Remote viewing via web browser, your Apple TV,

NRN

- Remote control included
- 5 year limited warranty\*\*
- NDAA Compliant\*\*\*

8 CH. IPC audio input

Crowd Density, People Counting, Object Detection, Tampering, Tripwire, Intrusion

80Mbps

SecureGuard® CMS, SecureGuard® Client, Apple TV, Amazon Fire TV, Speco Blue iOS, Speco Blue Android, Internet Explorer, Google Chrome

with Speco Smart Analytic IP Cameras

NRN

People and vehicle detection\*

\*\*Excludes HDDs

8

H.264 / H.265 Auto Detection (Max. 8MP)

HDMI (Max. 4K) and VGA (Max. Full HD)

\*\*\*Products are in compliance with NDAA Section 889 Part B Guidelines

16

16 CH. IPC audio input

SATA x 2, up to 16TB per HDD

96Mbps



. 🛯 🧿

**P2P** 



Auto Live Camera Pop-Up View A Camera Event Tag



• Smart Search - Specify a region on the camera view and search on changes in that area\*

4K HDMI out and VGA monitor output

MODEL

**CHANNELS** 

Network Input

2-way Audio

Local Output

**Recording Mode** 

Pre-recording

Post-recording

Digital Zoom

S.M.A.R.T

Bandwidth

Smart Analytics

**Power Consumption** 

Input

Output

Codec

HDD

USB

Video

Audio

Recording

Storage

Features

Network

Viewing Clients

Power

2 SATA ports for up to 32TB storage (N16NRN)

### What is UL 2900-2-3?

UL 2900-2-3 was developed by Underwriters Laboratories (UL) to provide a foundational set of cybersecurity performance and evaluation requirements for manufacturers like Speco Technologies. It was developed with industry input and establishes a baseline of cyberprotection against known vulnerabilities, weaknesses and malware.

UL and the UL logo are trademarks of UL LLC © 2021



# NDI

NRL Series - 4K H.265 NVR A Lite Smart NVR with PoE

N4NRL	4 Channel Network Video Recorder with 4 Built-in PoE Ports
N8NRL	8 Channel Network Video Recorder with 8 Built-in PoE Ports

CONFIGURATIONS							
N4NRL2TB N4NRL12TB N8NRL8TB							
N4NRL4TB	N4NRL16TB	N8NRL10TB					
N4NRL6TB	N8NRL2TB	N8NRL12TB					
N4NRL8TB	N8NRL4TB	N8NRL16TB					
N4NRL10TB	N8NRL6TB						

### EZ Wizards: For ease of use and setup

- Camera: quickly discover and install all Speco IP cameras
- Setup: for guick setup of general settings
- Network: network setup and port forwarding

· Record: quickly setup recording resolutions and recording type EZ Search 2.0: quickly search events from thumbnails EZ Copy: copy what you are playing onto a USB flash drive

- Real time recording up to 8MP resolution (4K) @ 30fps
- H.265 compression Store up to 2x more than H.264!
- Built-in PoE ports for all channels for easy installation
- 1 SATA port for up to 16TB storage
- 4K HDMI out and VGA monitor output
- 2-way audio communication
- Smart Search Specify a region on the camera view and search on changes in that area\*



IP

**4**K

H.265

N8NRL shown

- Object and line crossing detection and alerts\*
- Free US-based DDNS and P2P services
- Remote viewing via web browser, your Apple TV, Amazon Fire TV, or your mobile device
- Easy video exporting via USB
- 5 year limited warranty\*\*

\*with Speco Smart Analytic IP Cameras \*\*Excludes HDDs



CIRC .

EZP SEARCH 2.0



Auto Live Camera Pop-Up Event Tag

Speco

BLUE



**Optional Accessories** 

ERS1V Vented Rack Shelf

# NRE

NRE Series - 4K H.265 NVR with Facial Recognition and Smart Analytics

N8NRE 8 Channel Facial Recognition Network Video Recorder with 8 Built-in PoE Ports N16NRE 16 Channel Facial Recognition Network Video Recorder with 16 Built-in PoE Ports N32NRE 32 Channel Facial Recognition Network Video Recorder

	CONFIGURATIONS							
N8NRE2TB	N8NRE16TB	N16NRE12TB	N32NRE4TB	N32NRE24TB	N32NRE96TB			
N8NRE4TB	N16NRE2TB	N16NRE16TB	N32NRE6TB	N32NRE32TB	N32NRE112TB			
N8NRE6TB	N16NRE4TB	N16NRE24TB	N32NRE8TB	N32NRE40TB				
N8NRE8TB	N16NRE6TB	N16NRE32TB	N32NRE12TB	N32NRE64TB				
N8NRE12TB	N16NRE8TB	N32NRE2TB	N32NRE16TB	N32NRE70TB				



- · Camera: quickly discover and install all Speco IP cameras
- Setup: for guick setup of general settings
- Network: network setup and port forwarding
- · Record: quickly setup recording resolutions and recording type
- EZ Search 2.0: quickly search events from thumbnails
- EZ Copy: copy what you are playing onto a USB flash drive

EZ Mobile: easy mobile setup for viewing on desktop or mobile apps

8

N/A

RCA x 1

RCA x 1

8 CH. IPC audio input

4K/5MP/4MP/3MP/1080P/720P

H.264 / H.265 Auto Detection

SATA x 1, up to 16TBper HDD

Live and Playback, Free Size

≤ 15W (without HDD)

Any Resolution @ 30fps

Max. 5 seconds

Max. 10 seconds

USB 2.0 x 1

USB 3.0 x 1

80Mbps

- Real time recording up to 8MP resolution (4K) @ 30fps
- H.265 compression Store up to 2x more than H.264! • 1 SATA port for up to 16TB storage (N8NRE) 2 SATA ports for up to 32TB storage (N16NRE) 8 SATA ports for up to 112TB storage (N32NRE)
- 4K HDMI out and VGA monitor output

MODEL

CHANNELS

**Network Input** 

2-way Audio

Local Output

**Recording Mode** 

Pre-recording

Post-recording

**Digital Zoom** 

S.M.A.R.T

Bandwidth

**Smart Analytics** 

**Power Consumption** 

**Supported Resolutions** 

Max Frame Rate per Channel

Front

Rear

Input

Output

Codec

HDD

USB

Video

Audio

Recording

Storage

Features

Network

**Viewing Clients** 

Power

52

(N32NRE: additional storage via 2 eSATA ports)

**IP Camera** 

**Main Monitor** 

Sub Monitor

 Smart Search - Specify a region on the camera view and search on changes in that area\*

N8NRE shown

- Object and line crossing detection and alerts
  - Facial Recognition and Comparison\*\*
- Free US-based DDNS and P2P services
- Remote viewing via web browser, your Apple TV Amazon Fire TV, or your mobile device

32

1 HDMI

32 CH. IPC audio input

USB 2.0 x 1. USB 3.0 x 1

256Mbps

- Easy video exporting via USB
- Remote control included

\*\*\*Excludes HDDs

16 CH. IPC audio input

Facial Recognition, Crowd Density, People Counting, Object Detection, Tampering, Tripwire, Intrusion

16

H.264 / H.265 Auto Detection (Max. 8MP)

Analytics, continuous, motion, sensor, schedule, manual

Temperature, Power On Time, Bad Sectors and Health

HDMI (Max. 4K) and VGA (Max. Full HD)

- Rack ears included (N16NRE and N32NRE)
- 5 year limited warranty\*\*\*
  - \*with Speco Smart Analytic IP Cameras \*\*with Speco Facial Recognition Cameras

NRE





**P2P** 

WALL MOUNT CONFIGURABLE

# speco access



Auto Live Camera Pop-Up **Event Tag** 



P32S3	

Network Switch (32 ports PoE, 4xSFP Uplink)

----

P24526G

### **Optional Accessories**

ERSIV P4S5G P4S5G P4S5U P4S5G P8S9G P8S9G P8S9G P8S9G P8S9G P8S9U P8S9U

(4 ports PoE, 1 port Uplink)

(4 ports PoE, 1 port uplink)

160Mbps

SecureGuard® CMS, SecureGuard® Client, Apple TV, Amazon Fire TV, Speco Blue iOS, Speco Blue Android, Internet Explorer , Google Chrome

(4 ports PoE, 2 ports uplink)

(8 ports PoE, 1 port Uplink)

(8 ports PoE, 2 ports uplink)



NRD

NRD Series - 4K H.265 NVR with Facial Recognition and Smart Analytics



N16NRD 16 Channel Facial Recognition Network Video Recorder with Dual LAN Ports

CONFIGURATIONS				
N16NRD2TB	N16NRD12TB			
N16NRD4TB	N16NRD16TB			
N16NRD6TB	N16NRD24TB			
N16NRD8TB	N16NRD32TB			

### EZ Wizards: For ease of use and setup

- · Camera: quickly discover and install all Speco IP cameras
- Setup: for quick setup of general settings
- Network: network setup and port forwarding
- Record: guickly setup recording resolutions and recording type
- EZ Search 2.0: quickly search events from thumbnails
- EZ Copy: copy what you are playing onto a USB flash drive
- EZ Mobile: easy mobile setup for viewing on desktop or mobile apps 5 year limited warranty\*\*\*
- Two LAN ports to help isolate camera traffic on a PoE switch from the main network.
- Real time recording up to 8MP resolution (4K) @ 30fps
- H.265 compression Store up to 2x more than H.264!
- 2 SATA ports for up to 32TB storage (N16NRE)
- 4K HDMI out and VGA monitor output
- Smart Search Specify a region on the camera view and search on changes in that area\*

Object and line crossing detection and alerts\*

N16NRD shown

- Facial Recognition and Comparison\*
- Free US-based DDNS and P2P services
- Remote viewing via web browser, your Apple TV, Amazon Fire TV, or your mobile device
- Easy video exporting via USB
- Remote control included
- \*with Speco Smart Analytic IP Cameras
- \*\*with Speco Facial Recognition Cameras
- \*\*\*Excludes HDDs

MODEL			NRD	
	CHANNEL	S	16	
	Input	IP Camera	H.264 / H.265 / H.265+	
Video	Output	Main Monitor	HDMI (Max. 4K) and VGA (Max. Full HD)	
	Output	Sub Monitor	N/A	
	Network Input		16 CH. IPC audio input	
Audio	2-way Audio		RCA x 1	
	Local Output		RCA x 1	
	Supported Resoluti	ons	4K/5MP/4MP/3MP/1080P/720P/960H/D1/CIF	
	Codec		H.264 / H.265 Auto Detection	
Recording	Max Frame Rate per Channel		NTSC @ 30fps; PAL @ 25fps	
Recording	Recording Mode		Motion, sensor, manual, exception, intelligence	
	Pre-recording		Max. 5 seconds	
	Post-recording		Max. 10 seconds	
	HDD		SATA x 2, up to 16TB per HDD	
Storage	USB	Front	USB 2.0 x 1	
	USB	Rear	USB 3.0 x 1	
	Digital Zoom		Live and Playback, Free Size	
Features	Smart Analytics		People Counting, Object Detection, Tampering, Tripwire, Intrusion	
	S.M.A.R.T		Temperature, Power On Time, Bad Sectors and Health	
Network	rk Bandwidth		160Mbps	
Power	Power Consumptio	n	≤ 15W (without HDD)	
Viewing Clier	ıts		SecureGuard <sup>®</sup> CMS, SecureGuard <sup>®</sup> Client, Speco Blue iOS, Speco Blue Android, Internet Explorer , Google Chrome	



P32S36GM 36 Port Managed Gigabit Network Switch (32 ports PoE, 4xSFP Uplink)

### **Optional Accessories**



 ERSIV
 P4S5G
 P4S5V
 P4S6G
 P8S9G
 P8S10G

 Vented Rack Shelf
 5 Port Gigabit Network Switch
 5-Port Gigabit Network Switch
 6-Port Gigabit Network Switch
 9 Port Gigabit Network Switch
 10-Port Gigabit Network Switch

 (4 ports PoE, 1 port Uplink)
 (4 ports PoE, 1 port uplink)
 (4 ports PoE, 2 ports uplink)
 (8 ports PoE, 1 port Uplink)
 (8 ports PoE, 2 ports uplink)

### NR NR Series - 4K H.265 NVR with Smart Analytics

N64NR 64 Channel Network Video Recorder

N128NR 128 Channel Network Video Recorder

CONFIGURATIONS						
N64NR6TB	N64NR24TB	N64NR72TB	N128NR6TB	N128NR24TB	N128NR72TB	N128NR160TB
N64NR8TB	N64NR30TB	N64NR80TB	N128NR8TB	N128NR30TB	N128NR80TB	N128NR192TB
N64NR12TB	N64NR32TB	N64NR96TB	N128NR12TB	N128NR32TB	N128NR96TB	N128NR224TB
N64NR16TB	N64NR40TB	N64NR112TB	N128NR16TB	N128NR40TB	N128NR112TB	N128NR256TB
N64NR20TB	N64NR64TB	N64NR128TB	N128NR20TB	N128NR64TB	N128NR128TB	

### EZ Wizards: For ease of use and setup

- Camera: quickly discover and install all Speco IP cameras
- Setup: for quick setup of general settings
- Network: network setup and port forwarding
- Record: quickly setup recording resolutions and recording type
- EZ Search 2.0: guickly search events from thumbnails
- EZ Copy: copy what you are playing onto a USB flash drive

EZ Mobile: easy mobile setup for viewing on desktop or mobile apps • 5 year limited warranty\*\*

- Real time recording up to 8MP resolution (4K) @ 30fps
- H.265 compression Store up to 2x more than H.264!
- 8 SATA ports for up to 128TB storage (N64NR)
- 16 SATA ports for up to 256TB storage (N128NR) • 4K HDMI out and VGA monitor output
- (additional storage via 2 eSATA ports)

MODEL

• Smart Search - Specify a region on the camera view and search on changes in that area\*

	Object and line cross	ssing detection and alerts*
--	-----------------------	-----------------------------

- Free US-based DDNS and P2P services
- Remote viewing via web browser, your Apple TV, Amazon Fire TV, or your mobile device

64NR shown

00

- Easy video exporting via USB
- Remote control included
- Rack ears included
- \*with Speco Smart Analytic IP Cameras \*\*Excludes HDDs

NR



EZP SEARCH 2.0

EZ

(**5**) **3 SKY** 

P2P



- Auto Live Camera Pop-Up View A CameraEvent Tag

CHANNELS		ELS	64	128	
Input IP Camera		IP Camera	H.264 / H.265 Auto Detection (Max. 8MP)		
Video	Main Monitor		HDMI (Max. 4K) and VGA (Max. Full HD)		
	Output	Sub Monitor	1 HDMI		
Network Input		put	64 CH. IPC audio input	128 CH. IPC audio input	
Audio 2-way Audio		io	RCA x 1		
Local Output		out	RCA x 1		
Supported Resolutions		Resolutions	4K/5MP/4MP/3MP/1080P/720P		
Codec			H.264 / H.265 Auto Detection		
Recording	Max Frame Rate per Channel		Any Resolution @ 30fps		
Recording	Recording Mode		Analytics, continuous, motion, sensor, schedule, manual		
	Pre-record	ing	Max. 5 seconds		
	Post-recording		Max. 10 seconds		
HDD			SATA x 8, up to 16TBper HDD	SATA x 16, up to 16TBper HDD	
Storage	USB	Front	USB 2.0 x 1		
	0.00	Rear	USB 2.0 x 1, USB 3.0 x 1		
	Digital Zoom		Live and Playback, Free Size		
Features	Smart Ana	lytics	People Counting, Object Detection, Tampering, Tripwire, Intrusion		
S.M.A.R.T			Temperature, Power On Time, Bad Sectors and Health		
Network	Network Bandwidth		320Mbps	384Mbps	
Power Power Consumption		sumption	≤ 15W (without HDD)		
Viewing Clients			SecureGuard® CMS, SecureGuard® Client, Apple TV, Amazon Fire TV, Speco Blue iOS, Speco Blue Android, Internet Explorer , Google Chrome		

### **Optional Accessories**

 ERSIV
 P4S5G
 P4S5V
 P4S6G
 P8S9G
 P859G

 Vented Rack Shelf
 5 Port Gigabit Network Switch
 5-Port Gigabit Network Switch
 6-Port Gigabit Network Switch
 9 Port Gigabit Network Switch
 10-Port Gigabit Network Switch

 (4 ports PoE, 1 port Uplink)
 (4 ports PoE, 1 port Uplink)
 (4 ports PoE, 2 ports uplink)
 (8 ports PoE, 2 ports uplink)
 (8 ports PoE, 2 ports uplink)

P24526G 26 Port Gigabit Network Switch (24 ports PoE, 2xSFP Uplink)

-----

P32S36GM

Speco BLUE

88 100

(1)

36 Port Managed Gigabit Network Switch (32 ports PoE, 4xSFP Uplink)

# **RECORDERS | 4MP DVRS**

VN Series - HD-TVI NDAA Compliant DVR

D4VN 4 Channel Digital Video Recorder D8VN 8 Channel Digital Video Recorder D16VN 16 Channel Digital Video Recorder

CONFIGURATIONS			
D4VN2TB	D8VN2TB	D16VN2TB	
D4VN4TB	D8VN4TB	D16VN4TB	
D4VN6TB	D8VN6TB	D16VN6TB	
D4VN8TB	D8VN8TB	D16VN8TB	
D4VN10TB	D8VN10TB	D16VN10TB	

### EZ Wizards: For ease of use and setup

- · Camera: quickly discover and install all Speco IP cameras
- Setup: for quick setup of general settings
- Network: network setup and port forwarding

• Record: quickly setup recording resolutions and recording type EZ Search: quickly search events from thumbnails

EZ Copy: copy what you are playing onto a USB flash drive

- 4MP max recording resolution @ 10fps
- UTC function allows for zoom/focus and OSD control over coax
- Signal distance up to 1600ft.
- H.265/H.264 compression supported
- Digital Deterrent<sup>®</sup> for triggering during sensor or motion detection
- 1 HDMI out and VGA monitor output

**Power Supply Voltage** 

Power

**Viewing Clients** 

12VDC 3A

- 2-way audio communication
- 4 channel audio recording



- · Smart (Museum) Search Quickly search for a specific video event without the need for motion setup
- Free US-based DDNS and P2P services
- Remote viewing via web browser, your Apple TV, Amazon Fire TV, or your mobile device
- Built-in S.M.A.R.T. Technology (Self-Monitoring,
- Analysis and Reporting Technology for HDD)
- Password to secure installation authorization
- Easy firmware upgrade by USB port
- Remote control and mouse included
- 5 year limited warranty\*
- TAA Compliant
- NDAA Compliant\*\*
- \*Excludes HDDs

\*\*Products are in compliance with NDAA Section 889 Part B Guidelines



SecureGuard® Client, Apple TV, Amazon Fire TV, Internet Explorer

**Optional Accessories** 



ERS1V Vented Rack Shelf



YOUR LOGO

# ZIPKITS | 5MP KITS

# ZIPK4N1/ZIPK8N2

NDAA Compliant Economical Surveillance Kit

ZIPK4N1 4 Channel Network Video Recorder with 4 Built-in PoE Ports, Four 5MP IP Cameras ZIKP8N2 8 Channel Network Video Recorder with 8 Built-in PoE Ports, Six 5MP IP Cameras

### RECORDER FEATURES: N4JLN/N8JLN

EZ Wizards: For ease of use and setup

Record: quickly setup recording resolutions and recording type

EZ Copy: copy what you are playing onto a USB flash drive

EZ App Setup: just scan a QR code with the app to view your

cameras on your mobile device

- Up to 8MP resolution for live view, recording, and playback
- Plug & Play get video automatically via the PoE ports without any setup
- Supports streams up to H.265 for reduced bandwidth and reduced hard drive space requirements
- QR code based network setup for easy remote access
- 4K monitor output
- Gigabit Ethernet port
- Free US-based DDNS and P2P services
- Built-in S.M.A.R.T. Technology (Self-Monitoring, Analysis and Reporting Technology for HDD)
- Remote monitoring via PC, Mac, and mobile apps
- 1TB/2TB storage
- Expansion available for up to 8 cameras
- Analytics available with optional O8K1A\* camera
  - Facial Recognition
  - Human DetectionVehicle Detection
- 2 year warranty
- NDAA Compliant\*\*

\*\*Products are in compliance with NDAA Section 889 Part B Guidelines

### CAMERA FEATURES: 05K2

(works only with this kit)

- Captures up to 5MP
- 2.8mm wide angle lens
- H.265/H.264 compression supported
- True Day/Night operation (IR cut filter)
- IR range: up to 100' (depending on scene reflection)
- IP66 Weather Resistance

### WHAT'S IN THE BOX:

- NVR with 1TB/2TB hard drive
- Four/Six 5MP cameras
- Four/Six 60' Ethernet cables
- One 3' Ethernet cable
- Remote control (batteries included)

IP

uger JLN

- USB optical mouse
- 48V Power adapter
- HDMI cable



MODEL		EL	ZIPK4N1	ZIPK8N2	
CHANNELS		ELS	4	8	
Monitor Output		Output	HDMI and VGA (Max. Full HD)		
		Resolutions	VGA: 1024 x 768, 1280 x 720, 1280 x 1024, 1440 x 900, 1920 x 1080 HDMI: 1024 x 768, 1280 x 720, 1280 x 1024, 1440 x 900, 1920 x 1080, 2560 x 1440, 3840 x 2160/EDID		
Resolution		on	8MP		
Recording	Compres	sion	H.264 / H.265		
	Recordin	ng Mode	Continuous, motion		
Storage	USB Front Rear	Front	USB x 1		
		Rear	USB x 1		
Bandwidth		th	128Mbps		
Network	PoE		4 ports (802.3af PoE)	8 ports (802.3af PoE)	
Ethernet			RJ - 45 (100/1000M) Port		
Power Power Supply Voltage		upply Voltage	12VDC 3A		
Viewing Clients			Speco Gray Viewer, Apple TV, Amazon F	Fire TV, Speco Gray iOS, Speco Gray Android	

**Optional Accessories** 



O5KJBD Junction Box

### O5KWMT Wall Mount

H.265

IR

5MP

# ZIPKITS | 2MP KITS

# ZIPK8WN2

NDAA Compliant Wireless Surveillance Kit

### ZIPK8WN2 8 Channel Wireless Network Video Recorder, Six 2MP Wireless IP Cameras

### RECORDER FEATURES: N8JWN

- EZ Wizards: For ease of use and setup
- Record: quickly setup recording resolutions and recording type
- EZ Search: quickly search events from thumbnails
- EZ Copy: copy what you are playing onto a USB flash drive
- **EZ App Setup:** just scan a QR code with the app to view your cameras on your mobile device
- Up to 2MP resolution for live view, recording, and playback
- H.265 compression supported
- QR code based network setup for easy remote access
- Free US-based DDNS and P2P services
- Built-in S.M.A.R.T. Technology (Self-Monitoring, Analysis and Reporting Technology for HDD)
- 1 front and rear USB ports for mouse and exporting files
- HDMI output
- Motion Detection with notification alerts
- LAN port to connect to your network
- Remote monitoring via PC, Mac, and mobile apps
- 2TB storage
- 5 year warranty
- NDAA Compliant\*\*

\*\*Products are in compliance with NDAA Section 889 Part B Guidelines

### CAMERA FEATURES: O2WK1N (works only with this kit)

- (works only when this k
- Captures up to 2MP3.6mm wide angle lens
- 3.6mm wide angle lens
- True Day/Night operation (IR cut filter)
  IR range: up to 65' (depending on scene reflection)
- PIR function with white LED deterrent
- Digital WDR
- 12VDC operation
- IP66 Weather Resistance

### WHAT'S IN THE BOX:

- NVR with 2TB hard drive
- Six 2MP wireless cameras
- Six 45' DC power extension cables
- One 3' Ethernet cable
- Remote control (batteries included)
- HDMI cable



MODEL		ZIPK8WN2	
CHANNELS		6 Wireless	
Monitor Output		HDMI and VGA (Max. Full HD)	
Video	Display Resolutions	1 VGA / 1 HDMI (1024x768, 1280x1024, 1280x720, 1440x900, 1920x1080, 2560x1440, 3840x2160)/ EDID (monitor resolution auto detection)	
Audio	Simultaneous Output	HDMI and VGA	
Audio	Audio Out	No	
	Resolution	2MP (1080p)	
	Compression	H.265	
Recording	Frame Rate	Max. 60fps@1080p Main Stream: 1-15fps@1080p per channel Sub Stream: 1-15fps@640*360 per channel	
	Recording Mode	Manual, schedule (continuous/event), event (pre/post)	
	Live Stream	Max. 2MP @ 15fps (Auto fps, Auto bitrate)	
Storage USB USB USB 2.0 x 2 ports (for mouse and backup/u		USB 2.0 x 2 ports (for mouse and backup/upgrade)	
Network	Bandwidth	Up to 12Mbps	
Network	Ethernet	1 RJ - 45 10/100 Base-T	
Viewing Clie	ents	SecureGuard® Client, Speco Gray Viewer, Apple TV, Amazon Fire TV, Speco Gray iOS, Speco Gray Android, Internet Explorer	



# SecureGuard®

### SecureGuard® VMS

Comes pre-loaded on our SecureGuard Servers  $\mathfrak{S}$ **Real-Time Health Status** E E 2-Way Audio ۵ Integrated with Speco Access ۵ EZ Search F Schedule Recordings  $\triangleleft$ E-mail notifications on Event and Status E-mapping Î

# SecureGuard<sup>®</sup> CMS

৶	Download for FREE!
ļ	Lightweight in network and computer resources
A Contraction	P2P support
R	Bulk Network and Password Updates*
Ø	Add unlimited number of sites

# SecureGuard<sup>®</sup> CMS



### **Features Of SecureGuard CMS**

- Connect to all Speco devices including DVRs, NVRs, Hybrid Recorders, IP Cameras, SecureGuard Servers, and ONVIF Cameras\*
- Add an unlimited number of sites and view up to 36 channels in a 6x6 channel grid
- Create unlimited customized layouts
- Create unlimited customized sequences
- Break down and preview an entire day's worth of footage down to the minute with EZ Search 2.0
- Manually adjust channel streams to accommodate bandwidth and/or PC performance



- Control PTZ Cameras and create PTZ tours
- Include a watermark in exported footage to ensure it has not been tampered with
- Configure recorders and IP cameras through the software\*\*
- Back up configuration to import to another CMS installation for quick setup times

\*Requires license provided by Speco \*\* Some configurations will require logging into the recorder locally or via web browser

# **SecureGuard**<sup>®</sup>

### SecureGuard<sup>®</sup> Bridge

(available for Windows & Mac)



### THE ULIMATE IN CLOUD **VIDEO STORAGE**

All the features of SecureGuard VMS in compact device. Archive any Speco DVR, NVR, Hybrid channel to the cloud!

### Be ANYWHERE at ANYTIME. SecureGuard<sup>®</sup> Apps

### SecureGuard® Client



### SECUREGUARD® CLIENT APP

SecureGuard® Client App is a companion viewing app that allows you to connect and view sites from your SecureGuard® installation on the go. Download the app on your Android<sup>™</sup> and iPhone<sup>®</sup> devices FREE.

- Add multiple SecureGuard<sup>®</sup> Server or Speco recorder, IP camera installations using an IP address or DDNS
- Connect using your SecureGuard<sup>®</sup> login ID
- Create an unlimited number of custom layouts consisting of different sites and specific channels
- View your sites along with the ability perform 2-way audio
- Includes a help section with FAQ and contact information for our tech support team
- P2P capability





### SecureGuard<sup>®</sup> Client for Apple TV & Amazon Fire TV

We created SecureGuard® client apps for Apple TV and Amazon Fire TV. These home entertainment devices allow you to view your security cameras then resume your favorite shows with ease. Use these devices also as a quick and easy spot monitors solution for smaller sites and forgo complicated wirings.



Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Amazon's trademark is used under license from Amazon.com, Inc. or its affiliates.

### SecureGuard<sup>®</sup> Servers TAA NDAA

Become a Surveillance Powerhouse.

We've simplified the surveillance management process by pre-loading our dynamic VMS on all SecureGuard® Servers, which means easy setup, reliability, and complete security.

- With SecureGuard<sup>®</sup> VMS, multiple users can view and playback video from the server and the sites from anywhere in the world
- · Fully scalable to meet the growing demands of your business' surveillance needs
- Free software updates will keep you up-to-date with Speco's latest technological advancements and will keep your system performing optimally at NO ADDITIONAL COST

Products are in compliance with NDAA Section 889 Part B Guidelines



MODEL	SG319	SG519
Number of Cameras	62 4MP cameras	125 4MP cameras
	for SG319*	for SG519*
Operating System	Windows 10 Enterprise	Windows 10 Enterprise
CPU	Intel <sup>®</sup> Xeon	Intel <sup>®</sup> Xeon
Memory	16GB	16GB
Number of Storage Bays	8	24 (4U)
Maximum Raw Storage	Up to 128TB	Up to 384TB (4U)
RAID Levels	Yes (RAID 5, 6)	Yes (RAID 5, 6)
<b>RAID Cache Protection</b>	Yes	Yes
Hot Swappable	Yes (RAID 5, 6)	Yes (RAID 5, 6)
Network Ports	Dual Gigabit	Dual Gigabit
Max. Throughput	360 Mbps	600 Mbps
Redundant Power	Yes	Yes
Supply		
Warranty	3 year (NBD Onsite Repair)	3 year (NBD Onsite Repair)

### SecureGuard<sup>®</sup> Branding



Custom | Have your company logo visible Branding in our software at NO COST!

Speco will display your logo in the following areas:

- All desktop icons
- Configurator tool splash screen
- On the client-side toolbar
- Across all background grids
- Throughout the SecureGuard® Player
- As a watermark on exported videos

For more information about SecureGuard® Branding service, email sales@specotech.com or call 1.800.645.5516

### SecureGuard<sup>®</sup> Design Service

We design your surveillance system!

Don't stress over what surveillance system you need! SecureGuard® experts will help design a custom surveillance solution from the ground up with SecureGuard® at NO ADDITIONAL COST! Let our professionals select cameras and technologies that will best fit your needs or design a system that supports your existing surveillance system.



# SECUREGUARD<sup>®</sup> | SGBRIDGE

# SecureGuard® Bridge

SGBRIDGE Backup IP Camera & Recorder Video in the Cloud SGBRIDGE1 Backup IP Camera & Recorder Video in the Cloud with 1TB storage

The SecureGuard<sup>®</sup> Bridge is a compact, quiet solution for backing up recordings to the cloud. It affords the user the ability to store multiple channels worth of recordings in a safe location as a backup to the typical hard drive-only storage solution. It also allows for remote viewing and playback of video via SecureGuard<sup>®</sup> Client for desktops and mobile devices.

- Free software updates
- Compatible with Speco's DVRs, NVRs, and IP cameras
- Linux based platform
- Stay connected from anywhere in the world with Speco's Free DDNS service
- Secure your camera network with Dual Gigabit NICs
- Multi-client access available with our easy-to-use free client software, SecureGuard® Client
- Store on a surface or mount to wall with VESA pattern
- View live video on the SecureGuard® VMS Client and SecureGuard® CMS for PC and Mac and SecureGuard® Client app for iOS and Android
- View cloud-stored video on SecureGuard® VMS Client for PC & Mac
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines





	MODEL	SGBRIDGE	SGBRIDGE1	
Supported Resolutions		Up to 8MP (4K)		
System	Max. Cameras Supported	Up to 32 (depending on camera model)		
	Operating System	Linux		
	Operating System Drive Size	128GB SSD		
	СРИ	Intel® Celeron		
	Memory	8GB		
	Available Embedded Storage	80GB		
	Additional Storage	N/A	875GB	
Storage	Video Buffer	Up to 6 cameras @ 1MP for 1 day on-premises Up to 4 cameras @ 2MP for 1 day on-premises Up to 3 cameras @ 4MP for 1 day on-premises Up to 2 cameras @ 5MP for 1 day on-premises Up to 1 cameras @ 8MP for 1 day on-premises	Up to 32 cameras @ 1MP for 1 day on-premises Up to 32 cameras @ 2MP for 1 day on-premises Up to 32 cameras @ 4MP for 1 day on-premises Up to 25 cameras @ 5MP for 1 day on-premises Up to 18 cameras @ 8MP for 1 day on-premises	
	Cloud Backup	Yes		
Network	NIC	2 x Gigabit Ethernet		
	USB	USB 2.0 x 2, USB 3.0 x 2		
I/O Ports	Serial Port	2		
	Video Out	HDMI x 1, VGA x 1		
Dimensions 5.35" (L) x 5.05" (W) x 1.55" (H)				
	Weight	1.5 lbs		
Physical	Operating Temperature	32° - 104°F		
	Non-operating Temperature	-4° - 140°F		
	<b>Operating Relative Humidity</b>	90% @ 104°F (non-condensing)		
	Input Voltage	100 - 240 VAC		
	Adapter Type	12VDC 2A		



# Secure Guard® DASHBOARD Goud Based Remote Management Platform



The Central Dashboard connects you to an unlimited number of customer sites for real-time management and communication.



### Health Care

Conveniently view the health status of your systems remotely for all installs setup with SecureGuard® Dashboard.

+ Installer

- Store

New Yor

+ <u>Massachusetts</u>

Recorder 1



### Configurations

Configure hardware and analytics remotely.



### **Recurring Monthly Revenue**

Increase your monthly revenue by charging to remotely manage and maintain each location without the need to roll a truck.



### **QR Code Connections**

Utilize encrypted, QR Code-based network connections via Mobile App for field Installations.



### **Remote Passwords**

Change the passwords for all users remotely without having to leave the SecureGuard® Dashboard. Change the password of a user for a single site, or multiple site deployment with ease.

the same states and the

# SPECO ACCESS BROWSER BASED ACCESS CONTROL

# THE BENEFITS





**OUT-OF-THE-BOX READY:** Embedded Linux OS



**BROWSER-MANAGED INTERFACE:** No software or server to install - use your favorite browser on PC or Mac. Works with Internet Explorer, FireFox, Google Chrome, Safari, & more.



**HIGHER PROFITS:** Generate recurring monthly revenue by offering value-added services



**FULLY SCALABLE:** Hardware and software are fully scalable up to 128 doors



**MOBILE APP & REMOTE MANAGEMENT:** Speco Access Mobile App offers key administrative tools on the go while the remote management console gives the benefit of full edge control from anywhere.



VIDEO INTEGRATION:

Fully integrated with our NR & HR Series recorders.



### FITS MORE INSTALLATIONS:

No software required. Lower cost of installation, setup, and support.

Speco Access is a browser and mobile app managed access control system that is fully scalable. It offers many value-added benefits including eliminating on site tech calls with the Remote Management Console. This allows for all the benefits of edge management from anywhere. It is also integrated with our NR and HR Series recorders, which adds live video viewing and event video tagging on both the browser and mobile app. The dedicated mobile app also gives users the ability to lock and unlock doors, manage users and their credentials, and lock down the system by changing the threat level.

# SPECO ACCESS | CONTROLLERS & READERS

ACS

ACS

NDAA

NDAA COMPLIAN

# **A1**

### **Single Door Controller**

- Out of the box ready browser managed
- Embedded Linux operating system
- 1 Reader In
- 1 Reader Out
- 2 Relays (Lock/Aux)
- 3 Inputs (REX, DPS, Aux) Global
- Scalable to 128 doors when used with A2E4/A2E4P
- UL listed 294 Series 7
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



(5)

c(UL)us

**Optional Accessories** 



# A2E4/A2E4P

2 door controller, expandable up to 4 doors, basic power/power package

### **Two Door Controller**

- Out of the box ready
- Embedded Linux operating system
- Expandable up to 4 doors
- (when used with A2M board)
- 2 Readers In
- 2 Readers Out
- 4 Relays (Lock/Aux)
- 6 Inputs (REX, DPS, Aux) Global
- Scalable to 128 doors
- UL listed 294 Series 7
- 12V/24V selectable lock power (A2E4P)
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



### **Expansion Board**

- Expands A2E4/A2E4P up to 4 doors
- 2 Readers In
- 2 Readers Out
- 4 Relays (Lock/Aux)
- 6 Inputs (REX, DPS, Aux) Global
- UL listed 294 Series 7
- 5 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



(5)

### **Optional Accessories**



A2M Expansior Board

# **AP300HA**

### **Mullion Proximity Reader**

- Up to 5 in of read range
- Contactless Digital Radio Frequency Identification (RFID) technology
- Compliant with the Wiegand communication protocol
- Tamper resistant
- IP67 Weather Resistance
- UL listed
- Lifetime warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

### **Compatible Credentials** APSM2, APSC1, APSI4, APDT1, APSK3, AWRT4

# **AP500HA**

### **Proximity Reader**

- Up to 8 in of read range
- Contactless Digital Radio Frequency Identification (RFID) technology
- Compliant with the Wiegand communication protocol
- Tamper resistant
- IP67 Weather Resistance
- UL listed
- Lifetime warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

**Compatible Credentials** APSM2, APSC1, APSI4, APDT1, APSK3, AWRT4

# **AP620HA**

### **Mullion Proximity Reader & Keypad**

- Up to 5 in of read range
- Contactless Digital Radio Frequency Identification (RFID) technology
- Compliant with the Wiegand communication protocol
- Tamper resistant
- IP67 Weather Resistance
- UL listed
- Lifetime warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

**Compatible Credentials** APSM2, APSC1, APSI4, APDT1, APSK3, AWRT4



cUL)us

LIFE TIM



ACS













# SPECO ACCESS | READERS

# **AP640HA**

### **Proximity Reader & Keypad**

- Up to 7 in of read range
- Contactless Digital Radio Frequency Identification (RFID) technology
- Compliant with the Wiegand communication protocol
- Tamper resistant
- IP67 Weather Resistance
- UL listed
- Lifetime warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

**Compatible Credentials** APSM2, APSC1, APSI4, APDT1, APSK3, AWRT4

# ACSR35L

### **Contactless Smartcard Reader**

- Up to 1.5 in of read range (physical)
- Up to 15 feet of read range (mobile)
- Contactless smartcard reader solution with mobile access support
- Digital Radio Frequency Identification (RFID) platform
- Supports both sector and card serial number (CSN) reads
- · Offers the option of mobile access credentials loaded on Bluetooth Low Energy (BLE) enabled smartphones or contactless smartcard module
- Tamper resistant
- IP67 Weather Resistance
- Lifetime warranty NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines



### **Smartcard Reader & Keypad**

- Up to 2 in of read range (physical)
- Up to 15 feet of read range (mobile)
- Keypad with contactless smartcard and mobile credential access support
- Digital Radio Frequency Identification (RFID) platform
- Supports both sector and card serial number (CSN) reads
- Offers the option of mobile access credentials loaded on Bluetooth Low Energy (BLE) enabled smartphones or contactless smartcard module
- Tamper resistant
- IP67 Weather Resistance
- Lifetime warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines





# APCR35L

### **Contactless Proximity Reader**

- Up to 4 in of read range (physical)
- Up to 15 feet of read range (mobile) Contactless smartcard reader solution
- with mobile access support Digital Radio Frequency
- Identification (RFID) platform Supports both sector and card
- serial number (CSN) reads
- Offers the option of mobile access credentials loaded on Bluetooth Low Energy (BLE) enabled smartphones or contactless proximity module
- Tamper resistant
- IP67 Weather Resistance
- Lifetime warranty
- NDAA Compliant\*
- \*Products are in compliance with NDAA Section 889 Part B Guidelines

### ACSR62L IP67

### **Mullion Smartcard Reader & Keypad**

- Up to 2 in of read range (physical)
- Up to 15 feet of read range (mobile)
- Keypad with contactless smartcard and mobile credential access support
- Digital Radio Frequency Identification (RFID) platform
- · Supports both sector and card serial number (CSN) reads
- Offers the option of mobile access credentials loaded on Bluetooth Low Energy (BLE) enabled smartphones or contactless smartcard module
- Tamper resistant
- IP67 Weather Resistance

• Up to 200 feet of read range

the transmitters to function

• IP65 Weather Resistance

• III listed

1 year warranty

NDAA Compliant\*

Ultra high frequency (UHF) technology

• Receiver range covers a 360-degree radius and

does not need to be installed in line-of-sight for

\*Products are in compliance with NDAA Section 889 Part B Guidelines

- Lifetime warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

# **AWRR44** Long Range Receiver





**Compatible Credentials** AWRT4



Shown in Switch Plate

### **Compatible Credentials**

APSM2, APSC1, APSI4, APDT1, APSK3, ACMC2, AWRT4

NDAA

ACS

Shown in Switch Plate

**Compatible Credentials** ACSM2P, ACSC2,



ACS





. 123



**Compatible Credentials** 

ACSM2P, ACSC2,

ACSK2, ACMC2





**Compatible Credentials** 

ACSM2P. ACSC2.

ACSK2, ACMC2

# SPECO ACCESS | CREDENTIALS

# **APDT1**

### **Proximity Disc Tag**

- Up to 3.5 in contactless read range Contactless Digital Radio Frequency Identification (RFID) technology
- Frequency 125kHz
- Pack quantity: 25 cards
- Lifetime warranty
- NDAA Compliant\*

Use with

\*Products are in compliance with NDAA Section 889 Part B Guidelines

AP300HA, AP500HA, AP620HA,



Shown in use



### **Proximity Card**

- Up to 7in contactless read range
- Contactless Digital Radio Frequency
- Identification (RFID) technology • Frequency 125kHz
- Pack quantity: 25 cards
- Lifetime warranty
- NDAA Compliant\*

Products are in compliance with NDAA Section 889 Part B Guidelines

### Use with

ΑΡ300ΗΑ, ΑΡ500ΗΑ, ΑΡ620ΗΑ, AP640HA, APCR35L

# **APSK3**

AP640HA, APCR35L

### **Proximity Key Ring Tag**

- Up to 3.5 in contactless read range
- Digital Radio Frequency Identification (RFID) technology
- Frequency 125kHz
- Pack quantity: 25 tags
- Lifetime warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

Use with

AP300HA, AP500HA, AP620HA, AP640HA, APCR35L

# APSC1

### **Clamshell Proximity Card**

- Up to 8in contactless read range
- Contactless Digital Radio Frequency Identification (RFID) technology
- Frequency 125kHz
- Pack quantity: 25 cards
- Lifetime warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

Use with АРЗООНА, АР5ООНА, АР62ОНА, AP640HA, APCR35L



# ACS APSM2 NDAA

### **Proximity Credential**

- Up to 7in read range
- Digital Radio Frequency
- Identification (RFID) technology
- Frequency 125kHz
- Pack quantity: 25 cards
- 1 vear warrantv
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

### Use with

ACS

AP300HA, AP500HA, AP620HA, AP640HA, APCR35L

# ACMC2

### **Mobile Credential for Bluetooth Reader**

- Up to 15ft read range
- Supports both presentation and longer-range options
- Bluetooth Low Energy: operates with mobile ready readers • High Security Encryption Technology: protected
- behind the smartphone's security parameters Respect for Privacy: easy one-time registration
- without disclosure of private information Pack quantity: 25 codes
- NDAA Compliant\*
- Products are in compliance with NDAA Section 889 Part B Guidelines

### Use with

ACSR35L, ACSR62L, ACSR64L, APCR35L



ACS

ACS





NDA

ACS







# **SPECO ACCESS | CREDENTIALS & KITS**

ACS

ACS

NDAA

# ACSM2P

### **Imageable Smartcard Credential**

- Up to 2.25in read range
- Frequency 13.56MHz
- High-Security Encryption Technology
- Pack quantity: 25 cards
- 1 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

Use with ACSR35L, ACSR62L, ACSR64L

# ACSK3

### **Smartcard Key Fob**

- Up to 1in read range
- High-Security Encryption Technology
- Frequency 13.56MHz
- Fraudulent Data Detection Solution
- Pack quantity: 25 cards
- 1 year warranty
- NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

Use with

ACSR35L, ACSR62L, ACSR64L

# A1PS

### **Single Door Access Controller** and Power Supply

Products Included:

(1) A1 Single Door Controller

ACKIT1S

(1) PSDC24 12VDC 2A Wall Plug Power Supply (1) DCPLGBLOKM1 (DC Plug to Terminal Block)

**4 Door Access Control System** 





### **Clamshell Smartcard Credential**

- Up to 2.25in read range
- High-Security Encryption Technology
- Frequency 13.56MHz
- Fraudulent Data Detection Solution
- Pack quantity: 25 cards
- Lifetime warranty
- NDAA Compliant\*

Products are in compliance with NDAA Section 889 Part B Guidelines

Use with

ACSR35L, ACSR62L, ACSR64L

# AWRT4

### Long Range Transmitters

- Up to 200ft button press read range; Up to 3.5in presentation read range
- Proven Digital Ultra High Frequency (UHF) technology
- IP65 compliant, weather resistant
- UL listed Standard 294
- Pack quantity: 5 transmitters
- 1 year warranty
- NDAA Compliant<sup>\*</sup>
- \*Products are in compliance with NDAA Section 889 Part B Guidelines

### Use with

<u>АРЗООНА, АР500НА, АР620НА,</u> AP640HA, APCR35L, AWRR44

# ACKIT1/ACKIT1B

### 4 Door Access Control System

ACKIT1 Products Included: (1) A2E4P (1) A2M (4) AP300HA (1) APSC1 (pack of 25) (1) AP4 (License)

ACKIT1B Products Included: (1) A2E4 (1) A2M (4) AP300HA (1) APSC1 (pack of 25)

(1) AP4 (License)

### NDAA Compliant\*

Products are in compliance with NDAA Section 889 Part B Guidelines

# ACKIT2DRS

### 2 Door Access Control System

ACKIT2DRS **Products Included:** (1) A2E4P (2) AP300HA (1) APSC1 (pack of 25)













ACS

### **NDAA** ACS





(1) APSC1 (pack of 25)

**NDAA** 

ACS



ACKIT1S

(1) A2E4P

(1) A2M



# **SPECO ACCESS | CREDENTIALS & KITS**

### ACKIT2DR/ACKIT2DRB ACKIT2VID/ACKIT2VIDB ACS NDAA COMPLIANT **4 Door Access Control System** & Video Integrated System

ACKIT2VID Products Included: (1) A2E4P (1) A2M (4) AP300HA (1) APSC1 (pack of 25) (1) AP4 (License) (1) N8NRL2TB (4) **O4D6N** (1) NVR (License)

ACKIT2VIDB **Products Included:** 



# ACKITM2DR

### **2 Door Access Control Kit with Bluetooth Mobile Reader & Credentials**

ACKITM2DR Products Included: (1) A2E4P (2) ACSR35L (1) ACMC2 (1) AP4 (License)

NDAA Compliant\*

Products are in compliance with NDAA Section 889 Part B Guidelines

IP

ACS

**4**K

A

H.265





ACS

ACS



EΖ

**P2P** 

# N8WA4/N8WA4P

### 4K H.265 Advanced Analytics Wall Mount NVR with Integrated 4 Door Access Controller

CONFIGURATIONS				
N8WA42TB	N8WA48TB	N8WA4P2TB	N8WA4P8TB	
N8WA44TB	N8WA412TB	N8WA4P4TB	N8WA4P12TB	
N8WA46TB	N8WA416TB	N8WA4P6TB	N8WA4P16TB	

### WALL MOUNT NVR FEATURES: N8WNRE

- EZ Wizards: For ease of use and setup
- Camera: quickly discover and install all Speco IP cameras
   (1) NVR (License)
- Setup: for guick setup of general settings
- Network: network setup and port forwarding
- · Record: quickly setup recording resolutions and recording type
- EZ Search 2.0: quickly search events from thumbnails
- EZ Copy: copy what you are playing onto a USB flash drive EZ Mobile: easy mobile setup for viewing on desktop or mobile apps
- Real time recording up to 8MP resolution (4K) @ 30fps
- H.265 compression Store up to 2x more than H.264!
- 1 SATA port for up to 16TB storage (N8WNRE)
- 4K HDMI out and VGA monitor output
- Smart Search Specify a region on the camera view and search on changes in that area\*
- Object and line crossing detection and alerts\*
- Facial Recognition and Comparison\*\*
- Free US-based DDNS and P2P services

- N8WA4 **Products Included:** (1) A2E4 (1) A2M (1) P4S5G (1) **N8WNRE** (1) AP36 (License)
  - Remote viewing via web browser, your Apple TV, Amazon Fire TV, or your mobile device
  - Easy video exporting via USB

N8WA4P **Products Included:** 

(1) A2E4P

(1) P4S5G

(1) **N8WNRE** 

(1) AP36 (License)

(1) NVR (License)

(1) A2M

Remote control included

\*with Speco Smart Analytic IP Cameras \*\*with Speco Facial Recognition Cameras

### A2E4/A2E4P & A2M FEATURES:

- Embedded Linux operating system
- 4 Readers (In/Out)
- 8 Relays (Lock/Aux)
- 12 Inputs (REX, DPS, Aux) Global Lock Power - 12V/24V DC
- selectable lock power (A2E4P)



- Gigabit performance on all ports (uplink and downlink)
- CCTV mode isolates each port from one another for added
- security and performance • Includes built-in surge immunity







E .....

ACS NDAA

### ACKIT2DRB Products Included: (1) A2E4 (2) AP300HA (1) APSC1 (pack of 25)

(1) AP4 (License)

(2) AP300HA (1) APSC1 (pack of 25) (1) AP4 (License)

\*Products are in compliance with

NDAA Section 889 Part B Guidelines

**ACKITM1** 

**4 Door Access Control Kit with** 

ACKIT2DR Products Included:

NDAA Compliant\*

(1) A2E4P

ACKITM1

(1) A2E4P

(4) ACSR35L

(1) AP4 (License)

NDAA Compliant\*

\*Products are in compliance with NDAA Section 889 Part B Guidelines

(1) ACMC2

(1) A2M

**Products Included:** 

2 Door Access Control System

# SPECO ACCESS THE ULTIMATE SCREENING SOLUTION

# ARE YOU WHO YOUR CREDENTIALS SAY YOU ARE?

# Speco adds an extra layer of security with 2 Factor Authentication with Facial Recognition



Fully integrated with our NRE series recorders



SEAMLESS VIDEO & MOBILE INTEGRATION WITH SPECO'S NRE SERIES OF RECORDERS



LOCK & UNLOCK DOORS REMOTELY

# WHY SPECO?







# ADVANCED ANALYTIC CAPABILITIES

Cameras and recorders with analytic capabilities, such as: Facial Recognition, License Plate Recognition, Vehicle Detection, Human Detection, Line Crossing, Object Detection, and Smart Search. A great high margin RMR opportunity.

# **DIGITAL DETERRENT®**

Stop the crime before it occurs with Audio and Visual alerts.

# SPECO'S NDAA & TAA COMPLIANT PRODUCTS

Meet the standards for installation in U.S. Government facilities. \*See our website specotech.com for a list of available models.

# **UL-Listed and ETL-listed Products Available!**

We offer solutions certified for safety by Nationally Recognized Testing Laboratories.

# FREE U.S. BASED DDNS SERVICE

Our DDNS and P2P services are free and US-based. No phoning home to China or other countries.

# S.E.A.L. TEAM

Speco's Sales, Engineering, and Leadership team, call us and we can help design the system!

# **FREE TECHNICAL SUPPORT**

Great, Fast, Tech Support - Get your techs in and out quicker.

# **INCLUDED JUNCTION BOXES**

One less thing for the technicians to worry about during the installation! Comes included in the box at no additional cost!

# **5 YEAR WARRANTY**

We are confident in our quality!

# EZ SEARCH 2.0

Search through 24 Hours of Video Events From Thumbnails in Seconds.

# PATENTED "WALL MOUNT" SOLUTION

Perfect for covert applications and where counter space is limited.

# **INCREASE YOUR BRAND AWARENES**

Have your logo on cameras and wall mount recorder doors.

### SPECO IS FULLY STOCKED WITH ALL PRODUCTS!







# Contact us at: **sales@specotech.com** Toll Free: 1.800.645.5516 • Metro NY: 631.957.8700 200 New Highway, Amityville NY 11701 www.specotech.com

# EDITION: V.6 Rev. 11.18.2022

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. We are not responsible for typographical errors. © 2023 Speco Technologies. All rights reserved.