

IP SPEAKERS

15W Ceiling Speaker | [SPIPC6A](#)

15W Ceiling Speaker with Mic Input | [SPIPC6AM](#)

- PoE or 12/24VDC
- Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP
- Compatible with SecureGuard® VMS via ONVIF
- Supports pre-recorded messages, schedules, and alarm trigger using SecureGuard® software
- Two-way audio support with mic input (SPIPC6AM Only)



15W Horn Speaker | [SPIPH8A](#)

15W Horn Speaker with Mic Input | [SPIPH8AM](#)

30W Horn Speaker with Mic Input | [SPIPH9AM](#)

- PoE or 12/24VDC
- Compatible with VoIP, SIP devices (IPPBX, IP Phone) via SIP
- IP67 waterproof design is ideal for outdoor installations
- Compatible with SecureGuard® VMS via ONVIF
- Supports pre-recorded messages, schedules, and alarm trigger using SecureGuard® software
- Two-way audio support with mic input (SPIPH8AM & SPIPH9AM only)



6.5" Modern Grille In-Ceiling Speaker | [SPIPG66T](#)

8" Modern Grille In-Ceiling Speaker | [SPIPG86T](#)

8" Classic Grille In-Ceiling Speaker | [SPIPG86TG](#)

- PoE or 12/24VDC
- Works with Speco Audio Manager Software
- Compatible with SecureGuard® VMS via ONVIF
- Supports pre-recorded messages, schedules, and alarm trigger
- Two-way audio support with mic input
- Dog-ear mounting clamps for secure installation (SPIPG66T & SPIPG86T only)



MIXER AMPLIFIERS

60W/120W/240W PA Amplifier with Tuner [PBM60AT/PBM120AT/PBM240AT](#)

60W/120W/240W PA Amplifier [PBM60A/PBM120A/PBM240A](#)

60W/120W/240W PA Amplifier with Tuner, CD, USB, SD Player [PBM60AU/PBM120AU/PBM240AU](#)

- 6 Source inputs (3 AUX + 3 MIC)
- One amplifier design, nine models
- 70V (240W model) and 70V/25V (60W/120W)
- RS232 connection to integrate with control systems
- Includes rack mount accessories
- Includes IR remote control
- Telephone paging input and music on hold output



30W Mixer Amplifier | [PBM30](#)

- Compact paging amplifier
- 4/8/16 Ohms and 70/25V output
- 3 inputs (2 MIC + 1 AUX)
- Telephone paging input and music on hold output



ACCESSORIES

Desktop Paging Microphone | [MHL5S](#)

- Momentary switch for priority paging and lock down for continuous use
- Dual Impedance



Goose Neck Microphone | [MGS1/MGS1C](#)

- Uni-directional
- Impedance: 500 Ohms
- With push-to-talk switch
- Chrome (MGS1C)



UHF 700 Frequency-Selectable Single Channel True Diversity PLL Receiver | [MUHF101](#)

UHF 700 Frequency-Selectable Handheld Microphone | [MUHFHH](#)

UHF 700 Frequency Selectable Lapel Microphone | [MUHFLLP](#)

- Up to 700 selectable pre-programmed frequencies
- Clear, interference-free channels of communication for roaming distances in excess of 150 ft.
- Use one MUHF101 with either MUHFHH or MUHFLLP (sold separately)



10W/50W 70/25V silver/black or white/white decora wall-mount Volume Control [WAT10/WAT50/WAT10DW/WAT50DW](#)

- Standard single-gang wall-plate style
- 11-step attenuation
- Total attenuation at 33dB



100W 70/25V Slider Volume Control with Swappable Décora Plates | [WAT100D](#)

- 3 Décora plate, insert and knob color options included in package: Ivory, Almond, and White
- 12-position soft-touch slider switch
- Total attenuation at 33dB



MATRIX AMPLIFIER

5x4 160W Mixer Amplifier | [PL200M](#)

- Play up to 5 sources into any combination of 4 zones
- 4 zone outputs @40W per zone; total of 160W
- 5 inputs (3 combo + 2 AUX)
- Combo inputs can be mic level or line level and accept 1/4 in. or XLR
- All controls from front panel



COMMERCIAL CEILING SPEAKERS

5.25" MA Series Speakers-30 Watt RMS, 60 Watt Max

6.25" MA Series Speakers-40 Watt RMS, 80 Watt Max

SP5MAT/SP6MAT

- Also available in all-black (SP5MATB/SP6MATB)
- Optional ceiling tile mounting brackets available
- Easy Select transformer dial with 70V or 25V selector switch



6.5" UL listed Nexus Series Speaker

SP6NXCTUL

- Metal backcan
- Sold in pairs
- Includes ceiling tile mounting brackets
- UL1480 and UL2043
- Also available in 5.25" (SP5NXCTUL)



10 Watt RMS, 15 Watt Max 8" 86 Series Speaker - Classic Grille| G86TG

- Classic style white steel grille
- 70V/25V transformer with colored leads
- Optional backcan (STH8) and ceiling tile bracket (TS8) available



10 Watt RMS, 15 Watt Max 8" 86 Series Speaker - Modern Grille| SPG86T

- Modern mesh steel grille
- 70V/25V transformer with colored leads
- Also available in 6" or 6" with volume control knob (SPG66T/SPG66TC)
- Optional ceiling tile bracket (BRC8) available



30 Watt RMS, 60 Watt Max 5" Pendant Speakers SP30PTB/SP30PTW

- Easy Select transformer dial with 70V or 25V selector switch
- Compact, aesthetically pleasing design
- Includes 11.25" hanging apparatus



32 Watt RMS, 64 Watt Max 6" Contractor Elite Pendant Speakers | SP6PTB/SP6PTW

- Easy Select transformer dial with 70V or 25V selector switch
- Includes eye-bolt for connection to hanging chain/wire
- Optional mounting kit available for pendant or ground mounting (SP6PMNTB or SP6PMNT)



40 Watt RMS, 80 Watt Max 6.25" MA Series In- Wall Speakers | SP6MAWT

- Easy Select transformer dial with 70V or 25V selector switch
- ABS backcan



30 Watt RMS, 60 Watt Max 6.5" 70/25V Outdoor Rock Speakers with transformers SPRK65CBT/SPRK65CGT

- Weather resistant
- Realistic rock design to bring sound seamlessly into a commercial outdoor environment
- Available in brown (B) or gray (G)



COMMERCIAL OUTDOOR SPEAKERS

60 Watt RMS, 120 Watt Max Black & White 6.5" Contractor Elite Wall-Mount Speakers

SPCE60TB/SPCE60TW

- Sold in pairs
- Ideal for indoor or outdoor applications
- 70V transformer with easy select dial
- IP66 compliant and constructed from weather resistant materials
- Also available in 5" versions (SPCE50TB/SPCE50TW) and 8" versions (SPCE80TB/SPCE80TW)



15 Watt RMS, 25 Watt Max 4" 3-Way Wall-Mount Speakers DMS3TS/DMS3TSW

- Ideal for indoor or outdoor applications
- 4" woofer, 2" midrange, 1" tweeter
- 70V/25V transformer with easy select dial



PAGING HORNS

10 Watt RMS, 15 Watt Max 6" Weather-Resistant Horn | SPC10

- Rubber bell protector
- Aluminum construction
- 8 Ohms Impedance
- Includes mounting bracket



15 Watt RMS, 25 Watt Max 8.5" Weather-Resistant Horn | SPC15T

- Aluminum construction
- Easy Select transformer dial with 70V or 25V selector switch
- Also available in 6.5" (SPC10T) and 10.5" (SPC30T) models
- Rubber bell protector



40 Watt RMS, 75 Watt Max 11" x 8" Weather-Resistant Horn | SPC30RT

- ABS construction
- Easy Select transformer dial with 70V or 25V selector switch
- Also available in 7"x 5" (SPC10RT) and 8" x 6" (SPC15RT) models

