



Outdoor Digital Deterrent® Alert Box with Built-in Strobe and Audio/Voice Warning

DD4

white housing

Features

- 120W integrated control module for full box operation, supporting up to 240W maximum power capacity
- DC12V/10A and DC24V/5A power inputs for solar panel and power adaptor
- 9-CH DC12v outputs and 1-CH DC24V output and 1-CH DC48V output plus 3xalarm in & out and RJ45
- Built-in siren(120db)
- External red & blue light strips (up to 18W, aluminum material, IP67 rating and angle adjustable)
- Built-in thermostat fan for cooling and also heat sink foil inside box
- 4 X IP cameras installation with NPT 3/4" screw set of camera plate support 6x cameras max
- Convenient hand carrier design
- Built-in din-rail and universal panels for flexible installation
- 4-CH NVR (N4NRM2TB) and 4G Router included
- IP Speaker Horn with built-in mic (SPIPH8AM) included

Power Control Module

Inputs	1x DC12V, 1x DC24V
	1x RJ45, 3x Alarm
Outputs	9x DC12V, 1xDC24V, 1xDC48V,
	3x Alarm, 1x RJ45

Fan

Mounting	Pole (4 clamps included) and wall mount
Box Dimension	39cm (width) x 54cm (height) x 20cm (depth)

N4NRM2TB Specifications

Network	Network Bandwidth	80Mbps
	P2P/Dynamic DNS	Free US-Based Speco P2P and DDNS service
	Network Protocols	TCP/IP, PPPoE, DHCP, DNS, UPnP, NTP, SMTP
Network Access	Mobile	iOS®/Android™ via Speco Blue App, SecureGuard® Client
	Web Viewer	Google Chrome®, Microsoft Edge®, Firefox®
	VMS/CMS	Speco Blue VMS, SecureGuard®
	Max. User Access	Max 64 users access
Features	Digital Zoom	Live and playback, free size
	S.M.A.R.T.	Temperature, power on time, bad sectors, and health



Speaker

Speaker	15W Outdoor Horn Speaker
Max Sound Pressure Level	113dB
Frequency Response	300Hz-8kHz
Low Frequency Range	500-KHz 3 10dB
High Frequency Range	400-12kHz 3 20dB
Harmonic Distortion	0.1@1kHz
Signal to Noise Ratio	91dB

Strobe Light

Material	Aluminum
Power	18W
Red and Blue	Yes
IP Rating	IP67

Network

Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45

Interfaces

Built-in mic




Built-in Speaker



DC 12V



Alarm In/Out



Products are in compliance with NDAA Section 889 Part B Guidelines. Google Chrome® and Firefox® use Java™ which requires an initial internet connection. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™, Google Play® and the Google Play logo® are trademarks of Google Inc. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 02/07/25

