

5.8 GHz Wireless Point to Point with DIP Configuration

AP2PLR

Wireless Link with DIP Configuration

Features

- Support DIP physical setting for simple configuration
- Easy installation, supports wall-mount and pole-mount
- Support PoE 24V power supply
- Support IEEE 802.11 a/n/ac protocol
- Wireless speed up to 867Mbps
- Equipped with IP65 shell to prevent harsh weather from rain, dust and sun
- Excellent transmitting power and receiving sensitivity up to 1.5 miles in ideal conditions



Specifications

Model	Specification
Wired Port	10/100/1000Mbps LAN*2
Wireless Bridge	IEEE802.11a,IEEE802.11n,IEEE802.11ac, IEEE802.3u
Power	POE 24V 1A
802.11a	Up to 54 Mbps
802.11n	Up to 300 Mbps
Management	WEP Management
	SNMP MIB
	Telnet
	Serial
Encryption	WEP 64/128bits,WPA,WPA2,802.1x
Operating Temperature	-22F - 140F
Storage Temperature	-58F - 170F
Humidity	≤95% (non-condensed)
Dimensions	Size: 8.07in x 8.07in x 5.21in
	Weight: 1.1lbs



Products are in compliance with NDAA Section 889 Part B Guidelines. ONVIF® is a trademark of Onvif, Inc. Chrome® and Firefox® use Java™, which requires an initial internet connection. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™ is a trademark of Google LLC. Google Play® and the Google Play logo® are trademarks of Google LLC. Amazon® is a trademark of Amazon.com, Inc. or its affiliates, used under license. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 3/6/26