



8MP 180° MultiSensor IP Bullet Camera with Digital Deterrent

Integrated with and

O8LMSB2

2.8mm lens fixed lens, white housing

Features

- 8MP 180° multisensor with image stitching
- Advance Analytics with multi-trigger support
- Up to 98ft IR night view distance
- 24/7 Full color options with white light
- Built-in micro SD card slot, up to 256GB
- IP66 compliant, weather resistant
- Digital Deterrent and red & blue light feature with two way audio
- EZ connect: instant remote access without network port forwarding

*with compatible Speco Blue Recorder

NDA COMPLIANT **ONVIF** | **GMST**



Included Junction Box



Camera Specifications

Image Sensor	1/2.7" Progressive Scan CMOS x2
Max. Resolution	4640 x 1760
Electronic Shutter	1/3 S - 1/1000000 S
Lens Type	Fixed lens
Min. Illumination	0.002 Lux (F1.6, AGC ON); 0 Lux with LED on
Lens	2.8 mm @F1.6
Field of View	Horizontal: 180° ; Vertical: 66°
Day/Night	Auto
Wide Dynamic Range	DWDR
BLC / HLC	Yes
Defog	Yes
S/N Ratio	> 50dB
IR Range	Up to 98 ft
White Light Range	Up to 65 ft
Image Adjustment	Pan: 0°-360°, Tilt: 0°-75°, Rotation: 0°-360°

Video Specifications

Main Resolution	H.265/H.264: 30FPS@8MP (4640x1760), 6MP (3264x1760), 5MP (2592x1944), 4MP (2688x1520), 3MP (2048x1536), 1080p, 720p
Sub Stream	2048x768/1600x608/1280x448/896x320 - 30fps (30FPS @60Hz)
Third Stream	1200x448/960x360/640x240/608x224 - 30fps (30FPS @60Hz)
Video Compression	H.265+/H.265/H.264+/H.264/MJPEG
H.264 Profiles	Baseline / Main / High
Bit Rate	64Kbps - 10Mbps
Bit Rate Type	VBR / CBR
Audio Compression	G.711A / U / R
Video Settings	ROI, Saturation, Brightness, Hue, Contrast, WDR, Sharpness, NR, etc.

Audio Specifications

Audio In	2CH Built-in Microphone, 3.5mm Input
Alarm Out	1CH Built -in Speaker (Left), 1 CH Built-in Speaker (Right), 3.5mm output
Alarm	1CH Alarm Input, 1CH Alarm Output

Network Specifications

Network Interface	RJ-45 (10M/100M adaptive Ethernet port)
Protocols	UDP, IPv4/IPv6, DHCP, NTP, RTP, RTSP, SMTP, FTP, DDNS, UPnP, HTTPS, QoS, P2P
Interface Protocol	ONVIF
Storage	Micro SD card (up to 256GB)
Smart Alarm	Motion detection, SMD, storage abnormal, face detection, intrusion detection, region entrance/exit, line crossing, video exception
Security	User authentication, HTTPS encryption, IP address filter, log recording

Operating & Unit Specifications

Power Supply	DC12V/PoE
Power Consumption	<10W
Operating Conditions	(-22°F - 140°F), humidity ≤95% (non-condensing)
Storage Conditions	(-22°F - 140°F), humidity ≤95% (non-condensing)
Ingress Protection	IP66
Dimensions	5.08 inches x 4.39 inches x 4.02 inches
Weight	Approx. 1.5 pounds

Client Specifications

Web Browser Support	Chrome, Edge, Safari, Firefox
PC Application	Speco Blue VMS
Mobile	Speco Blue App (iPhone® and Android™)



Dori Distance

Lens	Detect	Observe	Recognize	Identify
2.8mm	196ft(60m)	79ft(24m)	39ft(12m)	20ft(6m)

Optional Accessories



JB2
Alternate
Junction Box



PSW5
12VDC
Power Supply



CMT1
Corner Mount



PMT1
Pole Mount



CLTX1
Ceiling Mount
4" Extension



CLT2J
Ceiling Mount



WMT1
Wall Mount



CLTX2
Ceiling Mount
8" Extension

Camera Interfaces

3.5mm
Audio In



3.5mm
Audio Out



Built-in
Mic



Built-in
Speaker



DC 12V



Alarm
In/Out



Products are in compliance with NDAA Section 889 Part B Guidelines. ONVIF® is a trademark of Onvif, Inc. Chrome® and Firefox® use Java™, which requires an initial internet connection. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™ is a trademark of Google LLC. Google Play® and the Google Play logo® are trademarks of Google LLC. Amazon® is a trademark of Amazon.com, Inc. or its affiliates, used under license. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 4/7/26

