



1000BASE-T Copper SFP Transceiver

SFP1G

Features

- 1000BASE-T Copper Small Form Pluggable (SFP) transceivers, which supporting 1000Mbps data rate up to 328 feet reach over unshielded twisted-pair CAT 5 cable.
- Easy installation, plug and play, fully hot-pluggable with ESD protection.
- Used in fiber switches, routers, NIC, server or other fiber optic equipments with 1Gbps SFP ports. SFP MSA Compliant, IEEE 802.3ab Compliant
- Standard: 0 to +70°C



NDAA
COMPLIANT

Specifications

Description	Specification
Data Rate	1250Mbps
Tx Output Impedance	100Ohm
Rx Input Impedance	100Ohm
Supply Current	320mA
Input Voltage	3.3V
Rise/Fall Time	175psec
Operating Humidity	10% - 90% non-condensing
Storage Humidity	5% - 90% non-condensing
Cable Length	328 feet

Compatible with



P32S36GM2



P24S26G2



P16S182

Products are in compliance with NDAA Section 889 Part B Guidelines. ONVIF® is a trademark of Onvif, Inc. Chrome® and Firefox® use Java™, which requires an initial internet connection. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™ is a trademark of Google LLC. Google Play® and the Google Play logo® are trademarks of Google LLC. Amazon® is a trademark of Amazon.com, Inc. or its affiliates, used under license. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 3/18/26