

4MP 25X IP PTZ Camera with Advanced Analytics and Smart Tracking

Integrated with OCHEKT and immix

04P25X3

4.8-120mm 25x optical zoom lens, white housing

Features

- •Captures up to 4MP @ 30fps
- •Up to 25x optical zoom
- •Power with built in PoE++ support (IEEE 802.3bt)

or included 24VDC power adaptor

- •True Day/Night operation (IR cut filter)
- •IR range up to 400 ft. (depending on scene reflection)
- •True WDR Operation
- •Micro SD card slot up to 256GB (card not included)
- •Line Crossing, Video Blurring Detection•
- People/Vehicle Detection
- •Two-way audio support
- •IP67 compliant, weather resistant
- •Wall mount included
- •5 year warranty
- *with compatible Speco recorder

















NDAA Onvif*10000

Camera Specifications

Image Sensor	Progressive scan 1/2.7" CMOS, 4MP
Maximum Resolution	2560 x 1440
Minimum Illumination	0.01 lux @ F1.65, AGC ON; O lux with IR
Field of View	Horizontal: 55° ~ 2.4°; Vertical: 35° ~ 1.4°; Diagonal: 61.5°~2.8°
Image Settings	Flip, Mirror, Saturation, Brightness, Contrast, Sharpness
Compensation	True WDR/BLC/HLC
Day/Night	Smart IR with cut filter
Electronic Shutter Speed	1s ~ 1/10000s
DNR	3D DNR
Angle Adjustment	Pan: 0° ~ 360°; Tilt -3°~90°

Interfaces

Network	RJ45 jack
Power	AC/DC jack (24V)
Microphone Input	3.5mm
Audio Output	3.5mm
Card Slot	MicroSD, up to 256GB (card not included)
Alarm	1-CH alarm input; 1-CH alarm output
Reset	Yes
RS 485	No

Audio

Audio Compression G.711A/G.711U

Client Specifications

Web Browser Support	Chrome, Edge, Safari, Firefox
PC Application	SecureGuard® VMS, SecureGuard® CMS
Mobile	SecureGuard® Client (iPhone® and Android™), Speco Blue (iPhone® and Android™)

Network Specifications

Protocols	HTTP, HTTPS, IPv4/IPv6, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, IGMP, ICMP, DHCP, PPPoE
DDNS Support	Speco DDNS (No fee)
Security	User ID & Password protection, IP/MAC address filtering, digest authentication
User Access	Max. 16 simultaneous users (Actual num- ber of users may vary depending on bandwidth)

System Specifications

PoE	PoE++ (IEEE 802.3bt)
Analytics	Line crossing, Intrusion (people/motor vehicle/non-motor vehicle classification), face detection.
Exception Detection	Scene change, video blur detection
Alarm Triggers	Motion, Sensor alarm, Analytics, SD card error
Image Settings	Watermark, IP address filtering, video mask, password protection
Action Modes	Preset/Cruise/Auto Scan/Random Scan





Opertating & Unit Specifications

Power	PoE++ (IEEE 802.3bt), 24V AC/DC (power supply included)
Power Consumption	34W (max)
Operating Temperature	-22°F - 140°F
Operating Humidity	less than 95% RH (non-condensing)
Unit Dimensions	8.22" (Dia.) x 12.91" (H)
Unit Weight	8.31 lbs.
Certifications	IP66, FCC

Video Specifications

Main Stream Resolution	4MP/3MP/1080P/720P (1~ 30fps)
Sub Stream Resolution	1080P/1280x960/720P/D1/VGA/CIF (1-30fps)
Third Stream	D1/CIF/480x240 (1~30fps)
Compression	H.265, H.264, MJPEG
Multiple Streaming	3 streams



Camera Interfaces

3.5mm Audio In

3.5mm Audio Out

Alarm In/Out

12VDC/24 VAC In

Micro up to

NDAA

Google Play







Products are in compliance with NDAA Section 889 Part B Guidelines. ONVIF* is a trademark of Onvif, Inc. Chrome* and Firefox* use Java™, which requires an initial internet connection. Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark of Apple Inc. Android is a trademark of Google LLC. Google Play* and the Google Play logo* are trademarks of Google LLC. Amazon* is a trademark of Amazon.com, Inc. or its affiliates, used under license. Speco Technologies* is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Revised 6/14/25



