



Smart IP Video Intercom

SPIPIC

Features

- Two-way audio communication over IP networks
- SIP & Onvif protocol compatible
- Echo Cancellation, Automatic Gain Control, Noise Reduction
- PoE Power supply, 2M Pixels Camera
- TF Card Slot, Stable Alloy Shell
- Solid and durable, easy installation



Audio Specifications

Decoding	OPUS 48K, MP3 44.1 kHz, G.722 ADPCM 16 kHz, G.711 PCMU 8 kHz, G.711 PCMA 8 kHz
----------	--

Video Specifications

Video codec	H.264
Video resolution	Main stream 1080P and 720P, Sub stream D1 and CIF

Network Specifications

Security	Password protection, IP address filtering, Digest authentication, User access log, firewall
Network Protocol	SIP, ONVIF, HTTP, IPv4, DHCP, RTSP, RTP, RTCP, TCP, UDP, ARP, FTP, TFTP, NFS, NTP
Network Interface	10/100 Base-TX, RJ45
VoIP	Support SIP protocol for intergration with VoIP systimes, intergrated with SIP/PBX. Support SIP features: secondary/backend SIP server, IPv4 (IPv6 futhur). Support codecs: G711U, G711A, GSM, MP3, WAV.

Other Specifications

Material	Alloy panel Metal back cover
Power Supply	PoE or DC 12V
Interface	Interface 1* IO input, 1* IO output, 1* Relay (NO/COM/NC)
Dimensions	3.5in x 3.5in x 1.3in
Weight	0.63 pounds
Languages	English
Package includes	Smart IP Video Intercom & User Manual



Products are in compliance with NDAA Section 889 Part B Guidelines. ONVIF® is a trademark of Onvif, Inc. Chrome® and Firefox® use Java™, which requires an initial internet connection. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™ is a trademark of Google LLC. Google Play® and the Google Play logo® are trademarks of Google LLC. Amazon® is a trademark of Amazon.com, Inc. or its affiliates, used under license. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 10/15/25