



4MP IP Turret Camera with Analytics and White Light Intensifier

O4KT1

2.8mm fixed lens, white housing

Features

- Supports up to 4MP @ 20fps
- Full Color Capture in Day & Night with White LED
- H.265/H.264 compression supported
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- IR range: 98 ft. (depending on scene reflection)
- MicroSD card slot up to 256GB max (card not included)
- Built-in Microphone
- IP67 weather resistance
- 5 year warranty



Camera Specifications

Image Sensor	Progressive scan 1/3" CMOS, 4MP
Maximum Resolution	2560 x 1440 (4MP)
Field of View	98° (H), 53° (V), 111°(D)
Minimum Illumination	0.07 lux @ F.20, AGC ON; 0 lux with IR
Image Settings	Region of interest, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Defog, Sharpen, Noise Reduction
Day/Night	Smart IR up to 100' (depending on scene reflection)
Compensation	DWDR, BLC, HLC
Electronic Shutter Speed	1/3 - 1/100000 sec.
DNR	3D DNR
Angle Adjustment	Pan 0°-360°, Tilt 0°-75°, Rotation 0°-360°

Video Specifications

Main Resolution	2560x1440 @ 20fps
Sub stream Resolution	720p (1-15fps), D1, CIF (1-30fps)
Compression	H.265, H.264
Bitrate Control	VBR, CBR (64Kbps - 5Mbps)
Multiple Streaming	2 streams

Audio Specifications

Audio Compression	G.711A / G.711U
-------------------	-----------------

Network Specifications

Protocols	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, 802.1x, UPnP, HTTP, HTTPS, QoS
DDNS support	Speco DDNS (free of charge)
Security	User ID & Password protection, IP/Mac address filtering, digest authentication
User Access	Max. 4 simultaneous users

Interfaces

Ethernet	RJ45 Jack
Power	DC Jack
Audio In	Built-in Microphone
Audio Out	No
Card Slot	MicroSD, up to 256GB (not included)
Alarm In/Out	No
Reset	Yes

Client Specifications

Web Browser Support	Google Chrome®, Microsoft Edge®, Internet Explorer®, Apple Safari®, Firefox®
PC	Speco Blue VMS
Mobile	Speco Blue (iPhone® and Android™)

System Specifications

PoE	Standard (IEEE 802.3af)
Alert Triggers	Motion, Detection Events, SD card error
Image Settings	Watermark, IP address filtering, video mask, password protection, Corridor mode

Dori Distance

Lens	Detect	Observe	Recognize	Identify
2.8mm	58m(190ft)	23m(76ft)	12m(38ft)	6m(19ft)
3.6mm	79m(260ft)	32m(104ft)	16m(52ft)	8m(26ft)

Operating & Unit Specifications

Power	PoE, 12VDC (power supply not included)
Power Consumption	6W
Operating Temperature	-22°F - 140°F
Operating Humidity	Less than 95 % (non-condensing)
Unit Dimensions	4.2" (Dia.) x 3.75" (H)
Unit Weights	1.0 lb.
Certifications	FCC

Optional Accessories



POEINJ60
60W
PoE Injector



PSW5
12VDC
Power Supply



CMT1
Corner Mount



PMT1
Pole Mount



JB3
Junction Box



WMT1*
Wall Mount



CLT3*
Ceiling Mount



CLTX1
Ceiling Mount
4" Extension




CLTX2
Ceiling Mount
8" Extension

*Requires JB3


Camera Interfaces


Built In
Mic

DC 12V



RJ45 PoE





up to 256GB



Products are in compliance with NDAA Section 889 Part B Guidelines. ONVIF* is a trademark of Onvif, Inc. Chrome* and Firefox* use Java™, which requires an initial internet connection. Apple* and the Apple logo* are trademarks of Apple Inc., registered in the U.S. and other countries. App Store* is a service mark of Apple Inc. Android™ is a trademark of Google LLC. Google Play* and the Google Play logo* are trademarks of Google LLC. Amazon* is a trademark of Amazon.com, Inc. or its affiliates, used under license. Speco Technologies* is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 10/14/25

