



16-Channel Blue Series Surveillance Kit with 4TB Hard Drive, (12) 4MP IP Cameras with White Light Intensifier NDAA Compliant

ZIP16T12

16-Channel Network Video Recorder
with (16) Built-in PoE Ports (12) 4MP IP Cameras

Key Features:

- EZ Wizard:** Simple Network and System Setup
- EZ Record:** Setup Recording Resolutions and Recording Type
- EZ Copy:** Copy What You Are Playing onto a USB Flash Drive
- EZ App Setup:** Just Scan a QR Code with the App to View Your Cameras on Your Mobile Device

NRX Recorder Features:

- Real time recording up to 16MP resolution (8K) @ 30fps
- H.265 compression - Store up to 2x more than H.264
- 4K HDMI out and one VGA monitor output
- Facial Recognition and Comparison (With face detect cameras)
- Object and line crossing detection and alerts
- Smart Search - Specify a region on the camera view and search on changes in that area
- Remote viewing via web browser, or your mobile device
- Rack ears included

NDAA
COMPLIANT



O4KT1 Camera Features:

- Supports up to 4MP Resolution
- 2.8mm fixed lens, white housing
- True Day/Night Operation (IR Cut Filter)
- IR Range up to 98 ft. (Depending on scene reflection)
- Supports H.265/H.264 Compression
- IP67 Compliant, Weather Resistant
- Line Crossing + Region Intrusion with Human Detection

Camera Specifications

Image Sensor	Progressive scan 1/3" CMOS, 4MP
Resolution	2560 x 1440 (4MP)
Minimum Illumination	0.07 lux @ F.20, AGC ON; 0 lux with IR
Day/Night	Smart IR up to 100' (depending on scene reflection)
Compensation	Digital WDR, BLC, HLC
White Balance	Auto / Manual / Indoor
Electronic Shutter Speed	1/3 - 1/100000 sec.
DNR	3D DNR
IR Range	100 ft. (Depending on Scene Reflection)
Compression	H.265, H.264
Bitrate Control	VBR, CBR (64Kbps ~ 5Mbps)
Multiple Streaming	2 Streams
Ethernet	RJ45 Jack
Power	PoE/12VDC (Power Supply Not Included)
Power Consumption	<7W Max
Operating Temperature	-22°F ~ 140°F
Operating Humidity	0% - 95% (non-condensing)
Unit Dimensions	3.72 inches x 3.25 inches
Unit Weight	1.0 lbs.
Camera Model Number	O4KT1

NRX Recorder Specifications

Max. Bit Rate	128 Mbps
Max. Recording Resolution	16MP
PoE Ports	16
Monitor Output	1 HDMI, 1 VGA
Display Resolutions	VGA: 1024 x 768, 1280 x 720, 1280 x 1024, 1440 x 900, 1920 x 1080 HDMI: 1024 x 768, 1280 x 720, 1280 x 1024, 1440 x 900, 1920 x 1080, 2560 x 1440, 3840 x 2160/EDID
USB Ports	1 x USB 2.0 (Front), 1 USB 2.0, 1 USB 3.0 (Rear)
HDD Slots	2
Ethernet	RJ-45 (100/1000M) port
Remote Viewing	Google Chrome®, Microsoft Edge®, Firefox®, Safari®, Speco Blue VMS, Speco Blue App
Power Supply	48VDC, 1.5A (included)
Dimensions	380mm x 268mm x 45mm (15.0" x 10.6" x 2.0")
Model	N16NRX4TB

Box Contents

- NVR with 4TB Hard Drive
- (12) 4MP IP Cameras
- Remote Control (Batteries Included)
- USB Optical Mouse



Optional Accessories



JB3
Junction Box



PSW5
12VDC
Power Supply



CMT1
Corner Mount



PMT1
Pole Mount



CLTX1
Ceiling Mount
4" Extension



CLTX2
Ceiling Mount
8" Extension



WMT1*
Wall Mount



CLT3*
Ceiling Mount

Camera Interfaces

RJ45 PoE



DC 12V



Built-in Mic



micro
up to
256GB

NDAA
COMPLIANT

Onvif[®] | GMST

GET IT ON
Google Play

Download on the
App Store

available on
amazon appstore

Products are in compliance with NDAA Section 889 Part B Guidelines. Google Chrome[®] and Firefox[®] use Java[™] which requires an initial internet connection. This product has earned the UL[®] Listed Mark. Apple[®] and the Apple logo[®] are trademarks of Apple Inc., registered in the U.S. and other countries. App Store[®] is a service mark of Apple Inc. Android[™], Google Play[®] and the Google Play logo[®] are trademarks of Google Inc. Amazon[®] is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies[®] is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 07/28/26

