



16-Channel Blue Series Surveillance Kit with 4TB Hard Drive, (12) 8MP IP Cameras with White Light Intensifier NDAA Compliant

ZIP16T128B

16-Channel Network Video Recorder
with (16) Built-in PoE Ports (12) 8MP IP Cameras

Key Features:

- EZ Wizard:** Simple Network and System Setup
- EZ Record:** Setup Recording Resolutions and Recording Type
- EZ Copy:** Copy What You Are Playing onto a USB Flash Drive
- EZ App Setup:** Just Scan a QR Code with the App to View Your Cameras on Your Mobile Device



NRX Recorder Features:

- Real time recording up to 16MP resolution (8K) @ 30fps
- H.265 compression - Store up to 2x more than H.264
- 4K HDMI out and one VGA monitor output
- Facial Recognition and Comparison (With face detect cameras)
- Object and line crossing detection and alerts
- Smart Search - Specify a region on the camera view and search on changes in that area
- Remote viewing via web browser, or your mobile device
- Rack ears included

NDAA
COMPLIANT

O8KT1B Camera Features:

- Supports up to 8MP Resolution
- 2.8mm Wide Angle Lens
- True Day/Night Operation (IR Cut Filter)
- IR range: 98 ft. (depending on scene reflection)
- Supports H.265/H.264 Compression
- IP67 Compliant, Weather Resistant
- Line Crossing + Region Intrusion with Human Detection

NRX Recorder Specifications

Max. Bit Rate	128 Mbps
Max. Recording Resolution	16MP
PoE Ports	16
Monitor Output	1 HDMI, 1 VGA
Display Resolutions	VGA: 1024 x 768, 1280 x 720, 1280 x 1024, 1440 x 900, 1920 x 1080 HDMI: 1024 x 768, 1280 x 720, 1280 x 1024, 1440 x 900, 1920 x 1080, 2560 x 1440, 3840 x 2160/EDID
USB Ports	1 x USB 2.0 (Front), 1 USB 2.0, 1 USB 3.0 (Rear)
HDD Slots	2
Ethernet	RJ-45 (100/1000M) port
Remote Viewing	Google Chrome®, Microsoft Edge®, Firefox®, Safari®, Speco Blue VMS, Speco Blue App
Power Supply	48VDC, 1.5A (included)
Dimensions	380mm x 268mm x 45mm (15.0" x 10.6" x 2.0")
Model	N16NRX4TB

Camera Specifications

Image Sensor	Progressive scan 1/3" CMOS, 8MP
Resolution	3840 x 2160 (8MP)
Minimum Illumination	0.01 lux @ F16, AGC ON; 0 lux with Illumination on
Day/Night	Smart IR up to 100' (depending on scene reflec- tion)
Compensation	DWDR, BLC, HLC
Electronic Shutter Speed	1/3 - 1/100000 sec.
DNR	3D DNR
IR Range	100 ft. (Depending on Scene Reflection)
Compression	H.265, H.264
Bitrate Control	VBR, CBR (64Kbps - 5Mbps)
Multiple Streaming	2 Streams
Ethernet	RJ45 Jack
Power	12VDC/ PoE Standard (IEEE 802.3af)
Power Consumption	7W
Operating Temperature	-22°F ~ 140°F
Operating Humidity	0% - 95% (non-condensing)
Unit Dimensions	4.2" (Dia.) x 3.75" (H)
Unit Weight	1.0 lbs.
Camera Model Number	O8KT1B

Box Contents

- NVR with 4TB Hard Drive
- (12) 8MP IP Cameras
- Remote Control (Batteries Included)
- USB Optical Mouse



Optional Accessories



JB3B
Junction Box



PSW5
12VDC
Power Supply



CMT1B
Corner Mount



PMT1B
Pole Mount



CLTX1B
Ceiling Mount
4" Extension



CLTX2B
Ceiling Mount
8" Extension



WMT1B*
Wall Mount



CLT3B*
Ceiling Mount

Camera Interfaces

RJ45 PoE



DC 12V



Built-in Mic



micro
up to
256GB

NDAA
COMPLIANT

Onvif | GMST

GET IT ON
Google Play

Download on the
App Store

available on
amazon appstore

Products are in compliance with NDAA Section 889 Part B Guidelines. Google Chrome® and Firefox® use Java™ which requires an initial internet connection. This product has earned the UL® Listed Mark. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™, Google Play® and the Google Play logo® are trademarks of Google Inc. Amazon® is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 08/03/26

