



8-Channel Blue Series Surveillance Kit with 2TB Hard Drive, (6) 8MP IP Cameras with White Light Intensifier NDAA Compliant

ZIP8T2B8B

8-Channel Network Video Recorder with (8) Built-in PoE Ports
(6) 8MP IP Cameras

Key Features:

- EZ Wizard:** Simple Network and System Setup
- EZ Record:** Setup Recording Resolutions and Recording Type
- EZ Copy:** Copy What You Are Playing onto a USB Flash Drive
- EZ App Setup:** Just Scan a QR Code with the App to View Your Cameras on Your Mobile Device



Front Panel

Back Panel



Recorder Features:

- Up to 8MP Resolution For Live View, Recording and Playback
- Plug & Play – Get Video Automatically via the PoE Ports Without any Setup
- Supports Streams up to H.265 for Reduced Bandwidth and Reduced Hard Drive Space Requirements
- QR Code Based Network Setup for Easy Remote Access
- Free US-based DDNS Service
- 4K Monitor Output
- Gigabit Ethernet Port
- Built-in S.M.A.R.T technology (Self-Monitoring, Analysis and Reporting Technology for HDD)
- Remote Monitoring via PC, Mac and Mobile Apps
- 2TB Storage
- Expansion Available for up to 8 Cameras

Recorder Specifications

Max. Bit Rate	128 Mbps
Max. Recording Resolution	8MP
PoE Ports	8
Monitor Output	1 HDMI, 1 VGA
Display Resolutions	VGA: 1024 x 768, 1280 x 720, 1280 x 1024, 1440 x 900, 1920 x 1080 HDMI: 1024 x 768, 1280 x 720, 1280 x 1024, 1440 x 900, 1920 x 1080, 2560 x 1440, 3840 x 2160/EDID
USB Ports	2 x USB 2.0 (Rear)
HDD Slots	1
Ethernet	RJ-45 (100/1000M) port
Remote Viewing	Speco Blue App (IOS, Android) Speco Blue VMS (Windows, Mac)
Power Supply	48VDC, 1.5A (included)
Dimensions	10" (W) x 1.6" (H) x 8.7" (D)
Model	N8NRV2TB

O8KT1 Camera Features:

- Supports up to 8MP Resolution
- 2.8mm Wide Angle Lens
- True Day/Night Operation (IR Cut Filter)
- IR range: 98 ft. (depending on scene reflection)
- Supports H.265/H.264 Compression
- IP67 Compliant, Weather Resistant
- Line Crossing + Region Intrusion with Human Detection

Camera Specifications

Image Sensor	Progressive scan 1/3" CMOS, 8MP
Resolution	3840 x 2160 (8MP)
Minimum Illumination	0.01 lux @ F16, AGC ON; 0 lux with Illumination on
Day/Night	Smart IR up to 100' (depending on scene reflection)
Compensation	DWDR, BLC, HLC
Electronic Shutter Speed	1/3 - 1/100000 sec.
DNR	3D DNR
IR Range	100 ft. (Depending on Scene Reflection)
Compression	H.265, H.264
Bitrate Control	VBR, CBR (64Kbps - 5Mbps)
Multiple Streaming	2 Streams
Ethernet	RJ45 Jack
Power	12VDC/ PoE Standard (IEEE 802.3af)
Power Consumption	7W
Operating Temperature	-22°F ~ 140°F
Operating Humidity	0% - 95% (non-condensing)
Unit Dimensions	4.2" (Dia.) x 3.75" (H)
Unit Weight	1.0 lbs.
Camera Model Number	O8KT1B

Box Contents

- NVR with 2TB Hard Drive
- (6) 8MP Cameras
- USB Optical Mouse
- 48V Power Adapter



Optional Accessories



PSW5
12VDC
Power Supply



CMT1B
Corner Mount



PMT1B
Pole Mount



JB3B
Junction Box



WMT1B*
Wall Mount



CLT3B*
Ceiling Mount
*Requires JB3B



CLTX1B
Ceiling Mount
4" Extension



CLTX2B
Ceiling Mount
8" Extension

Camera Interfaces

