



Wi-Fi/Video Doorbell with IR & White light Face Detection

Integrated with **immix**

O4DB2

2.3mm fixed lens, black and silver housing

Features

- Max resolution: 4MP (2048x2048)
- Noise cancellation and echo suppression
- White light distance and 2-3ft IR distance
- 2.4GHz/5GHz dual band Wi-Fi
- Supports wired mechanical chime kit
- Supports wireless chime
- Built-in micro SD card slot, up to 256GB
- Built with IP66 Support
- USB-C Pigtail configuration



Built-In White Light To
Capture Faces In Color

Wireless Chime
Included



Camera Specifications

Image Sensor	1/2.7" Progressive Scan CMOS
Image Size	2048 x 2048
Electronic Shutter	1s ~ 1/100000s
IRIS Type	Fixed IRIS
MIN. Illumination	0.009lux @F2.2, AGC ON; 0lux with IR
WDR	Yes
BLC	Yes
HLC	Yes
DNR	3DNR
Lens	2.3mm @F2.2, Vertical FOV: 97.7°, Horizontal FOV: 97.7°, Diagonal FOV: 146.5°

Network Specifications

Network	100M RJ45
Audio	Built-in MIC x 1, built-in speaker x 1
User Count	Supports multiple users (up to 20 users)

Video Specifications

Main Stream	4MP(2048 x 2048), 2MP (1440 x 1440), 1080P(1920 x 1080), 960 x 960, 720P(1280 x 720), 480 x 480, D1, CIF.
Sub Stream	60Hz: D1/480 x 480/CIF(1-30fps), 50Hz: D1/480 x 480/CIF(1-25fps)
Third Stream	60Hz: D1/480 x 480/CIF(1-30fps), 50Hz: D1/480 x 480/CIF(1-25fps)
Compression	H.265/H.264/H.264-MPEG
Resolution	Varies by stream. Main stream resolutions are listed above. Sub and Third streams are D1/480 x 480/CIF

System Specifications

Alarm Triggers	Motion, sensor, analytics
Alarm Events	MicroSD recording, FTP upload
Analytics	Face detection, face capture, Tamper Detection



Operating & Unit Specifications

Power	DC 12V-24V/DC12V-V power supply; (You cannot use the existing wired chime) AC 16V-24V; 5V/1.5V (USB-C) power supply
PoE Power	Not supported
Power Consumption	< 5W
Working Environment	-30°C-50°C, Humidity: less than 95% (non-condensing)
Unit Dimensions	5.9in x 1.98in x 1.12in

Client Specifications

Web Browser Support	Chrome, Edge, FireFox
Mobile	Speco Blue App
Client	Speco Blue VMS

Included in Box

O4DB1	(1) Mounting Bracket, (1) Sun Shield Bracket, (1) Corner bracket, (1) Wired Chime Kit, (1) DB1CHIME
-------	---

Optional Accessories



DB1CHIME
Wireless
Doorbell Chime



Products are in compliance with NDAA Section 889 Part B Guidelines. Google Chrome® and Firefox® use Java™ which requires an initial internet connection. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™, Google Play® and the Google Play logo® are trademarks of Google Inc. Amazon® is used under license from Amazon.com, Inc. or its affiliates. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 6/16/26

