



Outdoor Camera Enclosure with PTZ Camera and Cellular

DD4A2TMZC

white housing

Enclosure Features

- Proactive Surveillance Solution
- Simple Installation
- Aluminum Enclosure Construction
- Stainless Steel Mounting Bracket
- 360W Power Control Module
- Dual embedded Analog Red/Blue Strobe Lights
- Three Unique Camera Views
- Audible Announcements
- Strobe Light Deterrent
- Hardwired solution connects to IP network switch & AC Power
- Built in Air Breaker
- Dual Cooling Fans with Temperature Controller
- Pole and Wall mounting brackets included
- Cradlepoint Cellular Router Included (SIM Card not Included)
- 5G Antenna Included

NDA COMPLIANT **ONVIF** | **GMST**

Power Specifications

Power Type	AC Power
Power Input	AC110 264V
Power Output	12V DC, 48V DC, 110V-277V AC

Mount and Add-On Specifications

Air Ventilation	2x temperature-controlled fan (12V)
Mounting	For antenna and speaker
Mounting Plates	3x camera mounting plates
Audio Add-Ons	Horn Speaker Installation Ready (top)
Wireless Add-Ons	Antenna Installation Ready (top)
Mount Add-Ons	PTZ Mount Included (bottom)

Light-Siren Specifications

Siren Type	IP PoE Light Siren
Light Colors	Blue, Red and White lights
Light Alarm Settings	Strobe or Steady Lights
Light-Siren Triggers	Camera-based Intruder Detection

Enclosure Specifications

Dimension	18W x 19.5H x 12D inches
Total Gross Weight	43.2 lbs.
Material	Aluminum and Stainless Steel combined
Mount	Pole Mount & Wall Mount included (3.5 - 10 in. Diameter Pole is ideal)

Kit Specifications

Included Video Products	(1) O4P4X2 PTZ Camera (2) O4TDD2M 4MP Visual Deterrent Turret Cameras
Included Audio Products	(1) 6" ASPC20W Amplified Speaker (1) JB3 Junction Box (1) IP Strobe Light Bar
Included Misc. Products	(1) P12GS Industrial 8 Port POE Din Rail Mount Switch



Camera Specifications

Camera Model	O4TDD2M
Image Sensor	Progressive scan 1/3" CMOS
Maximum Resolution	2592 x 1520 (4MP)
Field of View	Horizontal: 96°- 32.3°, vertical: 53.47°-19.6°, diagonal: 114°-36°
Minimum Illumination	0.02lux @ F1.4(AGC ON) ; 0 lux @ LED ON
White Balance	Auto, indoor, outdoor, manual
Compensation	True WDR (120dB), BLC, HLC
Day/Night	Smart IR or supplemental White LED
Electronic Shutter Speed	1/3s ~ 1/1000000s
Angle Adjustment	Pan: 0° ~ 360°; Tilt: 0° ~ 75°; Rotation: 0° ~ 360°

PTZ Camera Specifications

Camera Model	O4P4X2
Image Sensor	Progressive scan 1/2.7" CMOS, 4MP
Maximum Resolution	2592 x 1440
Field of View	Horizontal: 97° ~ 31°; Vertical: 51° ~ 18°; Diagonal: 115°-36°
Minimum Illumination	COLOR: 0.01 LUX, B/W 0.002 LUX @ (F1.6 AGC ON); 0 LUX WITH IR
Compensation	True WDR (120dB) / BLC / HLC
Day/Night	Smart IR with cut filter
Electronic Shutter Speed	1/30s - 1/30000s
PTZ Pan Range	0° - 355°
PTZ Tilt Range	-5° - 90°

Speaker Specifications

Speaker Model	ASPC20W
Frequency Response	500Hz-5kHz
Input Impedance	3-16 Ohms
Output Audio	20W max
Impedance	8 OHMS
Requires	10-16VDC (power supply not included)
Fuse	2A, 3AG
Dimensions	6" (W) x 6" (H) x 6.25" (L)
Weight	3 lbs.

Audio and AI Specifications

AI Audio Analytics	Emergency Keyword & Critical Sound Detection
Keyword Detection	"Help Me," "Help 911," "Emergency"
Critical Sound Detection	Gunshot, Glass Breaking, Screaming
Microphone	Integrated SmartMic
Audio Output	Integrated Speaker
Audible Alerts	Customizable Audio Warnings

Deterrent Specifications

Visual Deterrent	High-Intensity LED Light Bar
LED Colors	Red, White and Blue
Audible Deterrent	Built-in Speaker
Trigger	AI Audio Detection
Response	Visual and Audible Alert
Custom Audio	Supported

Included Speco Products



O4TDD2M
4MP IP Turret
Camera with
Audio, & Visual
Deterrent



O4P4X2
4MP 4X PTZ IP
Camera



ASPC20W
6" Amplified
Weatherproof
P.A. Speaker



JB3
Junction
Box



IPLS
IP Light Siren



ASL
Analog Strobe
Lights



P12GS
PoE Switch

NDAA
COMPLIANT

Onvif® | G M S T



Products are in compliance with NDAA Section 889 Part B Guidelines. ONVIF® is a trademark of Onvif, Inc. Chrome® and Firefox® use Java™, which requires an initial internet connection. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™ is a trademark of Google LLC. Google Play® and the Google Play logo® are trademarks of Google LLC. Amazon® is a trademark of Amazon.com, Inc. or its affiliates, used under license. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

Revised 10/1/26

