



# Outdoor Camera Enclosure with PTZ Camera

## DD4B2TMZ

white housing

### Enclosure Features

- Proactive Surveillance Solution
- Simple Installation
- Aluminum Enclosure Construction
- Stainless Steel Mounting Bracket
- 360W Power Control Module
- Three Unique Camera Views
- Audible Announcements
- Strobe Light Deterrent
- Hardwired solution connects to IP network switch & AC Power
- Built in Air Breaker
- Dual Cooling Fans
- Pole and Wall mounting brackets included

**NDA**A COMPLIANT **ONVIF** | **GMS**T



### Power Specifications

|              |            |
|--------------|------------|
| Power Type   | AC Power   |
| Power Input  | AC110 264V |
| Power Output |            |

### Mount and Add-On Specifications

|                  |                                       |
|------------------|---------------------------------------|
| Air Ventilation  | 2x temperature-controlled fan (12V)   |
| Mounting         | For antenna and speaker               |
| Mounting Plates  | 3x camera mounting plates             |
| Audio Add-Ons    | Horn Speaker Installation Ready (top) |
| Wireless Add-Ons | Antenna Installation Ready (top)      |
| Mount Add-Ons    | PTZ Mount Included (bottom)           |

### Light-Siren Specifications

|                      |                                 |
|----------------------|---------------------------------|
| Siren Type           | IP PoE Light Siren              |
| Light Colors         | Blue, Red and White lights      |
| Light Alarm Settings | Strobe or Steady Lights         |
| Light-Siren Triggers | Camera-based Intruder Detection |

### Enclosure Specifications

|                    |                                                                           |
|--------------------|---------------------------------------------------------------------------|
| Dimension          | 18W x 19.5H x 12D inches                                                  |
| Total Gross Weight | 49.5 lbs.                                                                 |
| Material           | Aluminum and Stainless Steel combined                                     |
| Mount              | Pole Mount & Wall Mount included<br>(3.5 - 10 in. Diameter Pole is ideal) |

### Kit Specifications

|                         |                                                                           |
|-------------------------|---------------------------------------------------------------------------|
| Included Video Products | (1) O4P25X3 PTZ Camera<br>(2) O4TDD2M 4MP Visual Deterrent Turret Cameras |
| Included Audio Products | (1) 6" ASPC20W Amplified Speaker<br>(1) IP Strobe Light Bar               |
| Included Accessories    | (1) Industrial 8-Port POE Din Rail Mount Switch                           |

### Camera Specifications

|                          |                                                                   |
|--------------------------|-------------------------------------------------------------------|
| Camera Model             | O4TDD2M                                                           |
| Image Sensor             | Progressive scan 1/3" CMOS                                        |
| Maximum Resolution       | 2592 x 1520 (4MP)                                                 |
| Field of View            | Horizontal: 96°- 32.3°, vertical: 53.47°-19.6°,diagonal: 114°-36° |
| Minimum Illumination     | 0.02lux @ F1.4(AGC ON) ; 0 lux @ LED ON                           |
| White Balance            | Auto, indoor, outdoor, manual                                     |
| Compensation             | True WDR (120dB), BLC, HLC                                        |
| Day/Night                | Smart IR or supplemental White LED                                |
| Electronic Shutter Speed | 1/3s - 1/100000s                                                  |
| Angle Adjustment         | Pan: 0° - 360°; Tilt: 0° - 75°;<br>Rotation: 0° - 360°            |

### PTZ Camera Specifications

|                          |                                                                   |
|--------------------------|-------------------------------------------------------------------|
| Camera Model             | O4P25X3                                                           |
| Image Sensor             | Progressive scan 1/2.7" CMOS, 4MP                                 |
| Maximum Resolution       | 2592 x 1440                                                       |
| Field of View            | Horizontal: 97° - 31°; Vertical: 51° - 18°;<br>Diagonal: 115°-36° |
| Minimum Illumination     | COLOR: 0.01 LUX, B/W 0.002 LUX @ (F1.6 AGC ON); 0 LUX WITH IR     |
| Compensation             | True WDR (120dB) / BLC / HLC                                      |
| Day/Night                | Smart IR with cut filter                                          |
| Electronic Shutter Speed | 1/30s - 1/30000s                                                  |
| PTZ Pan Range            | 0° - 355°                                                         |
| PTZ Tilt Range           | -5° - 90°                                                         |

### Speaker Specifications

|                    |                                      |
|--------------------|--------------------------------------|
| Speaker Model      | ASPC20W                              |
| Frequency Response | 500Hz-5kHz                           |
| Input Impedance    | 3-16 Ohms                            |
| Output Audio       | 20W max                              |
| Impedance          | 8 OHMS                               |
| Requires           | 10-16VDC (power supply not included) |
| Fuse               | 2A, 3AG                              |
| Dimensions         | 6" (W) x 6" (H) x 6.25" (L)          |
| Weight             | 3 lbs.                               |



Audio and AI Specifications

|                          |                                              |
|--------------------------|----------------------------------------------|
| AI Audio Analytics       | Emergency Keyword & Critical Sound Detection |
| Keyword Detection        | “Help Me,” “Help 911,” “Emergency”           |
| Critical Sound Detection | Gunshot, Glass Breaking, Screaming           |
| Microphone               | Integrated SmartMic                          |
| Audio Output             | Integrated Speaker                           |
| Audible Alerts           | Customizable Audio Warnings                  |

Deterrent Specifications

|                   |                              |
|-------------------|------------------------------|
| Visual Deterrent  | High-Intensity LED Light Bar |
| LED Colors        | Red, White and Blue          |
| Audible Deterrent | Built-in Speaker             |
| Trigger           | AI Audio Detection           |
| Response          | Visual and Audible Alert     |
| Custom Audio      | Supported                    |



Products are in compliance with NDAA Section 889 Part B Guidelines. ONVIF® is a trademark of Onvif, Inc. Chrome® and Firefox® use Java™, which requires an initial internet connection. Apple® and the Apple logo® are trademarks of Apple Inc., registered in the U.S. and other countries. App Store® is a service mark of Apple Inc. Android™ is a trademark of Google LLC. Google Play® and the Google Play logo® are trademarks of Google LLC. Amazon® is a trademark of Amazon.com, Inc. or its affiliates, used under license. Speco Technologies® is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation.

**Revised 10/1/26**

